

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

30-039-25489

Operator: UNOCAL – Bloomfield, NM Location: Unit M Sec. 12 Twp. 26N Rng. 7W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 231E DK/MV

Elevation: 6640 GR Completion Date: 10/11/95 Total Depth: 285' Land Type\* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: WET AT 140'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 1300 LBS., SWB PETROLEUM COKE

Depths anodes placed: 187' 194' 201' 208' 215' 222' 229' 236' 243' 250'

Depths vent pipes placed: 0' – 285', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 285'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee  
If Federal or Indian, add Lease Number.

RECEIVED  
NOV - 8 1995  
OIL CON. DIV.  
DIST. 3

10.95

**RANGE:**

**HOLE MADE:**

300

**COLOR**

Q

160

Sandstone

160

300

Shale and sandstone

REMARKS:

water at 190°

Brian E. Burge

## Driller

## Tool Dresser