

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

176E 30-039-25490

9- 30-039-06822

Operator: UNOCAL – Bloomfield, NM Location: Unit F Sec. 31 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 176E DK/MV, RINCON UNIT 9 PC

Elevation: 6625 GR Completion Date: 10/02/95 Total Depth: 300' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: NONE

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2800 LBS., SWB PETROLEUM COKE

Depths anodes placed: 125' 159' 165' 170' 189' 199' 206' 213' 220' 276'

Depths vent pipes placed: 0' – 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

JOB # 351-00355 P/L NAME (S), NUMBER (S) Rincon Unit # 176 E
 TOTAL VOLTS 14.3 AMPS 11.1 OHMS 1.28 DATE 10-2-95 NAME [Signature]

REMARKS (notes for construction log)
 300' of 1" PVC 200' perforated / 2800 lb of coke breeze

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
00	1.1		295	.2		490			685			
05	.9		300	1.0		495			690			
10	1.0		305			500			695			
15	1.2		310			505			700			
20	1.1		315			510			ANODE	DEPTH	NO	FULLY
25	1.3		320			515			#		COKE	COK'D
30	.6		325			520			1	276	6	1.2
35	.6		330			525			2	220	1.0	2.0
40	.2		335			530			3	213	1.1	2.1
45	1.2		340			535			4	206	1.2	2.5
50			345			540			5	199	1.3	2.3
55	.4		350			545			6	189	1.1	2.9
60	1.2		355			550			7	170	1.3	2.9
65	1.3		360			555			8	165	1.3	2.8
70	1.2		365			560			9	159	1.2	2.7
75	.7		370			565			10	125	1.5	3.0
80	.6		375			570			11			
85	.9		380			575			12			
90	1.1		385			580			13			
95	1.2		390			585			14			
100	1.3		395			590			15			
105	1.3		400			595			16			
110	1.2		405			600			17			
115	.8		410			605			18			
120	1.0		415			610			19			
125	?		420			615			20			
130	.2		425			620			21			
135	.2		430			625			22			
140	.2		435			630			23			
145	.3		440			635			24			
150	.2		445			640			25			
155	.2		450			645			26			
160	.2		455			650			27			
165	.3		460			655			28			
170	.3		465			660			29			
175	.6		470			665			30			
180	.4		475			670						
185	.2		480			675						
190	.1		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy 1

- Division Construction Services

95

INDEX

HOLE MADE:

300'

COLOR

Sandstone

60

120

shade

1720

140

Sand / shale

140

700

shale

200

220

Sandy. Shale

2.2.0

300

Sandstone / some shale

REMARKS:

Brian S. Buzza Driller

Tool Dressing

