

#81 30-039-07045
#155 30-039-07024
#253 30-039-24819

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Location: Unit Sec. 17 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced Rincon Unit #155(DK), 81(MV), & 253(EC)

Elevation 6549 Completion Date 9/18/90 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 80' deep, damp = 5' thick, fresh

Depths gas encountered: NONE

Type & amount of coke breeze used: 300' with carbo-60=99.9 coke breeze

Depths anodes placed: 175', 185', 195', 205', 215', 225'

Depths vent pipes placed: 0-300' deep

Vent pipe perforations: Laser cut slots from 100' to 300' deep.

Remarks: 3rd ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED

JAN 30 1991

OIL CON. DIV.
DIST. 3

COMPANY Unocal JOB NO. 731-00084 DATE: 9-18-90
 WELL: River Unit N° 155 (253) PIPELINE: Ø
 LOCATION: SEC. 17 TWP. 27 RGE. 6 CO. Rio Arriba STATE NM
 ELEV. 6549'6 FT: ROTARY 300 FT: CABLE TOOL _____ FT: CASING COKE 40
 GROUNDBED: DEPTH 300' FT. DIA. 6" IN. GAS _____ LBS. ANODES 6-LIDA ST 1.5/6

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH TOP ANODE
		E	I	R				
	Brown Clay + Sandstone							
100	First water 80' Deep							
5	Vent Pipe							
10			1.0					
15			.9					
20			.9					
25			1.0					
30			1.0					
35			1.1					
40	Grey Shale w/ some Sandstone		1.6					
45			1.5					
50			1.7					
55			1.7					
60			2.1					
65			2.0					
70			2.4					
75			2.4					6
80			2.9					
85			2.7					5
90			2.9					
95			2.8					4
200			2.8					
5			2.4					3
10			2.7					
15			2.7					2
20			2.6					
25			2.0					1
30			2.3					
35			1.6					
40	Hard Sandstone / Streaks of Grey Shale		1.8					
45			1.7					
50			1.8					
55			1.5					
60			1.6					
65			1.4					
70			1.4					
75			1.1					
80			1.0					
85			1.1					
90			1.0					
95			.9					
300	T + D							
5								

GROUNDED RESISTANCE: (1) VOLTS 12.35 - AMPS 8.1 - 1.52 OHMS

(2) VIBROGROUND _____ OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKE'S COMPANY

MO-TE DRILLING, INC.

DAY

Monday

DRILLER

P. A. B.

LEFT⁴ TOWN

ARRIVED FIELD

HELPER

فردی

LEFT FIELD

ARRIVED TOWN

HELPER

July

TOTAL FOOTAGE TODAY

RIG NO.

206

DATE _____

9-12-90

CLIENT

T. (Kno-Cel)

BEGIN WORK ON HOLE NO.

Pin # 253

AT

__FEET

BEGIN WORK ON HOLE NO.

AT

FEET

[illegible]

BIT RECORD

SIZE & MAKE	SERIAL NO.	FOOTAGE
10 1/2	1000000000	1000000000

CIRCULATION MATERIAL

QUAN.	UNIT	MATERIAL

NO. OF LOADS OF WATER

_SOURCE