

#21 30-039-07047

#156 30-039-07034

#256 30-039-24561

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Location: Unit Sec. 16 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced Rincon Unit No. 156, 256(FC), 21(MV)

Elevation 6661' Completion Date 8/29/90 Total Depth 300' Land Type* P

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 80' deep, damp=5' thick, fresh

Depths gas encountered: NONE

Type & amount of coke breeze used: 300' deep with carbo-60=99.9 carbon coke breeze

Depths anodes placed: 220', 230', 240', 250', 260', 270'

Depths vent pipes placed: 0-300' deep

Vent pipe perforations: 80' to 300' deep

Remarks: 2nd ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
JAN 30 1991
OIL CON. DIV.
DIST. 3

COMPANY Unocal JOB NO. 751-00084 DATE: 8-29-90
 WELL: Rincon unit No 156 PIPELINE:
 LOCATION: SEC. 16 TWP. 27 RGE. 6 CO. Rio Arriba STATE NM
 ELEV. 6661 FT: ROTARY 300 FT: CABLE TOOL _____ FT: CASING Carbo 40 ^{COKE}
 GROUNDED: DEPTH 300 FT. DIA. 6" IN. GAS _____ LBS. ANODES 6 Lida ST 1.6/50

DEPTH.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE		WITH COKE		ANODE NO.	DEPTH, TOP OF ANODES
		E	I	R	I	I	I	I		
0-40	Brown sand & chip shale									
40-60	Brown sandstone, Red & grey shale									
60	Frist/wate 80' Ramp									
100	Vent Pipe 80'									
5										
10										
15										
20	Grey sandstone w/some shale									
25										
30										
35										
40										
45										
50										
55										
60										
65										
70	Grey to dark grey shale									
75										
80										
85										
90										
95										
200										
5										
10										
15										
20										
25										
30										
35										
40										
45										
50										
55										
60										
65										
70										
75										
80										
85										
90										
95										
300	T 40									
5										

GROUNDED RESISTANCE: (1) VOLTS 12.47 - AMPS 8.1 - 1.54 OHMS

(2) VIBROGROUND _____ OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKENS COMPANY

MO-TE DRILLING, INC.

DAY Wednesday

DRILLER	R. B. B.	LEFT TOWN	ARRIVED FIELD
HELPER	L. Morris	LEFT FIELD	ARRIVED TOWN
HELPER	Joe L.	TOTAL FOOTAGE TODAY	

RIG NO. 201 DATE 8-29-90 CLIENT Chm. Cal

BEGIN WORK ON HOLE NO. Keokuk 254 AT _____ FEET

BEGIN WORK ON HOLE NO. 156 AT _____ FEET

[illegible]

BIT RECORD		
SIZE & MAKE	SERIAL NO.	FOOTAGE
1 1/2" "	21005	Blades
CIRCULATION MATERIAL		
QUAN.	UNIT	MATERIAL

NO. OF LOADS OF WATER _____ SOURCE _____

san juan repr farm,nm Form 219-6