RECEWED

submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

JUN 10 2008

Bureau of Land Management Farmington Field Office

Sundry Notices and Reports on Wells		
	5.	Lease Number
Type of Well	6.	USA SF-078266 If Indian, All. or
GAS		Tribe Name
Name of Operator	7.	Unit Agreement Name
BURLINGTON		
RESOURCES OIL & GAS COMPANY LP	0	
Address & Phone No. of Operator	8.	Well Name & Number Wood 3N
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
1 Location of Wall France, Co. T. D. M.		30-045-34655
4. Location of Well, Footage, Sec., T, R, M Unit J (NWSE), 1990' FSL & 1875' FEL, Section 17, T29N, R10W, NMPM	10.	Field and Pool
		Basin Dakota Blanco Mesaverde
	11.	County and State
		San Juan Co., NM
Subsequent Report Flugging Non-Routille Flactifing		RCVD JUN 12 '08 OIL CONS. DIV.
Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection		OIL CONS. DIV. DIST. 3
Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection		OIL CONS. DIV.
Casing Repair Water Shut off Conversion to Injection Casing Repair Water Shut off Conversion to Injection	thead to 3960 08. Pumped c, .4%Sodiur w/1% CaCl2 ters @ 22:40 TD) reached w/10bbl gelled c, 6.25pps LC	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 p2 FL-52A, & .25pps Cellophahrs on 05/27/08. 05/29/08. Circ hole RIH w/161 water & 2bbl FW. 05/30/08
Casing Repair Water Shut off Conversion to Injection Casing Repair Water Shut off Conversion to Injection	thead to 3960 08. Pumped c, .4%Sodiur w/1% CaCl2 ters @ 22:40 TD) reached w/10bbl gelled c, 6.25pps LC	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 p2 FL-52A, & .25pps Cellophahrs on 05/27/08. 05/29/08. Circ hole RIH w/161 water & 2bbl FW. 05/30/08
Casing Repair Water Shut off Conversion to Injection Casing Repair Water Shut off Conversion to Injection	thead to 3960 08. Pumped c, .4%Sodiur w/1% CaCl2 ters @ 22:40 TD) reached w/10bbl gelled c, 6.25pps LC	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 p2 FL-52A, & .25pps Celloph. hrs on 05/27/08. 05/29/08. Circ hole RIH w/16 d water & 2bbl FW. 05/30/08 M-1, 1% FL-52A. Drop plug & CEPTED FOR RECORD
Casing Repair Water Shut off	thead to 3960 08. Pumped c, .4%Sodiur w/1% CaCl2 ters @ 22:40 TD) reached w/10bbl geller to 6.25pps LC	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 pr. 1.2 FL-52A, & .25pps Cellophahrs on 05/27/08. 05/29/08. Circ hole RIH w/161 water & 2bbl FW. 05/30/08 M-1, 1% FL-52A. Drop plug & CCEPTED FOR RECORD OCCEPTED FOR RECORD OTT. JUN 1 1 2008
Casing Repair Water Shut off Conversion to Injection 8. Describe Proposed or Completed Operations 6/24/08 MIRU H&P 283. PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit. drilled a IH 96jts, 7", 20#, J-55, ST&C csg & 1jts 7", 23#,J-55, LT&C set @3936. RU cmt 05/27/0bbl FW. Pumped Lead 487sx (1037cf-185bbl) Premium Lite FM Class C, 8% Bentonite CM-1, 4% FL-52, .25 pps Cellophane Flakes. Tail –93 sx (128cf-23bbl) Type 3 Class C wakes. Dropped plug & displaced on 05/27/08. Circ 70 bbl cement to surface. RD cement 5/28/08 PT 7" casing to 1500# for 30 min, good test. RIH 6 ¼" bit. Drill ahead to 6633" (" csg 10.5# J-55 ST&C & set @ 6628". RU to cement 05/30/08 @07:00 hrs. Pre flush water 207sx (410cf-73bbl) Premium lite HS FM, .25pps Cellophane Flakes, .3% CD-32 splaced w/106 bbl, (first 10 bbls sugar water) FW. Plug down a@ 09:13 hrs on 05/30/08. D, RR, 05/30/08 @ 15:30hrs.	chead to 3960 08. Pumped c, .4%Sodiur w/1% CaCl2 ters @ 22:40 TD) reached w/10bbl gelle c, 6.25pps LC	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 pp. 1.2 FL-52A, & .25pps Cellopha hrs on 05/27/08. 05/29/08. Circ hole RIH w/161 water & 2bbl FW. 05/30/08 M-1, 1% FL-52A. Drop plug & CCEPTED FOR RECORD OCCEPTED FOR RECORD OTT. JUN 1 1 2008
Casing Repair Water Shut off Conversion to Injection 8. Describe Proposed or Completed Operations 8. June Proposed or Completed Operations 8. Describe Proposed or Completed Operations 8. June Proposed or Completed Operations 8. June Proposed or Completed Operations 8. June Proposed or Completed Operations 8. Jule Proposed or Completed Operations 9. Jule Proposed or Completion of Summary of S	head to 3960 08. Pumped c, 4%Sodiur w/1% CaCl2. ters @ 22:40 TD) reached w/10bbl gelled c, 6.25pps LC AC TO next report Ty Technicia	OIL CONS. DIV. DIST. 3 2. Circ hole. 10bbl FW, 10bbl Mud Clean & Metasillicate, 3% CaCl2, 5 p. 1.2 FL-52A, & .25pps Cellophishrs on 05/27/08. 05/29/08. Circ hole RIH w/16/1 water & 2bbl FW. 05/30/08 M-1, 1% FL-52A. Drop plug & CCEPTED FOR RECORD OCCEPTED FOR RECORD