(This space for Federal or State Office use)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CONDITION OF APPROVAL, if any:

APPROVED BY

RECEIVED

JUN 17 2008

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

BUREAU OF LAND MANAGEMENT Bureau of Land Management Farmington Field Office Sundry Notices and Reports on Wells 5. Lease Number USA -SF-079391 If Indian, All. or 6. Type of Well **Tribe Name GAS** 7. **Unit Agreement Name** Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANY LP San Juan 27-5 Unit 8. Well Name & Number 3. Address & Phone No. of Operator SJ 27-5 Unit 901 PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-039-30317 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool Basin Dakota / Blanco MV Unit E (SWNW), 1646' FNL & 1146' FWL, Sec. 08, T27N, R5W, NMPM Unit D (NWNW), 960' FNL & 1010' FWL, Sec. 08, T27N, R5W, NMPM Rio Arriba Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Notice of Intent X Other - Casing Report Abandonment Change of Plans Subsequent Report Plugging Non-Routine Fracturing RCVD JUN 24'08 Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection OIL CONS. DIV. 13. Describe Proposed or Completed Operations DIST. 3 06/05/08 AWS 184. PT csg to 600# 30 min. 06/06/08 RIH w/8 3/4 bit, Tag cmt @ 176', D/O cmt and drilled ahead To 3855'. Circ hole. 06/09/08 RIH w/91jts, 7", 23#, L-80, LT&C csg set @ 3842'. RU cmt. Pumped 10bbl Gel Mud, 10bbl FW. Scavenger 20sx (60cf-11bbl) Premium Lite w/3%CaCl, .25pps Cello -Flakes, 5pps LCM-1,4%FL-52, 8% Bentonite,.4% SMS. Lead - 510sx (1086cf-193bbl) Premium Lite w/3%CaCl, .25pps Celloflakes, 5pps LCM-1, .4% Fl-52,8%Bentonite,.4% SMS. Followed by Tail – 90sx (124cf-22bbl) Premium Lite w/8% Bentonite, 5%LCM-1, 25pps Cello-Flakes, 4% FL-52, 4% SMS. Dropped plug & displaced w/ 150bbl of H20. 80bbls cmt to surface. Bumped Plug 21:22HRS @1400PSI, plug held. 06/10/08 PT csg to 1500#/30 min. - Good Test, RIH w/6 1/4" bit, RIH, tag cement @3789', D/O cmt & drilled ahead to 7931' (TD), TD reached on 06/13/08.RIH w/192jts, 4 1/2:", 11.6#, L-80, LT&C & set @ 7930'. 06/13/08 RU cement. Pre flush w/ 10bbl Chem Wash, 2bbl FW. Scavenger - 10sx (30cf-5bbl) Premium Lite w/.25pps Cello-Flakes, .3%CD-32, 6.25ppsLCM, 1%FL-52. Tail - 300sx (614cf-109) Premium Lite w/.25pps Cellophane Flakes, .3% CD-32, 6.25pps LCM-1,1% FL-52. Dropped Plug & displaced w/123bbl bump plug @1600 PSI @6:21hrs. RD, RR @ 12:00hrs on 06/14/08/ PT will be conducted by the completion rig & reported on the next report. 14. I hereby certify that the foregoing is true and correct. 326-9568 Sasha Spangler Title Regulatory Technician Date 06/17/08 ACCEPTED FOR RECORD

Title

MMOCD

FARMINGTON FIELD OFFICE BY _______