District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

 $1000\ Rio\ Brazos\ Rd$  , Aztec, NM  $\ 87410$ 

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

 $\label{eq:June 16} June~16,~2008$  For temporary pits, closed-loop sytems, and below-grade

Form C-144

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
DI 1	P 2 2 2 2 2 2 2 3 4 4 4 4 4 5 4 5 5 5 5 5 5 5 5 5 5 5 5

Instructions: Please submit one application (Form C-144) per individue Please be advised that approval of this request does not relieve the operator of liability environment. Nor does approval relieve the operator of its responsibility to comply with	ity should operations result in pollution of surface water, ground water or the
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
	RCVD JUL 15'08
Address: PO Box 4289, Farmington, NM 87499	nil cons. Div.
Facility or well name: Southeast Cha Cha #38	
	D Permit Number: DIST. 3
	Range: 13W County: San Juan ongitude: 108.21159000' W NAD: X 1927 1983 al Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC  Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined  Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced  Seams: Welded Factory Other Volume: bbl Dimensions: L xW xD	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC  Drying Pad X Tanks Haul-off Bins Other:  Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC  Other:  Seams: Welded Factory Other:  Volume: 500 bbl 104 yd3  Dimernsions: Length 45' x Width 10'
Below-grade tank:  Volume:bbl  Type of fluid:  Tank Construction Material:  Secondary containment with leak detection  Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off  Visible sidewalls and liner  Visible sidewalls only  Other: mil HDPE PVC  Other:	Fencing: Subsection D of 19.15.17.11 NMAC  Chain link, six feet in height, two strangs of barbed wire at top  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Netting: Subsection E of 19.15.17.11  Screen Netting Other  Monthly inspections  Signs: Subsection C of 19.15 17 11 NMAC  12"x 24", 2" lettering, provided Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19.15.3.103 NMAC
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	NA					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applied to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	∐NA					
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No				
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No				
- Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.	Yes	□No				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.	□Yes	□No				
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division						
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	∐Yes	∐No				
Within a 100-year floodplain - FEMA map	Yes	□No				
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.	9 NMAC	***				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do		e attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number: or Permit						
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.11 NMAC  Toperating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number:						

Form C-144 Oil Conservation Division Page 2 of 4

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC						
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Climatological Factors Assessment						
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC						
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC						
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC						
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC						
Quality Control/Quality Assurance Construction and Installation Plan						
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC,  Nuisance or Hazardous Odors, including H2S, Prevention Plan						
Emergency Response Plan						
Oil Field Waste Stream Characterization						
Monitoring and Inspection Plan						
Erosion Control Plan						
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Closure Fian - based upon the appropriate requirements of Subsection C of 19.13.17.9 (wife						
Proposed Closure: 19.15.17.13 NMAC						
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Altern	native					
Proposed Closure X Waste Excavation and Removal						
On-site Closure Method (only for temporary pits and closed-loop						
In-place On-site Trench						
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	or					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC						
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate						
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of						
approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.						
Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer, vWATERS detabase search, USGS: Data obtained from nearby wells.	☐Yes ☐No					
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells	NA NA					
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste	∏NA ∏Yes ∏No					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul>	□NA □Yes□No □NA					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> </ul>	NA Yes No NA Yes No					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul>	NA Yes No NA Yes No NA NA NA					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal</li> </ul>	NA Yes No NA Yes No					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> </ul>	NA Yes No NA Yes No NA NA NA					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> </ul>	NA Yes No NA Yes No NO NA Yes NO					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> </ul>	NA Yes No NA Yes No NA NA NA					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial</li> </ul>	NA Yes No NA Yes No NO NA Yes NO					
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No NA Yes No					
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> </ul>	NA Yes No NA Yes No NA Yes No NA Yes No					
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time</li> </ul>	NA Yes No NA Yes No NA Yes No NA Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No NA Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	NA Yes No NA Yes No NA Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No Yes No					
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended         <ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul> </li> <li>Within 500 feet of a wetland.</li> <li>proposed site&lt;</li></ul>	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended         <ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul> </li> <li>Within 500 feet of a wetland.</li> <li>proposed site&lt;</li></ul>	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No					
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - 1WATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> </ul>	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended             <ul></ul></li></ul></li></ul>	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					

Form C-144 Oil Conservation Division Page 3 of 4

to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.  [V] Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC.							
X   Protocols and Procedures - based upon the appropriate requirements of 19 15.17.13 NMAC   Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC							
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)							
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15.17.13 NMAC							
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17.13 NMAC							
X Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17 13 NMAC							
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.							
Disposal Facility Name: Envirotech, Basin Disposal Disposal Facility Permit Number: MM-01-0011 & NM-01-005							
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.							
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC							
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC							
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15 17.11 NMAC							
Protocols and Procedures - based upon the appropriate requirements of 19 15 17.13 NMAC							
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC							
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be							
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC							
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC							
Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.							
Name (Print) Crystal Tafoya Tıtle Regulatory Technician							
Signature: Lalaya Date: 7/14/2008							
e-mail address: crystal.tafoya@conocoph@lips.com  Telephone: 505-326-9837							
OCD Approval: Permit Application (including closure plan) Closure Plan (only)							
OCD Approval: Permit Application (including closure plan)  OCD Representative Signature: Signature: Approval Date: 7-/5-08							
OCD Representative Signature: Brand Sell Approval Date: 7-/5-08  Title: En vivo Spec OCD Permit Number							
OCD Representative Signature: Brand Sell Approval Date: 7-/5-08							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:  See Sold Approval Date: 7-/5-08  Title: En sivo Spec OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:    Bread   Gall   Gal							
OCD Representative Signature:    Approval Date: 7-/5-08							
OCD Representative Signature:    Second   Second							
OCD Representative Signature:    Approval Date: 7-/5-08							
Approval Date: 7-/5-08  Title: En Silo Spec. OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique							
Title:							
Approval Date: 7-/5-08  Title: En Silo Spec. OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique							
Title:							
Approval Date: 7-/5-08  Title: En Sivo Spec  OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude. NAD: 1927 1983							
Approval Date: 7-/5-08  Title: Environ and Removal  On-Site Closure completion): Subsection K of 19 15 17 13 NMAC    Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC    Closure Completion Date:							
OCD Permit Number    Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC   Closure Method:							

Form C-144 Oil Conservation Division Page 4 of 4

## OIL CONSERVATION DIVISION

STATE OF VEVL MEXICO ERGY AND MINERALS DEPARTMENT

### P. O. UOX 2088 SANTA FE, NEW MEXICO 87501

Form C-107 keylied 10-1-7:

		All distances must be fo	rom the cuter hounderly	· of the Seetler						
Operator			Lease			Well No.				
HICKS ENCO			SE CHA CHA			38				
Unit Letter	Section	Township	Range	County						
L	22	28N	13W	San .	Juan					
Actual Footage Location of Well:										
210C	· · · · · · · · · · · · · · · · · · ·	outh line and	<del></del>	feet from the Wi		line				
Ground Level Elev.	Producing For		Pool		Dedico	ited Acreage;				
6043	Gallup		Cha Cha			8() Acres				
<ol> <li>Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.</li> <li>If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and rayalty).</li> <li>If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consoli-</li> </ol>										
dated by c	ommunitization,	unitization, force-pool nswer is "yes," type owners and tract des	ling.etc?							
this form i No allowat	f necessary.) ole will be assign	ed to the well until a ) or until a non-standa	ll interests have bee	en consolidate	d (by communit	ization, unitization,				
			[		CER	TIFICATION				
	I		!		that we					
	1		l			that the Information can-				
	1					true and complete to the				
	ı				Desi or my know	ledge and bellef.				
	1		1		Milla	- Cin				
	İ		ŧ		Name					
				[ ]	J D Hicks					
	1		1		Position					
	1		I	1 1	President					
	I		1		Company	_				
	1		1		Hicks Enc	o, Inc.				
	Sec		t	.   01	Date 10 /1 = /00					
	l Dec	•	1		12/15/80					
			I							
		22	(	San	• 1	that the well location				
990' ⊚	. ]		l 1	CV TO DY		lat was plotted from field				
ľ	- 1		í	<b>\</b>	}	surveys mode by me or distant and that the same				
			ı	$\mathbf{V} \leq \mathbb{Z}_{>0}$		rrect to the best of my				
			1	N [5]	knowledge and i	1				
	I		1		A Company and a					
<del>  +</del>		<del></del>								
			1		Data Survey	Lu lu				
5.	- 1		Į.		Date Surveyed	The state of the s				
21001			İ		December 2					
			1		Registered Profes and Wand Burve	sional Engineer				
	1		1	1 1	2 5 4					
		1	f.		della	TUYON 1				
S			1		Certificate No.	er or a				
· • ·	Sca	le: l"=1000'		,	3950	1000				

# Burlington Resources Oil & Gas Company, LP Closed-loop Plans

#### **Closed-loop Design Plan**

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

#### **Closed-loop Operating and Maintenance Plan**

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

#### **Closed-loop Closure Plan**

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.