District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave, Artesia, NM 88210

District III

1000 Rio Brazos Rd , Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 16, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or RCVD JUL 17'08 Proposed Alternative Method Permit or Closure Plan Application All COMS. DIV.

X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method DIST. 3 Type of action: Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of hability should operations result in pollution of surface water, ground water or the environment. Not does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances

OGRID#: 14538 Operator: Burlington Resources Oil & Gas Company, LP Address: PO Box 4289, Farmington, NM 87499 Facility or well name: San Juan 32-9 Unit #43A OCD Permit Number: API Number: 30-045-22900 U/L or Qtr/Qtr: D(NWNW) Section: 2 Township: 10W 31N Range: County: San Juan Center of Proposed Design: Latitude: 36.93120' N Longitude: 107.858030' W NAD: X 1927 1983 Private Tribal Trust or Indian Allotment Surface Owner: State Federal Pit: Subsection F or G of 19.15.17.11 NMAC X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC Drying Pad X Tanks Haul-off Bins Other: Drilling Workover Temporary: Permanent Emergency Cavitation Lined Unlined Liner type: Thickness ____ mil LLDPE HDPE PVC Unlined Other: Liner type: Thickness mil LLDPE HDPE PVC String-Reinforced Seams: Welded Factory Other: Seams: Welded Factory Other Volume: yd3 Volume: bbl Dimensions: L xW xD Dimernsions: Length 45' x Width Fencing: Subsection D of 19.15.17.11 NMAC Below-grade tank: Subsection I of 19.15 17.11 NMAC Volume: bbl Chain link, six feet in height, two strangs of barbed wire at top Type of fluid: Four foot height, four strands of barbed wire evenly spaced between Tank Construction Material: one and four feet Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting Other Visible sidewalls and liner Monthly inspections Visible sidewalls only Subsection C of 19 15.17.11 NMAC Signs: Other: 12"x 24", 2" lettering, provided Operator's name, site location, and Liner type: Thickness: mil HDPE emergency telephone numbers Other: X Signed in compliance with 19.15.3.103 NMAC Alternative Method: **Administrative Approvals and Exceptions:** Submittal of an exception request is required. Exceptions must be Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. submitted to the Santa Fe Environmental Bureau office for consideration of approval. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No				
 (Applied to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	∐NA					
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No				
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No				
- Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.	Yes	□No				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	□ Vas					
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	∐Yes					
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	□No				
Within a 100-year floodplain	□Yes	□No				
- FEMA map						
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the definition of the following items must be attached to the application.	ocuments ar	e attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number: or Permit						
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9						
Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Querating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.19 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number:						

Form C-144 Oil Conservation Division

Page 2 of 4

Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attacked. [] Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC							
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC	ched.						
	Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC						
Situng Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC							
Climatological Factors Assessment							
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC							
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC							
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC							
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC							
Quality Control/Quality Assurance Construction and Installation Plan							
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
Nuisance or Hazardous Odors, including H2S, Prevention Plan							
Emergency Response Plan							
Oil Field Waste Stream Characterization							
Monitoring and Inspection Plan							
Erosion Control Plan							
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Proposed Closure: 19.15.17.13 NMAC Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alternative Proposed Closure X Waste Excavation and Removal On-site Closure Method (only for temporary pits and closed-loop In-place On-site Trench							
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for	r						
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.							
Ground water is less than 50 feet below the bottom of the buried waste.	□Vaa □Na						
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	∐Yes∐No ∐NA						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - IWATERS database serach; USGS; Data obtained from nearby wells							
Ground water is between 50 and 100 feet below the bottom of the buried waste	□NA □ □Yes □No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - tWATERS database serach; USGS; Data obtained from nearby wells	□NA □Yes □No □NA						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.	NA Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	NA						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	NA						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	NA						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No NA Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No NA Yes No Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No						
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - tWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No						

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NI						
to the closure plan. Please inducfate, by a check mark in the box, that the documents are attached.						
X Protocols and Procedures - based upon the appropriate requirements of 19 15 17.13 NMAC						
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC						
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15.17.13 NMAC						
X Re-vegetation Plan - based upon the appropriate requirements of Subse	1					
X Site Reclamation Plan - based upon the appropriate requirements of Su						
	MIT					
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off F facilities for the disposal of liquids, drilling fluids and drill cuttings.	tins Only: (19 15.17.13 D NMAC) Instructions: Please identify the facility or					
Disposal Facility Name Envirotech, Basin Disposal	Disposal Facility Permit Number: NM-01-0011 & NM-01-005					
On-Site Closure Plan Checklist: (19 15 17.13 NMAC) Instructions: Each of the check mark in the box, that the documents are attached.	following items must bee attached to the closure plan. Please indicate, by a					
Siting Criteria Compliance Demonstrations - based upon the appropria	te requirements of 19.15.17.10 NMAC					
Proof of Surface Owner Notice - based upon the appropriate requirement	•					
Construction and Design of Burial Trench (if applicable) based upon the						
Protocols and Procedures - based upon the appropriate requirements of	•• •					
Confirmation Sampling Plan (if applicable) - based upon the appropria						
Waste Material Sampling Plan - based upon the appropriate requireme						
Disposal Facility Name and Permit Number (for liquids, drilling fluids						
Soil Cover Design - based upon the appropriate requirements of Subse						
Re-vegetation Plan - based upon the appropriate requirements of Subsci						
Site Reclamation Plan - based upon the appropriate requirements of Su						
Operator Application Certification:						
I hereby certify that the information submitted with this application is true, accurate	e and complete to the best of my knowledge and belief					
Name (Print). Crystal Tafoya	Title. Regulatory Technician					
1 10-						
Signature: Cyptul Japapa	Date: 7/16/2008					
e-mail address crystal tafoya@conocophilips.com	Telephone: 505-326-9837					
OCD Approval: Permit Application (including closure plan)	losure Plan (only)					
	losure Plan (only)					
OCD Representative Signature: Brandon Donald	Approval Date: 7-18-08					
OCD Representative Signature: Brandon Bonds Title: Enviro 15pec	Approval Date: 7-18-08 OCD Permit Number					
OCD Representative Signature: Brandon Donald	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC					
OCD Representative Signature: Brandon Bonda Title: Enviro 15pec	Approval Date: 7-18-08 OCD Permit Number					
OCD Representative Signature: Title: Enviro Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:					
OCD Representative Signature: Title: Second Second Second Second Subsection K of 19 15 Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alternative Signature: Alternative Signature: OCD Representative Signature: Description: The second Se	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC					
OCD Representative Signature: Title: Enviro Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:					
OCD Representative Signature: Title: Sumbles Title: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items:	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
OCD Representative Signature: Title: Section Solution Closure Report (required within 60 days of closure completion): Subsection K of 19 15 in the section K of 19 15 in th	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
OCD Representative Signature: Title: Sumbles Title: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items:	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
OCD Representative Signature: Title: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 : Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
OCD Representative Signature: Title: Section Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable)	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the					
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alterial If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude:	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude. NAD: 1927 1983 e, accurate and complete to the best of my knowledge and belief. I also certify that the					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude. NAD: 1927 1983 e, accurate and complete to the best of my knowledge and belief. I also certify that the					
Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-8 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude. NAD: 1927 1983 e, accurate and complete to the best of my knowledge and belief. I also certify that the proved closure plan					

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACERAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section

Coerator EL	PASO NATUR	AL GAS CO		ease SAN JU	AN 32	-9 UNIT	(E-7025)	Well No.	
Unit Letter D	Section 2	Tewnship 31 NOR	ГН	Range 10 W		County SAN	JUAN		
Actual Factage La 1150		NORTH	line and	1055	feet	t from the	WEST	line	
Ground Level Elev. 6126		Formation VERDE	P	ool . BL	NCO ME	SA VERD	1	Dedicated Avereo	ge: Acres
2. If more the interest and r3. If more the interest and r	e acerage dedica nan one lease is oyalty), nan one lease of ization, unitizati	dedicated to the	ne well, outlin	ne each and	d identify	y the own	nership there	eof (both as t	_
(X) Yes (No I	f answer is "ye	s," type of co	onsolidati on	Un	nitizat	ion	***************************************	
If answer is '	'no," list the owr	ners and tract d	escriptions wh	hich have o	ctually o	consolidat	ed. (Use rev	erse side of th	nis Form if
	will be assigned herwise) or until					•		•	•

CERTIFICATION

I hereby certify that the information contained

herein is true and complete to the best of my knowledge and belief. Name Drilling Clerk Position Paso Natural Gas Co. Company Date I hereby certify that the well location shown on this plat was plotted from field notes of sectoal N surveys made by me or under my supervision, and E-286-27 that the same is truscand correct to the best of my knowledge and belief. MAES P. LEES 0 = 45 Date Surveyed Registerez Professional Engineer ana/or Land Surveyor James P. Leese Certificate No. 1463 FARMINGTON, N. M. SAN JUAN ENGINEERING COMPANY,

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.