### State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 16, 2008

<u>District II</u> 1301 W Grand Ave., Artesia, NM 88210 <u>District III</u> Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

1000 Rio Brazos Rd., Aztec, NM 87410

District IV
1220 S St Francis Dr., Santa Fe, NM 87505

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Proposed Alternative Method Per	Below-Grade Tank, or RCVD JUL 17'08 mit or Closure Plan Application OIL CONS. DIV.					
Type of action: X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.						
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538					
Address: PO Box 4289, Farmington, NM 87499						
Facility or well name: San Juan 32-9 Unit #223						
API Number: 30-045-28887 OC	CD Permit Number:					
U/L or Qtr/Qtr: L(NWSW) Section: 12 Township: 31N	Range: 10W County: San Juan					
	ongitude: 107.838860' W NAD: X 1927 1983 al Trust or Indian Allotment					
Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC					
Temporary: Drilling Workover	Drying Pad X Tanks Haul-off Bins Other:					
Permanent Emergency Cavitation	Lined Unlined					
Lined Unlined	Liner type: Thickness mil LLDPE HDPE PVC					
Liner type: Thickness mil LLDPE HDPE PVC	Other:					
Other String-Reinforced	Seams: Welded Factory Other:					
Seams: Welded Factory Other	Volume: 500 bbl 104 yd3					
Volume: bbl Dimensions: L xW xD	Dimernsions: Length 45' x Width 10'					
Below-grade tank: Subsection Lof 19.15.17 11 NMAC	Fencing: Subsection D of 19.15 17.11 NMAC					
Volume: bbl	Chain link, six feet in height, two strangs of barbed wire at top					
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between					
Tank Construction Material:	one and four feet					
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11					
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other					
Visible sidewalls and liner	Monthly inspections					
V <sub>1</sub> sible sidewalls only	Signs: Subsection C of 19 15.17.11 NMAC					
Other:	12"x 24", 2" lettering, provided Operator's name, site location, and					
Liner type: Thickness: mil HDPE PVC	emergency telephone numbers					
Other:	X Signed in compliance with 19.15.3.103 NMAC					
Alternative Method:	Administrative Approvals and Exceptions:					
Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please					
submitted to the Santa Fe Environmental Bureau office for consideration	refer to 19.15.17 NMAC for guidance.					
of approval.	Please check a box if one or more of the following is requested, if not leave blank:					
	Administrative approval(s): Requests must be submitted to the					
	appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan)					
	Exception(s): Requests must be submitted to the Santa Fe					
	Environmental Bureau office for consideration of approval.					

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		□No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site		□No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	$\square_{No}$				
(Applied to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA	LJ- '-				
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No				
- NM Office of the State Engineer - ıWATERS database search; Visual inspection (certification) of the proposed site.						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No				
- Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.	Yes	□No				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	□Yes	$\Box_{N_0}$				
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division						
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map		∐No				
Within a 100-year floodplain	Yes	□No				
- FEMA map						
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.	9 NMAC	,				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number: or Permit						
Closed-loop Systems Permit Application Attachment Checklist:  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number:						

	• •				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.					
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC					
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC					
Climatological Factors Assessment					
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC					
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC					
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC					
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC					
Quality Control/Quality Assurance Construction and Installation Plan					
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
Nuisance or Hazardous Odors, including H2S, Prevention Plan					
Emergency Response Plan					
Oil Field Waste Stream Characterization					
Monitoring and Inspection Plan					
Erosion Control Plan					
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Proposed Closure: 19.15.17.13 NMAC					
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alter	native				
Proposed Closure X Waste Excavation and Removal					
On-site Closure Method (only for temporary pits and closed-loop					
In-place On-site Trench					
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	for				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC					
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of					
approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.					
Ground water is less than 50 feet below the bottom of the buried waste.	☐Yes ☐No				
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐Yes ☐No ☐NA				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> </ul>	NA Yes No NA Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul>	□NA □Yes□No □NA				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> </ul>	NA Yes No NA Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> </ul>	NA Yes No NA Yes No No NA No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> </ul>	NA Yes No NA Yes No No NA No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial</li> </ul>	NA Yes No NA Yes No No NA No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic</li> </ul>	NA Yes No NA Yes No NA Yes No NA Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended         <ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li></ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li></ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> </ul>	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No				
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Witten confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> <li>Within an unstable area.</li> <li>Engineering measures incor</li></ul>	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No				
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> <li>Within an unstable area.</li> <li>Engineering measures incor</li></ul>	NA   Yes   No   NA   Yes   No   NA   Yes   No   NA   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No				

Waste Excavation and Removal Closure Plan Checklist: (19.15 17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.				
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC				
Confirantion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)				
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15 17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13.D NMAC) Instructions: Please identify the faculty or facilities for the disposal of liquids, drilling fluids and drill cuttings.				
Disposal Facility Name Envirotech, Basin Disposal Disposal Facility Permit Number. NM-01-0011 & NM-01-005				
On-Site Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC				
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be				
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19 15 17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.				
Name (Print). Crystal Tafoya Title: Regulatory Technician				
Signature Date 7/16/2008				
e-mail address. crystal.tafoya@conocoshillus.com Telephone: 505-326-9837				
OCD Approval: Permit Application (including closure plan) Closure Plan (only)				
Closure rian (only)				
OCD Representative Signature: 3 randon Dull Approval Date: 7-18-08				
OCD Representative Signature: Brandon Dull Approval Date: 7-18-08				
OCD Representative Signature: Reprode Dell Approval Date: 7-18-08  Title: Ensire 15 pts OCD Permit Number				
OCD Representative Signature: Strandon Dull Approval Date: 7-18-08  Title: Ensire / Spec OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC				
OCD Representative Signature: Reprode Dell Approval Date: 7-18-08  Title: Ensire 15 pts OCD Permit Number				
OCD Representative Signature: Strandon Dadd Approval Date: 7-18-08  Title: Ensire / Spec OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Completion Date:  Closure Method:				
OCD Representative Signature: Strandon Dadd Approval Date: 7-18-08  Title: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
OCD Representative Signature:				
Approval Date: 7-18-08  Title: Fuin Spec OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Completion Date:  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique				
Title:				
Approval Date: 7-18-08  Title: Fuin Spec OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC  Closure Completion Date:  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique				
Title:				
OCD Representative Signature:				
Approval Date: 7-18-08  Title: Ensire Spee OCD Permit Number  Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC  Closure Completion Date:  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Longitude: NAD: 1927 1983  Operator Closure Certification:  Thereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief Lalso certify that the				
Title:				

Form C-144 Oil Conservation Division Page 4 of 4

Fee Lame - 3 copics

# State of New Mexico Energy, Minerals and Natural Resources Department

Ferm C-102 Roviges 1-1-89

# OIL CONSERVATION DIVISION

ISTRICT I .O. Box 1980, Hobbs, NM HE ISTRICT II .O. Drawer DD, Artenia, NM 1	240	P.O. Box 20 P.O. Box 20 Santa Fe, New Mexico	88	LAT WELL NO. 2007
ISTRICT III 000 Red Briston Rd., Alber, No.		CATION AND ACREA		LAT
Meridian	Oil Inc.	Sa	n Juan 32-9 U	nit 223
Jan Loner Section	12 31	North 10	West	San Juan
1390 to the	0 <del>-</del> - 1-	980		West
Ground level Plev.	Producing Formation	Pool	feet f	Pose the West line
	Fruitland Coal	Basin		320 Acres
3. If spare than one is uncontained, force—  Yes  If shower is "no" his that force if shocouse No allowable well be	ease of different overship is proint, etc.?  No if so it is overses and want descriping.	gwer 12 "yes" type of contaided cone which have actually been o	unitiza	ation_
	<del></del>		sued to show	OPERATOR CERTIFICATION
4	3		cation 12-3-9	Peggy Bradfield Regulatory Affairs
707	SF-078389-A		1	Meridian Oil Inc.
5	6	7	i 8 ! !	12-3-92 Date
	1	<b>b</b>		SURVEYOR CERTIFICATION
12	//	10	9	I hereby certify that the well location shows on this piet was plotted from field notes of actual surveys made by me or water me supervison, and that the same is true and correct to the best of my incomedge and belief.  12-2-97
980'		<b></b>	<u> </u>	O Date Surprise C. EU W
1390.	14	15	16	9357
	45	579.08'		6857

# Burlington Resources Oil & Gas Company, LP Closed-loop Plans

### Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

# **Closed-loop Operating and Maintenance Plan**

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

#### **Closed-loop Closure Plan**

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.