

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED**AUG 04 2008**

Sundry Notices and Reports on Wells

Bureau of Land Management

Farmington Field Office

5. Lease Number

SF-079247 079047

6. If Indian, All. or
Tribe Name7. Unit Agreement Name
San Juan 32-8 Unit8. Well Name & Number
San Juan 32-8 Unit 18M
9. API Well No.
30-045-344271. Type of Well
GAS

2. Name of Operator

CONOCOPHILLIPS COMPANY3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-97004. Location of Well, Footage, Sec., T, R, M
Unit F (SENW), ~~2350'~~ FNL & ~~1798'~~ FWL, Sec. 11, T31N, R8W, NMPM

2294' 1865'

10. Field and Pool
Blanco MV/Basin DK11. County and State
San Juan CO., NM**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

Type of Action

☐ Abandonment☐ Recompletion☐ Plugging☐ Casing Repair☐ Altering Casing☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection☒ Other - Casing Report**RCVD AUG 7 '08****OIL CONS. DIV.****DIST. 3****13. Describe Proposed or Completed Operations**

7/21/08 H&P 281. RIH w/8 3/4" bit. PT csg to 1500#/30 mins - test ok. ✓ Tagged on cmt @ 200', D/O cmt & drilled ahead to 3850' intmed TD reached 7/24/08. Circ hole. RIH w/93 jts, 7", 20#, J-55 ST&C csg & set @ 3838'. Pre-flush & pump Scavenger 20 sx (60 cf - 11 bbls slurry) Class G, w/Bentonite, CACL2, Cellophane flakes, FL-52A, LCM. Lead 500 sx (1065 cf - 189 bbls slurry) Class G, w/Bentonite, CACL2, Cellophane flakes, FL-52A, LCM. Tail 90 sx (124 cf - 22 bbls slurry) Class G, CACL2, Celloflake, FL-52. Dropped plug & displaced w/154 bbls FW. Bumped plug to 1360# & 7/25/08 0730 hrs. Circ 65 bbls cmt to surf. ✓ WOC. 7/25/08 1630 hrs PT csg to 1600#/30 mins - test good. ✓

7/25/08 RIH w/6 1/4" bit. Drill to 8249' TD. TD reached 7/27/08. Circ hole. RIH w/200 jts, 4 1/2", 11.6#, L-80 LT&C csg & set @ 8246'. Pre-flush w/10 bbls gelled water & 2 bbls FW. Scavenger 20 sx (6 cf - 11 bbls slurry) Premium Lite, w/Bentonite, CACL2, Cellophane flake, FL-52A, LCM. Lead 300 sx (594 cf - 106 bbls slurry) Premium Lite HS FM, w/CD-32, Cellophane, FL-52A, LCM-1. Drop plug & displaced w/128 bbls FW. Plug down to 1475#. ND BOP & NU WH. RD & RR 7/28/08. ✓

PT will be conducted by the completion rig and recorded on the next report. The TOC will be recorded on the next report. ✓

14. I hereby certify that the foregoing is true and correct.

Signed



Rhonda Rogers Title Regulatory Technician

Date 08/1/08

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

