

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1993

SEP 08 2008

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

SUBMIT IN TRIPPLICATE		5. Lease Designation and Serial No NMSE-078769
1. Type of Well Oil Well Gas Well X Other	2. Name of Operator WILLIAMS PRODUCTION COMPANY	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. PO Box 640 Aztec, NM 87410-0640	4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1145' FNL & 2305' FEL SEC 16, 31N, 5W	7. If Unit or CA, Agreement Designation Rosa Unit
		8. Well Name and No Rosa Unit #374
		9. API Well No. 30-039-30112
		10. Field and Pool, or Exploratory Area Basin Fruitland Coal
		11. County or Parish, State Rio Arriba, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	Abandonment
<input checked="" type="checkbox"/> Subsequent Report	Recompletion
<input type="checkbox"/> Final Abandonment	Plugging Back
	Casing Repair
	Altering Casing
	<input checked="" type="checkbox"/> Surface Casing
	Change of Plans
	New Construction
	Non-Routine Fracturing
	Water Shut-Off
	Conversion to Injection
	Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

9/4/08
TD- 12 1/4" SURFACE HOLE @ 345', 1700 HRS
RAN 7 JTS, 9 5/8", K-55, 36#, LT&C, CSG SET @ 335', FC @ 288'
PJSM & RU & CEMENT SINGLE SLURRY CEMENT JOB : Press Test 1500#, 20 Bbl FW Spacer, 250 sx (37 Bbl slurry, 208cuft)
Type 3 Cement+2%CaCl2+1/4# Cello-Flake/sk+6.84 WGPS, Drop Plug & Displace W/22.5 Bbl FW.Plug Dn @ 2325 Hrs, 140#
Final Press, Bump Plug to 510#, Check Float-Held, Press Up to 60# & Shut In. Circ 9 Bbl, 36sx, Cement to Pit. ✓

RCVD SEP 12 '08
OIL CONS. DIV.
DIST. 3

9/5/08
WOC (INSTALL TEST PLUG & PRESS TEST PIPE RAMS, BLIND RAMS, CHOKE MANIFOLD VALVES, CHOKE LINE VALVES, & KILL LINE VALVES @ 250# LOW 5 MIN EACH, 1500# HIGH 10 MIN EACH, TEST PLUG, TEST PUMP & TEST CHARTS USED
PULL TEST PLUG & PRESS TEST KELLY & 4.5" FLOOR VALVE @ 250# LOW 5 MIN & 1500# HIGH 10 MIN EACH
TEST PUMP & CHARTS USED, ALL TESTED GOOD) ✓

ACCEPTED FOR RECORD
SEP 11 2008
FARMINGTON FIELD OFFICE
BY T.L. Salinas

14. I hereby certify that the foregoing is true and correct

Signed Heather Riley
Heather Riley

Title Regulatory Spec

Date September 8, 2008

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD 96