rm 3 160-5 .ugust 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposale to drill or reenter

OMB	No. 100	4-013
Expires Jn	ovembe	r 30, 2

	Lease	Serial	No.
--	-------	--------	-----

SF-07	7874

6.	If Indian,	Allottee

	. Use Form 3160-3 (APD)	and the second s	PUT 15 PH I	1	induce of Tribe Name
SUBMIT IN TRIPLI	ICATE – Other Instr	uctions on reven	se side	7. If Unit or Ca	A/Agreement, Name and/or No.
Type of Well Oil Well Same of Operator	Other	400	21 20 20 30 30 30 30 30 30 30 30 30 30 30 30 30	8. Well Name	
reck Operating Company . Address		3b. Phone No. (include	e area code)	9. API Well N	0.
7415 E. Main, Farmington, NM, Location of Well (Footage, Sec., T., R.,	M., or Survey Description)	505-327-4892		ے)/ √Basin Fruitla	
285' FNL and 660" FEL, Sectio	n 2, T27N, R10W		<u> </u>	San Juan	arish, State
TYPE OF SUBMISSION		TY	PE OF ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production Reclamation	(Start/Resume)	Water Shut-Off Well Integrity
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily	y Abandon	Other
Final Abandonment Notice 13. Describe Proposed or Completed Ope If the proposal is to deepen direction Attach the Bond under which the we Following completion of the involved Testing has been completed. Final	i operations. If the operation res	suits in a multiple completic	on or recompletion in	proposed work an vertical depths of a d subsequent repor a new interval, a F	'orm 3160-4 shall be filed once

determined that the site is ready for final inspection.)

9/29/03 Spud surface hole. Drilled to 137'. Ran 3 jts.(127.23") of 7", 23#, K-55, LT&C casing and set at 132' KB. Cemented with 60 sx (71Cu.ft.) of Cl "B" with 3% CaCl 2 and 1/4#/sk celloflake. Circulated 5.0 bbls of good cement to surface. Install casing head & NU BOP and pressure test to 600 psi.

10/4/03 Ran 48 jts. (2077.35') of 4-1/2", 10.5#, J-55, ST&C new casing and landed at 2077' KB. Insert float is at 2055' KB. Cemented with 230 sx (481 cu.ft.) of Cl "B" 2% econolite cement with 1/4#sk celloflake and 5#/sk gilsonite, followed by 100 sx (123 cu.ft.) of Cl "B" with 1/4#/sk celloflake and 5#/sk gilsonite. Circulated 10 bbls of cement to surface.

14. I hereby certify that the foregoing is true and correct		
Name (Printed/Typed)	Title	
Paul Thompson		Engineer/Agent
Signature	Date	
Paul C. Thomps		October 7, 2003
THI	SSPACE FOR FEDERALIOR STATE	ISE ACOS TECHNICONE
Approved by	Title	Date 06 f 2 7 2003
Conditions of approval, if any, are attached. Approval of this notice certify that the applicant holds legal or equitable title to those rights which would entitle the applicant to conduct operations thereon.		FARMINGTUM FIELD OFFICE

Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.