Form 3160-5 (June 1990)

4 Location of Well (Footage, Sec, T, R, M, or Survey Description)

790' FNL & 820' FEL

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No 1004-0135

Expires March 31, 1993

Basin Fruitland Coal

11 County or Parish, State

SFP 2 2 200c

Lease Designation and Serial No

NMSF07748	
-----------	--

SUNDRY NOTICES AND REPORTS ON WELLS; and Manage of Helidian, Allottee of Tribe No. | See RCVD SEP 24'08 Burgau of Land Manas 6miffindian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir OIL CONS. DIV. DIST. 3 Use "APPLICATION FOR PERMIT - -" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1 Type of Well Oil Gas Well Well 8 Well Name and No Other Red River #1S 2 Name of Operator McKay Oil & Gas, LLC 9 API Well No 30-045-34729 3 Address and Telephone No P. O. Box 14738 Albuquerque, NM (505) 296-5508 10. Field and Pool, or Exploratory Area 87191

Section	12, T30N, R12W			San Juan County, NM			
12	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
	TYPE OF SUBMISSION	TYPE OF ACTION					
V2	Notice of Intent  X Subsequent Report  Final Abandonment Notice		Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Casing Report	Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-off  Conversion to Injection  Dispose Water			
	·			(Note Report results of multiple completions or Well Completion or Recompletion Report and Log form )			

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work )\*

> Sept 8, 2008 Press, tested surface casing and BOP to 700#. Held for 30 min. ✓ Drilled 6 1/4" hole to 2369' Gr. TD. ✓

Sept 13, 2008 Ran 54 JTS, 4 1/2", 10.5#, J-55 to 2304'.

Cemented w/225 SKS Type 5,2% Super Sil-SP + 5# Gilsonite + 1/4# Superflake (472.5 Cu. Ft). Tailed w/150 SKS Type 5, 5# Gilsonite + 1/4# Superflake (177 Cu. Ft.). 15 BBLS cement to pit. 🗸

Rig released Sept 13, 2008. TD reached Sept 12, 2008. PT 41/2" CSG NEXT REPORT.

14 I hereby certify that the foregoing is true and correct  Signed  Mayhow	Title	General Manager	. Date	9/18/2008
(This space for Federal or State office)			ACC	PTED FOR RECORD
Approved by	Title		. Date St	P 2 2 2008
Conditions of approval, if any.			FARM BY TL	MOTON FIELD OFFICE Salvers