Form 3 160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0135 Expires Jnovember 30, 2000

DEC 1-8 20 8 Lease Serial No.

NMNM 05791

SUNDRY NOTICES AND REPORTS ON WELLS

Bureau of Land Management

abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE – Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No OIL CONS. DIV. DIST. 3	
2 Name of Operator					Graham 10 #9	
M&G Drilling Company, Inc. c/o Walsh Engineering					9. API Well No.	
3a. Address 3b.			e No (include	30-045-32729		
7415 E. Main, Farmington, NM, 87402 508			-4892		10. Field and Pool, or Exploratory Area	
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)			Blanco MV & Basin DK		Basin DK	
1010' FSL and 700' FEL, (P) Sec. 10, T27N, R8W					11. County or Parish, State	
					San Juan Cou	nty, NM
12. CHECK AP	PROPRIATE BOX(ES) TO IN	NDICATE	NATURE OF	NOTICE, REP	ORT, OR OTHER I	DATA
TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Intent	Acidize Alter Casing	Deepe	en ure Treat	Production Reclamation	(Start/Resume) [Water Shut-Off Well Integrity
X Subsequent Report	Casing Repair	New !	Construction	Recomplete	-	Other Spud & Casing
Final Abandonment Notice	Change Plans	Plug	and Abandon	Temporaril Water Disp	y Abandon	Report
- Company	Convert to Injection					
13 Describe Proposed or Completed Oper If the proposal is to deepen direction. Attach the Bond under which the wo Following completion of the involved Testing has been completed. Final A determined that the site is ready for final 12/6/08 spud 12-1/4" surface hole						
236' KB. Cemented with 150 sx (surface.	180 cu. ft.) of Type 5, 2%	CaCl ₂ and	1/4 #/sk cel	loflake. Circul	ated 15 bbls of go	ood cement to
12/7/08 Nippled up the BOP. Pre	essure tested the BOP,chok	e manifolo	and casing	to 250 psi - lov	w and 1500 psi - h	nigh both for 30 min.
Test held OK. Pressure casing to	750 psi for 30 min held (ok √	_	-	-	
12/9/08 TD 8-3/4" hole at 2658'.	Ran 63 jts (2630') of 7", 26	0#, J-55, S	ST&C produ	ction casing an	d set casing at	
2649' KB. Cemented with 250 sx	(540 cu.ft.) of Type 5 w/ 2	% SMS, 0	CF & gilsoni	te. Tailed w/ 15	50 sx (179 cu.ft.)	Type 5 w/ CF and
gilsonite. Bump plug to 1500 psi	- float held OK. Circulated	22 bbls o	f cement to	surface. Pressu	re test 7" cas	ing ? NEXT REPORT
12/11/08 TD 6-1/4" hole at 6750			_	_		
and set at 6750' KB. Float collar						
to 2000 psi - float held OK. Plan	to run CBL w/ Comp. logs	s. Release	d the rig at 0	000 hrs 12/13/0	08. J PRESSURE	TEST 4/2" CSG NEXT REPOR
14 I hereby certify that the foregoing is	true and correct					
Name (Printed/Typed) Paul C. Thompson, P.E.			Title Agent			
Signature	1	Date				
Taul C. Thomps -			December 16, 2008			1
	THIS SPACE	E FOR FE	DERAL OR S	TATE USE		ACCEPTED FOR RECORD
Approved by			Title		Date	
						DEC 2 9 2008
Conditions of approval, if any, are attached. Approval of this notice does not warra certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.			Office N	MOCD &		FARMINGTON FIELD OFFICE BY TL Salvers