## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires. January 31, 200-

NOV 1 & 2008

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

MDA /01-	-04-0014
ւլ6. If Indian, A	Allottee or Tribe Name POUD FED 4'03

abandoned we	ell. Use Form 3160-3 (APD)	for such propo	osals <sub>endo</sub> o con	Jicarilla	RCUD FEB 4'0'5 Apache Nation	
SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No. OIL CONS. DIU.	
I. Type of Well					ame and No.	
Oil Well Gas Well Other  2. Name of Operator					28-3 No. 1	
Jicarilla Apache Energy Corp					28-3 No. 1	
3a. Address 3b. Phone No. (include are			clude area code)	· · · · · · · · · · · · · · · · · · ·		
		,	10. Field and Pool, or Exploratory Area			
P.O. Box 710 Dulce, New Mexico 87528 575-759-3224  4. Location of Well (Footage, Sec., T, R., M., or Survey Description)				Blanco	Mesa Verde	
1490' FSL & 660' FWL, Sec 36, T28N, R3W					11. County or Parish, State  Rio Arriba, New Mexico	
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NA	TURE OF NOT			
TYPE OF SUBMISSION						
	Acidize	Deepen	Producti	ion (Start/Resume)	☐ Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclama	ntion	■ Well Integrity	
Subsequent Report	Casing Repair	New Constructi	on 🔲 Recomp	lete	Other Spud & Intermediate	
	Change Plans	Plug and Aband	lon 🔲 Tempor	arily Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water D	isposal		
Spud 12 1/4" Hole at 9:30 pm, 5 Cement with 200 sx Class B + 2 Pressure test BOPE and Casing Drill 8 3/4" hole to 4095'(6:00 a follows: Stage 1: 175 sks (363 cf) 35/65 (184 cf) class G + 5 lbs/sk Gilsot Stage 2: 395 sks (741 cf) 35/65 sks (63 cf) class G + 5 lbs/sk Gilsot BOPE & casing to 2000 psi - ok.	for final inspection.)  5/19/08. Drill to 334'. Ran 8 jts 9  2% CaCl2 + 1/4 #/sk cellophane to 2000 psi for 30 minutes - ok. um, 5/28/08) Ran Ind & NeuDen  POZ/G + 6% Gel + 5 lbs/sk Gils nite + 1/8 lb/sk Pol-E-Flake+ 3%  POZ/G + 6% Gel + 10 lbs/sk Gils ilsonite+ 1/8 lbs/sk Pol-E-Flake-	1 5/8" 36# J-55 ST flake mixed at 15 Log. Ran 101 jts sonite + 1/8 lb/sk 6 KCL mixed at 1 lsonite + 1/8 lbs/s	C, casing set at 33.6 #/gal yield 1.18.7" 20# J-55 STC c Pol-E-Flake + 3% 5.2 ppg, yield 1.26 kk Pol-E-Flake + 3	4' KB. Circulated 10 bbls esg, 4080', set at 409 KCL mixed at 12.1 b9 cf/sk. Circ 45 bbl 66 KCL mixed at 12	23' KB, DV at 2224'. Cemented as ppg, yield 2.076 cf/sk & 145 sks cmt off of DV to Surf.   .5 ppg, yield 1.887 cf/sk & 50	
14. I hereby certify that the foregoin Name (PrintedlTyped)	ng is true and correct					
Daneda A. Gonzales		Title	Title JAECO Production/Accounting Technician			
Signature Danida	A. Denzalis	Dat	Date November 10, 2008			
	THIS SPACE FO	R FEDERAL O	R STATE OFFIC	É ÚSE		
Approved by (Signature)			Name (Printed/Typed)		Title	
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject least which would entitle the applicant to conduct operations thereon.					Date	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.