

(November, 1996)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

SUNDY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPPLICATE - Other Instructions on the reverse side

1. Type of Well

☐

Oil Well

☐

Other

2. Name of Operator

Devon Energy Production Co. L.P. Attn: Kenny Rhoades

3a. Address

3b. Phone No. (include area code)

1751 Highway 511 Navajo Dam, NM 87419**(505)320-6310**

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1970' FNL & 1500' FEL SW 1/4, NE 1/4, Sec. 30, T 31N R. 6W

Latitude

Unit G

Longitude

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**TYPE OF SUBMISSION****TYPE OF ACTION**☐

Notice of Intent

☐

Acidize

☐

Deepen

☐

Production (Start/Resume)

☐

Water Shut-off

☒

Subsequent Report

☐

Altering Casing

☐

Fracture Treat

☐

Reclamation

☐

Well Integrity

☐

Final Abandonment Notice

☐

Change Plans

☐

Plug and abandon

☐

Temporarily Abandon

☒

Other

Casing and Cement

13. Describe Proposed or Completed Operation (clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recompleting horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands.

Attach the Bond under which the work will be performed or provide the Bond No. on file with the BLM/ BIA. Required subsequent reports shall be filed within 30 days

following completion of the involved operations. If the operation results in a multiple completion or recompleting in a new interval, a Form 3160-4 shall be filed once

testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamation, have been completed, and the operator has

determined that the site is ready for final inspection.)

Drilled 12-1/4" hole to 285'. On 9/29/2003 set 6 jts 9-5/8" 32.3# K-55 casing at 275'. Cemented with 200 sx (42 bbls) Class "B" cement w/ 2% CaCl and 1/4# Flocele. Circulated 10 bbls to surface. Pressure tested casing to 1500 psi.

Drilled 8-3/4" directional hole to 4400'. On 10/2/2003 set 84 jts 7" 23# K-55 casing at 3694' Cemented w/ 400 sx (104 bbls) 50/50 Poz w/ 2% gel, 0.2% Versaset, 0.1% Diacel LWL, and Nitrogen to foam slurry Tail w/ 75 sx (20 bbls) 50/50 Poz w/ 2% gel, 0.2% Versaset, 0.1% Diacel LWL. Circulated 8 bbls to surface. Pressure tested casing to 1500 psi.

Drilled 6-1/4" hole to 8168'. On 10/8/03 set 187 jts 4-1/2" 11.6# J-55 casing at 8158' with ACP at 7884'. Cemented w/ 490 sx (128 bbls) 50/50 Poz w/ 3% gel, 1.4% Halad 9, 0.3% CFR-3, 0.1% HR-5, 5# Gilsonite, 1/4# Flc Circ 20 bbls to surface. Pressure test casing to 4500 psi.

14. I hereby certify that the foregoing is true and correct.

Name (Printed/ Typed)

Kenny Rhoades

Title

Company Representative

Signature

Date

11-17-03

Approved by

Title

Date

Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

NOV 25 2003

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NMOCD