

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

RECEIVED

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON**

RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

660' FNL, 660' FEL, Sec. 25, T-31-N, R-17-W, NMPM

070 Farmington, NM

5. Lease Number  
14-20-603-2037  
6. If Indian, All. or  
Tribe Name  
Navajo  
7. Unit Agreement Name  
Horseshoe Gallup Unit

8. Well Name & Number  
Horseshoe Gallup U#119  
9. API Well No.  
30-045-10420  
10. Field and Pool  
Horseshoe Gallup  
11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

10/23/03 MIRU. Dig out bradenhead to check well pressures: 0#. TOOH w/rods and pump. Remove wellhead cap and release tubing slips. Install companion flange and NU BOP, test. TOOH w/2-7/8" tbg. Round-trip 5-1/2" csg scraper to 1300'. TIH and set 5-1/2" DHS cement retainer at 1300'. PT tbg to 1000#. Sting out of retainer. PT csg to 500#, held OK. Shut in well. SDON.

10/26/03 Circ well clean with 15 bbls of water. Plug #1 with retainer at 1300', spot 35 sxs Class B neat cmt above retainer inside casing up to 991' to isolate the Gallup perfs. TOOH & LD tubing. RU wireline truck. Perf 2 squeeze holes at 156'. Establish circ out bradenhead with 10 bbls of water and circ BH annulus well clean with additional 7 bbls of water. Plug #2 with 59 sxs Class B neat cmt pumped down 5-1/2" csg from 156' to surface, circ good cement out bradenhead valve. Shut in well and WOC as required by Davis Benallie, Navajo Nation. SDON.

10/27/03 ND BOP and flange. Dig out casing head, chip away cement outside casing. Cut off wellhead. Found cement at surface in casing and annulus. Mix 15 sxs cement and set P&A marker. RD. Rig released.

R. Maurer, Burlington Resources, representative was on location.  
D. Benallie, Navajo Nation representative was on location.

Well plugged and abandoned 10/27/03.

14. I hereby certify that the foregoing is true and correct.

Signed Tammy Winters Title Regulatory Specialist Date 12/9/03

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

DEC 11 2003

FARMINGTON FIELD OFFICE

NMOC