

RECEIVED

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

MAY 13 2009

## Sundry Notices and Reports on Wells

Bureau of Land Management  
Farmington Field Office1. Type of Well  
GAS5. Lease Number  
USA SF-080675  
6. If Indian, All. or  
Tribe Name

2. Name of Operator

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY LP

7. Unit Agreement Name  
San Juan 27-4 Unit

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number  
San Juan 27-4 Unit 57N

9. API Well No.

30-039-30485

4. Location of Well, Footage, Sec., T, R, M

10. Field and Pool

Surf: Unit N (SE/SW), 1130' FSL &amp; 2410' FWL, Section 28, T27N, R4W, NMPM

11. Blanco MV/ Basin DK  
County and State  
Rio Arriba, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - ☐ Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction

RCVD MAY 14 '09

☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair☐ Water Shut off

DIST. 3

☐ Altering Casing☐ Conversion to Injection

## 13. Describe Proposed or Completed Operations

4/23/2009 MIRU H&P 283. NU BOP. 4/23/2009 PT csg 600#/30min. Ok. 4/23/2009 RIH w/ 8 3/4" bit & tag cmt 154'. D/O cmt and drilled ahead to TD Int 4278' on 4/25/2009. Circ Hole. RIH w/ 102 jnts of 7" csg, 23#, J-55 ST&C set @ 4263' w/ Stage tool @ 3385'. RU CMT. 4/26/2009 1<sup>ST</sup> STAGE Preflushed w/ 10 bbls H2O, 10 bbls GW, Pumped Scavenger w/ 20sx(57cf-10bbl) Premium Lite Cement, Pumped Lead w/ 40sx(85cf-15bbl) Premium Lite Cement w/ FL-52A .4%, Bentonite 8%, SMS .4%, Cellophane Flakes .25 lbs, CaCl2 3%, and LCM-1 5lbs. Pumped Tail w/ 100sx(138cf-25bbl) Class C Cement w/ 1% CaCl, 0.25 pps Cello-Flake and 0.2% FL-52. Drop plug & displace w/ 50bbls FW & 121bbls DM. Open Stage Tool w/ 2190# and circ. Circ 20 bbls of cmt to surface. WOC 1900hrs on 4/26/2009

4/26/2009 2<sup>ND</sup> STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger w/ 20sx(56cf-10bbl) Premium Lite Cement, Pumped Lead w/ 435sx(967cf-165bbl) Premium Lite Cement w/ 3% CaCl, 0.25 pps Cello-Flake, 5 pps LCM-1, 0.4% FL-52, 8% Bentonite and 0.4% SMS. Drop Plug & displace w/ 137bbls FW. Circ 70bbls cmt to surface. Bump plug & Close Stage Tool. Plug down @ 0037hrs on 4/27/2009. WOC 4/27/2009 PT Stage Tool and csg @ 1500#/30Min @ 2000 hrs, OK. 4/27/2009 RIH W 6 1/4" bit & tag cmt, D/O DV Tool & cmt and drilled ahead to final TD @ 8526' on 4/29/2009. RIH w/ 42 jnts, 4 1/2" csg, 11.6#, J-55, LT&C, 160 jnts, 4 1/2" csg, 10.5#, J-55, LT&C set @ 8522'. RU cmt. 4/29/2009 Preflushed w/ 10bbls GW & 2bbls FW. Pumped Scavenger w/ 10sx(27cf-5bbl) Premium Lite HS FM Cement, Pumped Tail w/ 310sx(614cf-109bbl) Premium Lite HS FM Cement w/ 0.25pps Cello-Flake, 0.3% CD-32, 6.25pps LCM-1, 1% FL-52. Drop plug & displace w/ 135bbls FW. Bump plug. Plug down @ 0345hrs on 4/30/2009. RD&RR 4/30/2009.

PT will be conducted by Completion Rig. Results and TOC will appear on next report.

## 14. I hereby certify that the foregoing is true and correct.

Signed

*Ethel Tally*

Ethel Tally

Title Staff Regulatory Technician

Date 5/13/2009

(This space for Federal or State Office use)

APPROVED BY

Title

NMOCD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

5/15

ACCEPTED FOR RECORD
Date
MAY 13 2009
FARMINGTON FIELD OFFICE
BY <i>T. S. S. S.</i>