Form 3160-3 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0136 Expires November 30, 2000

5.	Lease Serial No.
	NM-17781

Į		14141 177	01	
İ	6.	If Indian,	Allottce or	Tribe Name

	****	MM 23 PM 3:08	NM-17781	
APPLICATION FOR PERMIT	TO DRILL OR REE	NTER	6. If Indian, Allottce or Trib	e Name
Ia. Type of Work: 🛛 DRILL 🔲 REENTER	070	Farmington, NM	7. If Unit or CA Agreement	, Name and No.
tb. Type of Well: ☐ Oil Well ☐ Gas Well 💆 Otl	her: CBM 🏿 Singl	e Zone	Lease Name and Well No PAUL REVERE COM). 95
	KURT FAGRELIUS E-Mail: kfagrelius@duganp		9. API Well No. 30 045 3	3/359
3a. Address 709 EAST MURRAY DRIVE FARMINGTON, NM 87401	3b. Phone No. (include Ph: 505.325.1821 Fx: 505.327.4613	arca code)	10. Field and Pool, or Explo BASIN FRUITLAND	
4. Location of Well (Report location clearly and in accorda	nce with any State require	ements.*)	11. Sec., T., R., M., or Blk.	and Survey or Area
At surface NWSW 1650FSL 1200FW	L 36.28160 N Lat, 10	8.12390 W Lon	Sec 22 T26N R13W	Mer NMP
At proposed prod. zone			<u></u>	
14. Distance in miles and direction from nearest town or post APPROX. 12-MILES NW OF CARSON TRADIN	office* IG POST		12. County or Parish SAN JUAN	13. State NM
 Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1200' 	16. No. of Acres in Lea	se Say	17. Spacing Unit dedicated	to this well
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 300' 	19. Proposed Depth 1430 MD		20. BLM/BIA Bond No. on	file
21. Elevations (Show whether DF, KB, RT, GL, etc. 6192 GL	22. Approximate date w	vork will start	23. Estimated duration	
	24. Attac	chments	-	
The following, completed in accordance with the requirements o	f Onshore Oil and Gas Ord	der No. 1, shall be attached to the	nis form:	
Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest Systems Supposed to the Supposed Suppose	em Lands, the	 Bond to cover the operation Item 20 above). Operator certification Such other site specific info authorized officer. 	·	
25. Signature / Fartherin	Name (Printed/Typed) KURT FAGRELII	JS		Date 01/22/2003
Title GEOLOGIST				
Approved by (Signature)	Name (Printed/Typed)	/s/ David J. Manki	ewicz	DEC 16 2003
Title	Office	-		
Application approval does not warrant or certify the applicant ho operations thereon. Conditions of approval, if any, are attached.	lds legal or equitable title t	to those rights in the subject lea	se which would entitle the app	licant to conduct
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, n	nake it a crime for any per	son knowingly and willfully to	make to any department or age	ency of the United

Additional Operator Remarks:

A water based gel-mud will be used to drill surface and production casing hole. Standard 2,000 psi BOP will be used to drill production hole. The Fruitland Coal will be completed from approximately 1260'-1300'. The interval will be fractured.

This action is subject to technical and procedural review pursuant to 43 CFR 3165.87 and appeal pursuant to 43 CFR 3165.4

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS".



District I 20 Box 1980, Hobbs, NM 88241–1980

District II PO Drawer DD, Artesia, NM 88211-0719

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Olstrict IV PO Box 2088, Santa Fe. NM 87504-2088

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088

Form C-102 Revised February 21, 1994 Instructions on back Submit to Appropriate District Office

State Lease - 4 Copies Fee Lease - 3 Copies

AMENDED REPORT

LOCATION AND ACDEAGE DEDICATION DLAT

			WELL	LUCAT	TON AND	JA	CREAGE DED	JILA	I TON PL	_A i		
30-045-31.359 *Pool Cod				1								
Property Code					°Property Name PAUL REVERE					*Well Number 95		
'0GRID 1 00651	1			DUGAN			Name N CORPORAT	TIOI	١		Elevation.	
					¹⁰ Surfa	ce	Location					
UL or lot no.	Section 22	Township 26N	Pange 13W	Lot Idn	feet from 1650	the	North/South line SOUTH		et from the	East/We WE		SAN JUAN
		11 B	ottom	Hole L	ocation	I	f Different	Fr	om Surf	ace	.,	
UL or lot no.	Section	Township	Range	Lot Idn	Feet from t	the	North/South line		et from the	East/Wes	st line	County
320.0 ACRES - (S/2) 33 Joint or Infill 44 Consolidation Code 45 Order No.						I						
NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION												
16			52	77.36	THE TRIVE	870			I hereby contained to the bit Signature Kurt Frinted N	certify to the fine the fine to the fine t	hat the instruction that the i	FICATION information it complete and belief

Title 01/23/2003 Date *SURVEYOR CERTIFICATION 00 00 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 5280 280 **DUGAN 100%** Date of Survey: JULY 15, 2002 NM-17781 Signature and Seal of Professional Surveyor SON C. EDWARDS 1200' SEN MEXICO PEGISTON PROFESSIONAL **MARALEX EDWARDS** NM-31059 NM-86086 650 5282.641 Certificate Number

EXHIBIT B OPERATIONS PLAN

Paul Revere Com #95

APPROXIMATE FORMATION TOPS:

Ojo Alamo	Surface'	Pictured Cliffs	1305′
Kirtland	80 ′		
Fruitland	1000′	Total Depth	1430'

Catch samples every 10 feet from 1200 feet to total depth.

LOGGING PROGRAM:

Run casedhole GR-CCL-CNL from total depth to surface.

CASING PROGRAM:

Hole	Casing		Setting	Grade and
<u>Size</u> 9-7/8''	<u>Size</u>	Wt./ft.	<u>Depth</u>	<u>Condition</u>
9-7/8''	7''	20#	120'	J-55
6-1/4''	4-1/2''	10.5#	1430'	J-55

Plan to drill a 9-7/8" hole and set 120' of 7" OD, 20#, J-55 surface casing. Then plan to drill a 6-1/4" hole to total depth with gel-water mud program to test the Fruitland Coal. 4-1/2", 10.5#, J-55 production casing will be run and cemented. Cased hole GR-CCL-CNL log will be run. Productive zone will be perforated and fractured. After frac, the well will be cleaned out and production equipment will be installed.

CEMENTING PROGRAM:

<u>Surface</u>: Cement to surface with 70 cf Class B + 2% CaCl₂.

Circulate to surface.

Production Stage-Cement with 142 cf 2%Lodense with

4# celloflake/sx followed by 78 cf Class "B" with

4# celloflake/sx.

Total cement slurry for production stage is 220 cf.

Circulate cement to surface.

An adequate spacer will be pumped ahead of the cement slurry to help prevent mud contamination of the cement. An adequate number of casing centralizers will be run through usable water zones to ensure that casing is centralized through these zones. The adequate number of centralizers will be determined based on API standards. Centralizers to impart a swirling action around the casing will be used just below and into the base of the lowest usable water zone. These devices will assist mud

displacement, increase cement bonding potential and create an effective hydraulic seal. A chronological log will be kept which records the pump rate, pump pressure, slurry density, and slurry volume for the cement job. The log will be sent to the BLM after completion of the job.

WELLHEAD EQUIPMENT:

Huber 7"x4-1/2" casing head, 1000# WP, tested to 2000#. Huber 4-1/2"x2-7/8" tubing head, 1000# WP, tested to 2000#.

BOP and Related Equipment will include for a 2000 psi system:

(Exhibit D)

Annular preventer, double ram, or 2 rams with one being blind and one being a pipe ram.

Kill line (2" minimum)

1 kill line valve (2" minimum)

1 choke line valve

2 chokes

Upper kelly cock valve with handle available Safety valve and subs to fit all drill string connections in use.

Pressure gauge on choke manifold.

2" minimum choke line.

Fill-up line.

Contacts:

Dugan Prod.Corp. Office & Radio Dispatch: 325-1821

Mark Brown	327-3632 320-8247	
Kurt Fagrelius	325-4327 320-8248	, ,
John Alexander	325-6927 320-1935	