UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECENTED

AUG 3 1 2009

Bureau of Land Management Farmington Field Office Sundry Notices and Reports on Wells 5. Lease Number SF-078835-A Type of Well If Indian, All. or 6. Tribe Name GAS 7. **Unit Agreement Name** San Juan 28-7 Unit Name of Operator ConocoPhillips Well Name & Number San Juan 28-7 Unit 244N Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-039-30762 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Surface: Unit K (NESW), 2252' FSL & 1673' FWL, Section 7, T27N, R7W, NMPM Blanco MV / Basin DK Bottomhole: Unit F (SENW), 2330' FNL & 1685' FWL, Section 7, T27N, R7W, NMPM 11. **County and State** Rio Arriba, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Abandonment Notice of Intent Change of Plans X Other - Casing Report Recompletion New Construction RCWD SEP 3'09 Plugging Subsequent Report Non-Routine Fracturing ATL CONS. DIV. Casing Repair Water Shut off DIST. 3 Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 08/21/2009 MIRU AWS 673. NU BOPE. PŢ csg to 600#/30min. 08/22/09. Test -OK ■ 08/22/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 4121' - Inter TD reached 8/25/09. Circ. hole. RIH w/ 95jts, 7", 23#, J-55 LT&C set @ 4111' w/ DV tool @ 2462'. 08/26/2009 RU to cmt. 1st Stage - Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premum lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, 4% FL-52, .4% SMS. Lead w/ 160sx (341cf-61bbls) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Tail w/ 96sx (133cf-24bbls) Type III cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .2% FL-52, .4% SMS. Drop plug & displaced w/ 60bbls FW, 100bbls MW. Bump plug. Plug down @ 21:44hrs on 8/26/09. Open DV tool & circ. 50bbls cmt to surface. WOC. 2nd Stage - Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS. Lead w/ 330sx (703cf-125bbls) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Drop plug & displaced w/ 95bbls FW. Bump plug & close DV tool. Circ. 40bbls cmt to surface. Plug down @ 02:48hrs on 08/27/09. RD cmt. WOC. 08/27/2009 RIH w/ 6 1/4" bit. Drill out DV tool @ 2462'. PT 7" csg to 1500#/30min @ 11:00hrs on 08/27/09. Test - OK. Drilled ahead w/ 6 1/4" bit to 7737' (TD) TD reached 8/29/09. Circ. hole & RIH w/ 190jts total. 100jts 4 1/2", 11.6#, L-80 LT&C and 90jts, 4 1/2", 11.6#, L-55 LT&C set @ 7737. 08/30/09 RU to cmt. Pre-flush w/ 10bbls CW, 2bbls FW. Pumped scavenger 10sx (28cf-5bbls) Premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Lead w/ 286sx (566cf-101bbls) Premium lite cmt w/ .3% CD-32, .25pps celloflake, 1% FL-52, 6.25pps LCM-1. Flushed lines w/ 20bbls FW. Drop plug & displaced 13bbls FW. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 03:45hrs on 08/31/09 PT will be conducted by Completion Rig. Results & TOC will appear on next report. 14. I hereby certify that the foregoing is true and correct. Crystal Tafoya Date 08/31/2009 Signed Title Regulatory Technician (This space for Federal or State Office use) CEPTED FOR RECORD APPROVED BY Title CONDITION OF APPROVAL, if any: SEP 0 1 2009 Title 18 U S C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter