District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008 For temporary pits, closed-loop sytems, and below-grade

tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the

1220 S. St Francis Dr., Santa Fe, NM 87505	appropriate NMOCD District Office
20910	Pit, Closed-Loop System, Below-Grade Tank, or
Prop	osed Alternative Method Permit or Closure Plan Application
Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,
Instructions, Plags asylmit on a	below-grade tank, or proposed alternative method spplication (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
	of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
	eve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1 Operator: Burlington Resources O	il & Gas Company, LP OGRID#: 14538
Address: PO Box 4289, Farmington	
Facility or well name: SAN JUAN	
API Number:	30-039- 30 79 0 OCD Permit Number:
U/L or Qtr/Qtr: K(NE/SW) Secti	
Center of Proposed Design: Latitud	e: 36.65829 °N Longitude: 107.45826 °W NAD: 1927 X 1983
Surface Owner: X Federal	State Private Tribal Trust or Indian Allotment
Permanent Emergency C X Lined Unlined L X String-Reinforced	rkover Cavitation P&A iner type: Thickness 20 mil X LLDPE HDPE PVC Other actory Other Volume. 7700 bbl Dimensions L 120' x W 55' x D 12'
Type of Operation: P&A Drying Pad Above Ground Unlined Line	tion H of 19.15.17.11 NMAC Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) and Steel Tanks Haul-off Bins Other Trype Thickness mil LLDPE HDPE PVD Other actory Other RECEIVED
	Visible sidewalls only Other
5 Alternative Method: Submittal of an exception request is rec	quired. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19,15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet X Alternate. Please specify 4' hogwire fence with a single strand of barbed wire on top.							
Netting: Subsection E of 19.15 17.11 NMAC (Applies to permanent pits and permanent open top tanks) X Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)							
8 Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.3.103 NMAC							
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration (Fencing/BGT Liner) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	leration of app	roval.					
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.							
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	XNo					
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	XNo					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	XNo					
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	NA						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No					
(Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	XNA						
Within 500 horizonal fect of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	XNo					
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	XNo					
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	XNo					
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	XNo					
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	X No					
Within a 100-year floodplain - FEMA map	Yes	XNo					

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached. X Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC X Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 X Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.11 NMAC X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17 12 NMAC X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17 13 NMAC Previously Approved Design (attach copy of design) API
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15 17.9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Previously Approved Operating and Maintenance Plan API
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.19 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: X Drilling Workover Emergency Cavitation P&A Permanent Pit X Below-grade Tank Closed-loop System Alternative Proposed Closure Method: X Waste Excavation and Removal (Below-Grade Tank) Waste Removal (Closed-loop systems only) X On-site Closure Method (only for temporary pits and closed-loop systems) X In-place Burial On-site Trench Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist (19 15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. X Protocols and Procedures - based upon the appropriate requirements of 19.15.17 13 NMAC X Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) X Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC X Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

1.6								
Waste Removal Closure For Closed-loop Systems That Utilize Above Instructions. Please identify the facility or facilities for the disposal of liq								
facilities are required	unus, arning plants and arni cannigs. Ose unachineni ij intre mun iwi	O .						
Disposal Facility Name:	Disposal Facility Permit #:							
Disposal Facility Name:								
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nbe used for future service and Yes (If yes, please provide the information No								
Required for impacted areas which will not be used for future service and	•							
l <u>==</u>	Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC								
Site recommendation rian - based upon the appropriate requirem	ichts of Subsection Con 19 19 17 13 WMAC							
17	17.10.114.0							
Siting Criteria (Regarding on-site closure methods only: 19.15. Instructions Each stung criteria requires a demonstration of compliance in the clo		w Requests regarding changes to						
certain siting criteria may require administrative approval from the appropriate di	strict office or may be considered an exception which must be submitted to the S							
office for consideration of approval Justifications and/or demonstrations of equiv	alency are required Please refer to 1915.1/10 NMAC for guidance							
Ground water is less than 50 feet below the bottom of the buried		Yes X No						
- NM Office of the State Engineer - iWATERS database search, US	GS Data obtained from nearby wells	N/A						
Ground water is between 50 and 100 feet below the bottom of the	buried waste	Yes X No						
- NM Office of the State Engineer - iWATERS database search, USC	GS, Data obtained from nearby wells	□N/A						
Ground water is more than 100 feet below the bottom of the burie	ed waste.	X Yes No						
- NM Office of the State Engineer - (WATERS database search; USC		∏N/A						
Within 200 feet of a continuously flewing watersource or 200 feet of our	othor cionificant watercours on labaked ciulikale on alace laba							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any (measured from the ordinary high-water mark).	. ,	Yes X No						
- Topographic map, Visual inspection (certification) of the proposed	site							
Within 300 feet from a permanent residence, school, hospital, institution,	••	Yes X No						
- Visual inspection (certification) of the proposed site; Aerial photo, s	aternite image	Yes X No						
Within 500 horizontal feet of a private, domestic fresh water well or spring	that less than five households use for domestic or stock watering	L CS A NO						
purposes, or within 1000 horizontal fee of any other fresh water well or sp	•							
- NM Office of the State Engineer - iWATERS database; Visual inspe								
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.								
- Written confirmation or verification from the municipality; Written	approval obtained from the municipality							
Within 500 feet of a wetland		Yes X No						
- US Fish and Wildlife Wetland Identification map. Topographic map	o, Visual inspection (certification) of the proposed site							
Within the area overlying a subsurface mine.	Yes X No							
- Written confiramtion or verification or map from the NM EMNRD-	Mining and Mineral Division							
Within an unstable area. - Engineering measures incorporated into the design, NM Bureau of C	Coolean, & Managed Danguages, LICCC NIM Cooleanest Conjecture	Yes X No						
Topographic map	sectory & Willetan Resources, OSGS, NW Geological Society.							
Within a 100-year floodplain. - FEMA map		Yes X No						
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instruct	ions: Each of the following items must bee attached to the cl	osure plan. Please indicate						
by a check mark in the box, that the documents are attached.	yyg	- prince of the control of the contr						
X Siting Criteria Compliance Demonstrations - based upon the	ne appropriate requirements of 19.15.17.10 NMAC							
X Proof of Surface Owner Notice - based upon the appropria	te requirements of Subsection F of 19.15.17.13 NMAC							
Construction/Design Plan of Burial Trench (if applicable)	based upon the appropriate requirements of 19.15.17.11 NMAC	0						
Construction/Design Plan of Temporary Pit (for in place by	urial of a drying pad) - based upon the appropriate requirement	s of 19.15.17.11 NMAC						
Protocols and Procedures - based upon the appropriate req	uirements of 19.15.17.13 NMAC							
Confirmation Sampling Plan (if applicable) - based upon the	he appropriate requirements of Subsection F of 19.15.17.13 NM	1AC						
X Waste Material Sampling Plan - based upon the appropriate	e requirements of Subsection F of 19.15.17.13 NMAC							
X Disposal Facility Name and Permit Number (for liquids, dr	rilling fluids and drill cuttings or in case on-site closure standard	ds cannot be achieved)						
X Soil Cover Design - based upon the appropriate requirement								
X Re-vegetation Plan - based upon the appropriate requirement								
IXI Site Reclamation Plan - based upon the appropriate require	ments of Subsection G of 19.15.17.13 NMAC	Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC						

19,	
Operator Application Certification: Thereby certify that the information submitted with this application is to	nue accurate and complete to the best of my knowledge and belief
Name (Print) Marie E Japanillo	Title: Staff Regulatory Technician
Signature Signature	Date. OPALOSI
e-mail address: marie.e.jaramillq@conpcophilips.co	
C-man address.	
20	
OCD Approval: Permit Application (including closure pl	lan) Closure Plan (only) OCD Conditions (see attachment)
OCD Representative Signature:	Approval Date: 9/30/09
Title: Enviro / Spec	7/30/81
Title: Enlin/Spec	OCD Permit Number:
21	
Closure Report (required within 60 days of closure complete	ion): Subsection K of 19 15 17 13 NMAC
Instructions Operators are required to obtain an approved closure pla	on prior to implementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the approved closure plan has been obtained and the closure activities hav	completion of the closure activities Please do not complete this section of the form until an
Toppe of the cooling pain has been contined and the closure detivities have	Closure Completion Date:
	Crosure Completion Date.
22 Clasura Mathada	
Closure Method: Waste Excavation and Removal On-site Closure Method:	Method Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain.	Waste Kelloval (Closed-loop systems only)
in different from approved plan, please explain.	
Character Water Park Character Character	Constitution of the terms of
	p Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: uids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.	g James and an action of the control
Disposal Facility Name:	Disposal Facility Permit Number.
Disposal Facility Name.	Disposal Facility Permit Number
· ·	erformed on or in areas that will not be used for future service and opeartions?
Yes (If yes, please demonstrate compliane to the items below)	_
Required for impacted areas which will not be used for future service. Site Reclamation (Photo Documentation)	ce and operations:
Soil Backfilling and Cover Installation	
Re-vegetation Application Rates and Seeding Technique	
24	
l .	of the following items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.	
Proof of Closure Notice (surface owner and division)	
Proof of Deed Notice (required for on-site closure)	
Plot Plan (for on-site closures and temporary pits)	
Confirmation Sampling Analytical Results (if applicable	
Waste Material Sampling Analytical Results (if applicab Disposal Facility Name and Permit Number	пој
Soil Backfilling and Cover Installation	
Re-vegetation Application Rates and Seeding Technique	8
Site Reclamation (Photo Documentation)	
On-site Closure Location Latitude	Longitude: NAD 1927 1983
25	
Operator Closure Certification:	
	is closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and cond	titions specified in the approved closure plan
Name (Print):	Title:
Signature:	Date:
Signature.	Day.
e-mail address:	Telephone:



New Mexico Office of the State Engineer Water Column/Average Depth to Water

(quarters are 1=NW 2=NE 3=SW 4=SE)

Pt II was by the property of t	A NAME AND ADDRESS OF THE PARTY	(quarte	rs a	re s	sma	llest	to larg	est) (N	VAD83 UTN	/ in meters)		(In feet)	oner Australia
Şu			NOT THE	DAME I	Q					17 Year 100 100 100 100 100 100 100 100 100 10	epth D	epth W	ater
POD Number bas	in Use C	County	64	16	4	Sec	Tws	Rng	X	Y	WellW	/aterCol	umn
SJ 00200	OFM	SJ		3	3	23	28N	06W	281564	4057870*	1551		
SJ 03005	STK	RA	2	2	4	21	28N	06W	279663	4058421*	245	175	70
SJ 03043	STK	RA	2	2	4	21	28N	06W	279663	4058421*	290	240	50
SJ 03443	STK	RA	3	3	3	22	28N	06W	279854	4057809*	300		
SJ 03675	DOM	RA	4	3	4	14	28N	06W	282528	4059346	420	100	320
									Aver	age Depth to	Water:	171 fee	t
										Minimum	Depth:	100 fee	t
										Maximum	Depth:	240 feet	t

Record Count: 5


PLSS Search:

Section(s): 11, 10, 09, 16, **Township:** 28N

Range: 06W

15, 14, 23, 22,

21



DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO

Operator Meridian Cil Location: Unit M Sec. 15 Twp 28 Rng 6
Name of Well/Wells or Pipeline Serviced Sen Suan 28-6 # 436 #122 #417
Elevation 572 Completion Date 8-28-9/ Total Depth 424 Land Type F Casing Strings, Sizes, Types & Depths 100 8 Puc Casing
If Casing Strings are cemented, show amounts & types used 189-2/Sacks
If Cement or Bentonite Plugs have been placed, show depths & amounts used
Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. 220 Fresh
Depths gas encountered: NONE Ground bed depth with type & amount of coke breeze used: 429 Alsbury (oke - 124 Bags
Depths anodes placed: $\frac{124}{488-325}$, $\frac{194}{49-365}$, $\frac{194}{49-365}$, $\frac{194}{49-365}$, $\frac{194}{49-365}$, $\frac{194}{49-395}$, 194
Depths vent pipes placed: From Surface to 924
Vent pipe perforations: From 12c to 424
Remarks:

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

Form 3160-4 (November 1983) (formerty 9-330)

UN ED STATES

SUBMIT IN DUPL

₹•

Form approved. Budget Bureau No. 1004-0137 Expires August 31, 1985

(formerty 9-330)		,	D STA			r in Du	PL 4Segrap	Expire	as Augu	ist 31, 1985
	,	TMENT JREAU OF L			1.*	EUEL)	reverse	side) 5 1 LASE DE	7919	ON AND SERIAL NO.
WELL CO	MPLETION	OR REC	OMPLET			AND I		* L. 1 6. IF INDIAN	. ALLOT	TEE OR TRIBE NAME
. TYPE OF WEL		ELL WEI	<u> </u>	RY 🗌	Other 9111	3, 60		7. UNIT AGE	EEMENT	NASEB
. TYPE OF COM					Other 3115	" DEALE	igTOì	A, MM. San	Juan	28-6 Unit
WELL [3]	OVER DE	F.P Byci	DIF	NR 🗌	Other 019 1	Min in		5 FARM OR		
Paso Nat		c Compan	.,					Sall		28-6 Unit
		- Compan	Υ					9. WELL NO.	•	
DO BOY A		minaton	NIM Q	749 9				1		
PO Box 4.		-			y State regure	menta) *				om wildcar uitland Co
At surface	(11. part 1000)					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				H BEOCK AND SURVEY
At top prod. int	count renouted b	1410'	s, 178	5 ' W				OR AREA		
at top prod. Int	iervar reported t	ieio w						Sec.	15,T	'-28-N,R-6-
At total depth								NMPM	-	
				RMIT NO.	25 02 5	DATE ISSU	€D	12. COUNTY RABIBE R10 A		II3. STATE
DATE SPUDDED	16 DATE TO	REACHED 17	,	•						LEV. CASINGHEAD
19-91				. necurity 40	18.			RKB, RT, GB, ETC.)*	13. 6	CEY. CASINGEAU
TOTAL DEPTH. MD	1-22- 4 TVD 21. PL	UG. BACK T.D., MI	-23-91	2. IF ME L	TIPLE COMPL.		3 GI	ALS ROTARY TOO)LS	CABLE TOOLS
74 '	!			HOW M.	ANT*		DRILLE	yes yes	l	
PRODUCING INTER	RVAL(S), OF THE	S COMPLETION-	гор, воттом,	NAME (M	AD AND TVD)*	···		 	25.	WAS DIRECTIONAL SURVEY MADE:
										SURVEY MADE
itland ()							no
TYPE ELECTRIC A	· · · · · · · · · · · · · · · · · · ·								27. ₩ <i>i</i>	AS WELL CORED
NL/LDT/DI	LL/NGT/MI						77.			no
CABING SIZE	WEIGHT, LB		SET (MD)		i.E SIZE	set in wer		TING RECORD	 -	AMOUNT PULILED
8 5/8"	24.0#		28'	12 1	./4"	248	B Cu	ft.		
5 1/2"	15.5#	· ·	73'		/8"					
		LINER RECO	RD	·		30.		TUBING REC	ORD	
SIZE	TOP (MD)	BOTTOM (MD	SACKS C	EMENT*	SCREEN (MD		3/8"	DEPTH BET (M	(D)	PACKER SET (MD)
9						$-\frac{2}{}$	3/8	3413'		
PERFORATION REC	CORD (Interval,)	nze and number)		32.	ACID S	SHOT F	RACTURE, CEMEN	T SOME	TOW PTC
					DEPTH INT			AMOUNT AND KIR		
50-53 ', 3	3259-61',	3271 ∸7	41,		3250-	3432	_	5,620# 40		
05-23', 3	3410-32'	w/2 spf						.66,740# 2		
								.00,430 ga	I. f	luid
FIRST PRODUCT	ION PROI	DUCTION METHOD	(Florence of		OUCTION	nd tune a	W nu == n	1 991	97.70	(Producina or
					• •			ahu	42-in)	•
E OF TEST	HOURS TESTED			N. FOR	016		SHALL	WATER-BBI		production
			TEST	PERIOD		1	520	MCF - TOM	t UDD	U
W. TURING PRESS.	CASING PRESS			BB1	GAS-A	CF.	w.	TER-THE OF THE	4.00	AVITT-API (COME.)
SI 957	SI 960) 24-Hour	-		ļ		ROPE	blen,	hest.	
DISPOSITION OF G	AB (Sold, used fo	r fuel, vented, e	(c.)		 		Hoo,	TEST WITH	SEED BY	. 764
to be so	ld	BHP @	3400	1	067			WAK I'	wer !	AREM
LIST OF ATTACH	BENES							STON REST	Mine	- The state of the
none	where the same	(nm and	A Imfan-	- 12 2	1242 22 3 222	<u> a.</u> r.		EVEWIRGION	10 11	
(/	Luar tue torego	oug and attached	. intormatioi	r is comodi ⇔ ⊂i	corre	er as dete -tr ∧ ==	≕mined £ai∽	FORMALI AVAILABLE	-ecotas	
SIGNED	Wex Mi	Mpula	<u>C</u> ti	TLE	gurator	Y AL	TOTI	DAT	e <u>3</u>	-14-91
/ 7	. ,			ODET	NT GU					


SAN JUAN 28-6 UNIT 122N


AERIAL MAP

ConocoPhillips


SAN JUAN 28-6 UNIT 122N MINES MILLS & QUARRIES

Mines, Mills	& Quarries Commodity Groups
Δ	Aggregate & Stone Mines
•	Coal Mines
*	Industrial Minerals Mines
▽	Industrial Minerals Mills
	Metal Mines and Mill Concentrate
	Potash Mines & Refineries
a	Smelters & Refinery Ops.
*	Uranium Mines
€	Uranium Mills
Population	
⊖	Cities - major
Transportation	on
+++	Railways
	Interstate Highways
	Major Roads









Siting Criteria Compliance Demonstration & Hydro Geologic Analysis

The San Juan 28-6 Unit 122N is not located in an unstable area. The location is not over a mine and is not on the side of a hill as indicated on the Mines, Mills and Quarries Map and Topographic Map. The location of the excavated pit material will not be located within 300' of any continuously flowing watercourse or 200' from any other watercourse as indicated on the Topographic Map. The location is not within a 100-year floodplain area as indicated on the FEMA Map. The Cathodic well data from the San Juan 28-6 Unit NP 438 has an elevation of 6593' and groundwater depth of 220'. The subject well has an elevation of 6593' which is the same as the San Juan 28-6 Unit NP 438, therefore the groundwater depth is greater than 100'. There are no iWATERS data points located in the area as indicated on the TOPO Map. The hydro geologic analysis indicates the groundwater depth and the San Jose formation will create a stable area for this new location.

Hydrogeological report for San Juan 28-6 Unit 122N

Regional Hydrogeological context:

The San Jose Formation of Eocene age occurs in New Mexico and Colorado, and its outcrop forms the land surface over much of the eastern half of the central basin. It overlies the Nacimiento Formation in the area generally south of the Colorado-New Mexico State line and overlies the Animas Formation in the area generally north of the State line.

The San Jose Formation was deposited in various fluvial-type environments. In general, the unit consists of an interbedded sequence of sandstone, siltstone, and variegated shale. Thickness of the San Jose Formation generally increases from west to east (200 feet in the west and south to almost 2,700 feet in the center of the structural basin). Ground water is associated with alluvial and fluvial sandstone aquifers. Thus, the occurrence of ground water is mainly controlled by the distribution of sandstone in the formation. The distribution of such sandstone is the result of original depositional extent plus any post-depositional modifications, namely erosion and structural deformation. Transmissivity data for San Jose Formation are minimal. Values of 40 and 120 feet squared per day were determined from two aquifer tests (Stone et al, 1983, table 5). The reported or measured discharge from 46 water wells completed in San Jose Formation ranges from 0.15 to 61 gallons per minute and the median is 5 gallons per minute. Most of the wells provide water for livestock and domestic use.

The San Jose Formation is a very suitable unit for recharge from precipitation because soils that form on the unit are sandy and highly permeable and therefore readily adsorb precipitation. However, low annual precipitation, relatively high transpiration and evaporation rates, and deep dissection of the San Jose Formation by the San Juan River and its tributaries all tend to reduce the effective recharge to the unit.

Stone et al., 1983, Hydrogeology and Water Resources of the San Juan Basin, New Mexico: Socorro, New Mexico Bureau of Mines and Mineral Resources Hydrologic Report 6, 70 p.

Jaramillo, Marie E

From:

Jaramillo, Marie E

Sent:

Tuesday, June 30, 2009 1:17 PM

To:

'mark kelly@nm.blm.gov'

Subject:

SURFACE OWNER NOTIFICATION 06/30/09

Importance:

High

The subject well will have a temporary pit that will be closed on-site. Please let me know if you have any questions.

NEW DRILL

SAN JUAN 28-6 UNIT 119N SAN JUAN 28-6 UNIT 122N

The subject wells have a temporary pit that will be closed on-site. Please let me know if you have any questions.

PIT CLOSURE

SAN JUAN 31-6 UNIT 3M SAN JUAN 30-5 UNIT 73N

Marie Jaramillo

Staff Regulatory Tech.
ConocoPhillips
Office # (505) 326-9865
Fax # (505) 599-4062
mailto:marie.e.jaramillo@conocophillips.com

District I 1625 N. French Dr., Hobbs, NM 88240

State of New Mexico Energy, Minerals & Natural Resources Department

Revised October 12, 2005 Instructions on back Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410

District IV 1220 S St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION 1220 South St. Francis Dr.

Santa Fe, NM 87505

AMENDED REPORT

Form C-102


WELL LOCATION AND ACREAGE DEDICATION PLAT


'API Number	*Pool Code	³Pool Name				
	72319 / 71599	BLANCO MESAVERDE / BAS	SIN DAKOTA			
*Property Code	⁹ Pr	operty Name	⁵Well Number			
İ	SAN JU	122N				
'OGRID No	*Ope	erator Name	°Elevation			
14538 İ	BURLINGTON RESOURCES OIL & GAS COMPANY LP 6593					

North/South line Feet from the UL or lot no. Sect 100 Township Range Lot Idn Feet from the East/West line RIÓ К 15 28N 6W 1550 SOUTH 1540 WEST ARRIBA 11 Bottom Hole Location If Different From Surface


North/South line UL or lot no Sect 100 Township Range Lot Idn Feet from the Feet from the East/West line RIO **28N** 2300 SOUTH 300 WEST 15 6W ARRIBA 12 Dedicated Acres Joint or Infill ¹⁴ Consolidation Code ¹⁵ Order No 320.0 Acres - W/2 (MV) 320.0 Acres - W/2(DK)

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION





BURLINGTON RESOURCES OIL & GAS COMPANY SAN JUAN 28-6 UNIT #122N 1550' FSL & 1540' FWL, SECTION 15, T28N, R6W, NMPM RIO ARRIBA COUNTY, NEW MEXICO ELEVATION: 6593'



NCE SURVEYS IS NOT LIABLE FOR LOCATION OF UNDERGROUND UTILITIES OR PIPELINES.

CONTRACTOR SHOULD CONTACT ONE-CALL FOR LOCATION OF ANY MARKED OR UNMARKED UNDERGROUND UTILITIES OR PIPELINES ON WELLPAD AND/OR ACCESS ROAD AT LEAST TWO WORKING DAYS PRIOR TO CONSTRUCTION.

Burlington Resources Oil & Gas Company, LP San Juan Basin Pit Design and Construction Plan

In accordance with Rule 19.15.17 the following information describes the design and construction of temporary pits on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all temporary pits. A separate plan will be submitted for any temporary pit which does not conform to this plan.

- BR will design and construct a properly sized and approved temporary pit which will contain liquids and solids and should prevent contamination of fresh water and protect public health and environment.
- 2. Prior to constructing the pit, topsoil will be stockpiled in the construction zone for later use in restoration.
- 3. BR will sign the well location in compliance with 19.15.3.103 NMAC.
- 4. BR shall construct all new fences around the temporary pit utilizing 48" steel mesh field-fence (hogwire) on the bottom with a single strand of barbed wire on top. T-posts shall be installed every 12 feet and corners shall be anchored utilizing a secondary T-post. Temporary pits will be fenced at all times excluding drilling or workover operations, when the front side of the fence will be temporarily removed for operational purposes.
- 5. BR shall construct the temporary pit so that the foundation and interior slopes are firm and free of rocks, debris, sharp edges or irregularities to prevent liner failure.
- BR shall construct the pit so that the slopes are no steeper than two horizontal feet to one vertical foot.
- 7. Pit walls will be walked down by a crawler type tractor following construction.
- 8. All temporary pits will be lined with a 20-mil, string reinforced, LLDPE liner, complying with EPA SW-846 method 9090A requirements.
- Geotextile will be installed beneath the liner when rocks, debris, sharp edges or irregularities cannot be avoided.
- All liners will be anchored in the bottom of a compacted earth-filled trench at least 18 inches deep.
- 11. BR will minimize liner seams and orient them up and down, not across a slope. Factory seams will be used whenever possible. BR will ensure all field seams are welded by qualified personnel. Field seams will be overlapped four to six inches and will be oriented parallel to the line of maximum slope. BR will minimize the number of field seams in corners and irregularly shaped areas.
- 12. The liner shall be protected from any fluid force or mechanical damage through the use of mud pit slides, or a manifold system.
- 13. The pit shall be protected from run-off by constructing and maintaining diversion ditches around the location or around the perimeter of the pit in some cases.
- 14. The volume of the pit shall not exceed 10 acre-feet, including freeboard.
- 15. Temporary blow pits will be constructed to allow gravity flow to discharge into lined drill pit.
- 16. The lower half of the blow pit (nearest lined pit) will be lined with a 20-mil, string reinforced, LLDPE liner. The upper half of the blow pit will remain unlined as allowed in Rule 19.15.17.11 F.11.
- 17. BR will not allow freestanding liquids to remain on the unlined portion of a temporary blow pit.

Burlington Resources Oil & Gas Company, LP San Juan Basin Maintenance and Operating Plan

In accordance with Rule 19.15.17 the following information describes the operation and maintenance of temporary pits on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all temporary pits. A separate plan will be submitted for any temporary pit which does not conform to this plan.

- BR will operate and maintain a temporary pit to contain liquids and solids and maintain the integrity of the liner and liner system to prevent contamination of fresh water and protect public health and environment.
- 2. BR will conserve drilling fluids by transferring liquids to pits ahead of the rigs whenever possible. All other drilling fluids will be disposed at Basin Disposal Inc., permit # NM-01-005.
- 3. BR will not discharge or store any hazardous waste in any temporary pit.
- 4. If any pit liner's integrity is compromised, or if any penetration of the liner occurs above the liquid's surface, then BR shall notify the Aztec Division office by phone or email within 48 hours of the discovery and repair the damage or replace the liner.
- 5. If a leak develops below the liquid's level, BR shall remove all liquids above the damaged liner within 48 hours and repair the damage or replace the liner. BR shall notify the Aztec Division office by phone or email within 48 hours of the discovery for leaks less than 25 barrels. BR shall notify the Aztec Division office as required pursuant to Subsection B of 19.15.3.116 NMAC shall be reported within twenty-four (24) hours of discovery of leaks greater than 25 barrels. In addition, immediate verbal notification pursuant to Subsection B, Paragraph (1), and Subparagraph (d) of 19.15.3.116 NMAC shall be reported to the division's Environmental Bureau Chief.
- The liner shall be protected from any fluid force or mechanical damage through the use of mud pit slides, or a manifold system.
- 7. The pit shall be protected from run-off by constructing and maintaining diversion ditches around the location or around the perimeter of the pit in some cases.
- 8. BR shall immediately remove any visible layer of oil from the surface of the temporary pit after cessation of a drilling or workover operation. Oil absorbent booms will be utilized to contain and remove oil from the pit's surface. An oil absorbent boom will stored on-site until closure of pit.
- Only fluids generated during the drilling or workover process may be discharged into a temporary pit.
- 10. BR will maintain the temporary pit free of miscellaneous solid waste or debris.
- 11. During drilling operations, BR will inspect the temporary pit at least once daily to ensure compliance with this plan. Inspections will be logged in the IADC reports. BR will file this log with the Aztec Division office upon closure of the pit.
- 12. After drilling operations, BR will inspect the temporary pit weekly so long as liquids remain in the temporary pit. A log of the inspections will be stored at BR's office electronically and will be filed with the Aztec Division office upon closure of the pit.
- 13. BR shall maintain at least two feet of freeboard for a temporary pit.
- 14. BR shall remove all free liquids from a temporary pit within 30 days from the date the operator releases the drilling rig.
- 15. BR shall remove all free liquids from a cavitation pit within 48 hours after completing cavitation. BR may request additional time to remove liquids from the Aztec Division office if it is not feasible to remove liquids within 48 hours.

Burlington Resources Oil & Gas Company, LP San Juan Basin Closure Plan

In accordance with Rule 19.15.17.12 NMAC the following information describes the closure requirements of temporary pits on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all temporary pits. A separate plan will be submitted for any temporary pit which does not conform to this plan.

All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of pit closure. Closure report will be filed on C-144 and incorporate the following:

- Details on Capping and Covering, where applicable.
- Plot Plan (Pit Diagram)
- Inspection Reports
- Sampling Results
- C-105
- Copy of Deed Notice will be filed with County Clerk

- All free standing liquids will be removed at the start of the pit closure process from the pit and disposed of in a division—approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011).
- 2. The preferred method of closure for all temporary pits will be on-site burial, assuming that all the criteria listed in sub-section (B) of 19.15.17.13 are met.
- 3. The surface owner shall be notified of BR's closing of the temporary pit prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 4. Within 6 months of the Rig Off status occurring BR will ensure that temporary pits are closed, re-contoured, and reseeded.
- 5. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email, or verbally. The notification of closure will include the following:
 - i. Operator's name
 - Location by Unit Letter, Section, Township, and Range. Well name and API number.
- 6. Liner of temporary pit shall be removed above "mud level" after stabilization. Removal of liner will consist of manually or mechanically cutting liner at mud level and removing all remaining liner. Care will be taken to remove "All" of the liner i.e., edges of liner entrenched or buried. All excessive liner will be disposed of at the San Juan County Landfill located on CR 3100.
- 7. Pit contents shall be mixed with non-waste containing, earthen material in order to achieve the solidification process. The solidification process will be accomplished using a combination of natural drying and mechanically mixing. Pit contents will be mixed with non-waste, earthen material to a consistency that is deemed a safe and stable. The mixing ratio shall not exceed 3 parts clean soil to 1 part pit contents.
- 8. A five point composite sample will be taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	_500
Chlorides	EPA 300.1	(1000/500

- 9. Upon completion of solidification and testing standards being passed, the pit area will be backfilled with compacted, non-waste containing, earthen material. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater. If standard testing fails BR will dig and haul all contents pursuant to 19.15.17.13.i.a. After doing such, confirmation sampling will be conducted to ensure a release has not occurred.
- 10. During the stabilization process if the liner is ripped by equipment the Aztec OCD office will be notified within 48 hours and the liner will be repaired if possible. If the liner can not be repaired then all contents will be excavated and removed.
- 11. Dig and Haul Material will be transported to the Envirotech Land Farm located 16 miles south of Bloomfield on Angel Peak Road, CR 7175. Permit # NM010011
- 12. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Reshaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 13. Notification will be sent to OCD when the reclaimed area is seeded.
- 14. BR shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality) Source No. two (better quality) Purity 50 percent 80 percent Purity Germination 40 percent Germination 63 percent 50 percent Percent PLS 20 percent Percent PLS 5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS


15. The temporary pit will be located with a steel marker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial upon the abandonment of all the wells on the pad. The marker will be flush with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information at the time of all wells on the pad are abandoned. The operator's information will include the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Design and Construction

In accordance with NMAC 19.15.17 the following information describes the design and construction of below grade tanks on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all below grade tanks (BGT). A separate plan will be submitted for any BGT which does not conform to this plan.

- 1. BR will design and construct a properly sized and approved BGT which will contain liquids and should prevent contamination of fresh water to protect the public health and environment.
- 2. BR signage will comply with 19.15.3.103 NMAC when BR is the operator. If BR is not the operator it will comply with 19.15.17.11NMAC. BR includes Emergency Contact information on all signage.
- 3. BR has approval to use alternative fencing that provides better protection. BR constructs fencing around the BGT using 4 foot hog wire fencing topped with two strands of barbed wire, or with a pipe top rail. A six foot chain link fence topped with three strands of barbed wire will be use if the well location is within 1000 feet of permanent residence, school, hospital, institution or church. BR ensures that all gates associated with the fence are closed and locked when responsible personnel are not onsite.
- 4. BR will construct a screened, expanded metal covering, on the top of the BGT.
- 5. BR shall ensure that a below-grade tank is constructed of materials resistant to the below-grade tank's particular contents and resistant to damage from sunlight as shown on design drawing and specification sheet.
- The BR below-grade tank system shall have a properly constructed foundation consisting of a level base free of rocks, debris, sharp edges or irregularities to prevent punctures, cracks or indentations of the liner or tank bottom as shown on design drawing.
- 7. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a belowgrade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 8. BR will construct and use a below-grade tank that does not have double walls. The below-grade tank's side walls will be open for visual inspection for leaks, the below-grade tank's bottom is elevated a minimum of six inches above the underlying ground surface and the below-grade tank is underlain with a geomembrane liner to divert leaked liquid to a location that can be visually inspected.

- 9. BR has equipped the below-grade tanks with the ability to detect high level in the tank and provide alarm notification and shutdown process streams into the tank. Once high level is detected RTU logic closes the inlet separator sales valve and does not permit vent valve to open. This shutdown of the sales valve and gagging of the vent valves prevents any hydrocarbon process streams from entering the pit tank once a high level is detected. Furthermore, an electronic page is sent to the BR MSO for that well site and to the designated contract "Water-Hauling" Company indicating a high level and that action must be taken to address this alarm. The environmental drain line from BR's compressor skid under normal operating conditions is in the open position. The environmental drain line is in place to capture any collected rain water or spilled lubricants from our compressor skids. The swab drain line is a manually operated drain and by normal operating procedures is in the closed position. The tank drain line is also a manually operated drain and during normal operations it is in the closed position.
- 10. The geomembrane liner consists of a 45-mil flexible LLDPE material manufactured by Raven Industries as J45BB. This product is a four layer reinforced laminated containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. The J45BB is reinforced with 1300 denier (minimum) tri-directional scrim reinforcement. It exceeds ASTMD3083 standard by 10%. J45BB has a warranty for 20 years from Raven Industries and is attached. It is typically used in Brine Pond, Oilfield Pit liner and other industrial applications. The manufacture specific sheet is attached and the design attached displays the proper installation of the liner.
- The general specification for design and construction are attached in the BR document.



ConocoPhillips

San Juan Business Unit

PRODUCED WATER PIT TANK
OPEN TOP GRAVITY FLOW TANK
INTERNALLY COATED WITH
12-14 MILS AMERON AMERCOAT 385

PROPERTIES	TEST METHOD	J30EE		136 56		JASBE	
P		Min. Roll Averages	Fypical Roll Averages	Min. Roll Averages	Typical Roll Averages	Min Roll Averages	Typical Roll Averages
Appearance		Black/Black		Black/Black		Black/Black	
Thickness	ASTM D 5199	27 mil	30 mil	32 mil	36 mil	40 mil	45 mil
Weight Lbs Per MSF (oz/yd²)	ASTM D 5261	126 lbs (18.14)	140 lbs (20.16)	151 lbs (21.74)	168 lbs (24.19)	189 lbs (27 21)	210 lbs (30.24)
Construction		**Extrusion laminated with encapsulated tri-directional scrim reinforcement					
Ply Adhesion	ASTM D 413	16 lbs	20 lbs	19 lbs	24 lbs	25 lbs	31 lbs
1" Tensile Strength	ASTM D 7003	88 lbf MD 63 lbf DD	110 lbf MD 79 lbf DD	90 lbf MD 70 lbf DD	113 lbf MD 87 lbf DD	110 lbf MD 84 lbf DD	138 lbf MD 105 lbf DD
1" Tensile Elongation @ Break % (Film Break)	ASTM D 7003	550 MD 550 DD	750 MD 750 DD	550 MD 550 DD	750 MD 750 DD	550 MD 550 DD	750 MD 750 DD
1" Tensile Elongation @; Peak % (Scrim Break)	ASTM D 7003	20 MD 20 DD	33 MD 33 DD	20 MD 20 DD	30 MD 31DD	20 MD 20 DD	36 MD 36 DD
Tongue Tear Strength	ASTM D 5884	75 lbf MD 75 lbf DD	97 lbf MD 90 lbf DD	75 lbf MD 75 lbf DD	104 lbf MD 92 lbf DD	100 lbf MD 100 lbf DD	117 lbf MD 118 lbf DD
Grab Tensile	ASTM D 7004	180 lbf MD 180 lbf DD	218 lbf MD 210 lbf DD	180 lbf MD 180 lbf DD	222 lbf MD 223 lbf DD	220 lbf MD 220 lbf DD	257 lbf MD 258 lbf DD
Trapezoid Tear	ASTM D 4533	120 lbf MD 120 lbf DD	146 lbf MD 141 lbf DD	130 lbf MD 130 lbf DD	189 lbf MD 172 lbf DD	160 lbf MD 160 lbf DD	193 lbf MD 191 lbf DD
* Dimensional Stability	ASTM D 1204	<1	<0.5	<1	<0.5	<1	<0.5
Puncture Resistance	ASTM D 4833	50 lbf	64 lbf	65 lbf	83 lbf	80 lbf	99 lbf
Maximum Use Temperature		180° F	180° F	180° F	180° F	180° F	180° F
Minimum Use Temperature		-70° F	-70° F	-70° F	-70° F	-70° F	-70° F

MD = Machine Direction
DD = Diagonal Directions



Note: Minimum Roll Averages are set to take into account product variability in addition to testing variability between laboratories.

*Dimensional Stability Maximum Value

**DURA-SKRIM J30BB, J36BB & J45BB are a four layer reinforced laminate containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. DURA-SKRIM J30BB, J36BB & J45BB are reinforced with a 1300 denier (minimum) tri-directional scrim reinforcement.

Note: FAYEN INDUSTRIES MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO no quarantee of satisfactory results from relance upon contained information or recommendations and bisolaims of unionty for resulting loss or damage.

PLANT LOCATION

Sioux Falls, South Dakota

SALES OFFICE

P.O. Box 5107 Sioux Falls, SD 57117-5107 (605) 335-0174 (605) 331-0333 FAX **800-635-3456**



08/06

RAVEN INDUSTRIES INC. EXPOSED GEOMEMBRANE LIMITED WARRANTY

Raven Industries Inc. warrants Dura-Skrim J30BB, J36BB, and J45BB to be free from manufacturing defects and to be able to withstand normal exposure to sunlight for a period of 20 years from the date of sale for normal use in approved applications in the U.S. and Canada, excluding Hawaii. This warranty is effective for products sold and shipped from January 1, 2008 to December 31, 2008. These dates will be updated prior to December 31, 2008.

This Limited Warranty does not include damages or defects in the Raven geomembrane resulting from acts of God, casualty or catastrophe including but not limited to: earthquakes, floods, piercing hail, or tornadoes. The term "normal use" as used herein does not include, among other things improper handling during transportation, unloading, storage or installation, the exposure of Raven geomembranes to harmful chemicals, atypical atmospheric conditions, abuse of Raven geomembranes by machinery, equipment or people; improper site preparation or covering materials, excessive pressures or stresses from any source or improper application or installation. Raven geomembrane material warranty is intended for commercial use only and is not in effect for the consumer as defined in the Magnuson Moss Warranty or any similar federal, state, or local statues. The parties expressly agree that the sale hereunder is for commercial or industrial use only.

Should defects or premature loss of use within the scope of the above Limited Warranty occur, Raven Industries Inc. will, at its option, repair or replace the Raven geomembrane on a pro-rata basis at the then current price in such manner as to charge the Purchaser/User only for that portion of the warranted life which has elapsed since purchase of the material. Raven Industries Inc. will have the right to inspect and determine the cause of any alleged defect in the Raven geomembrane and to take appropriate steps to repair or replace the Raven geomembrane if a defect exists which is covered under this warranty. This Limited Warranty extends only to Raven's geomembrane, and does not extend to the installation service of third parties nor does it extend to materials furnished or installed by others in connection with the intended use of the Raven geomembranes.

Any claim for any alleged breach of this warranty must be made in writing, by certified mail, to the General Manager of Engineered Films Division of Raven Industries Inc. within ten (10) days of becoming aware of the alleged defect. Should the required notice not be given, the defect and all warranties are waived by the Purchaser, and Purchaser shall not have any rights under this warranty. Raven Industries Inc. shall not be obligated to perform repairs or replacements under this warranty unless and until the area to be repaired or replaced is clean, dry, and unencumbered. This includes, but is not limited to, the area made available for repair and/or replacement of Raven geomembrane to be free from all water, dirt, sludge, residuals and liquids of any kind. If after inspection it is determined that there is no claim under this Limited Warranty, Purchaser shall reimburse Raven Industries Inc. for its costs associated with the site inspection.

In the event the exclusive remedy provided herein fails in its essential purpose, and in that event only, the Purchaser shall be entitled to a return of the purchase price for so much of the material as Raven Industries Inc. determines to have violated the warranty provided herein. Raven Industries Inc. shall not be liable for direct, indirect, special, consequential or incidental damages resulting from a breach of this warranty including, but not limited to, damages for loss of production, lost profits, personal injury or property damage. Raven Industries Inc. shall not be obligated to reimburse Purchaser for any repairs, replacement, modifications or alterations made by Purchaser unless Raven Industries Inc. specifically authorized, in writing, said repairs, replacements, modifications or alteration in advance of them having been made. Raven Industry's liability under this warranty shall in no event exceed the replacement cost of the material sold to the Purchaser for the particular installation in which it failed.

Raven Industries Inc. neither assumes nor authorizes any person other than the undersigned of Raven Industries Inc. to assume for it any other or additional liability in connection with the Raven geomembrane made on the basis of the Limited Warranty. The Limited Warranty on the Raven geomembrane herein is given in lieu of all other possible material warranties, either expressed or implied, and by accepting delivery of the material; Purchaser waives all other possible warranties, except those specifically given. This Limited Warranty may only be modified by written document mutually executed by Owner and Raven Industries Inc.

Limited Warranty is extended to the purchaser/owner and is non-transferable and non-assignable; i.e., there are no third-party beneficiaries to this warranty.

Purchaser acknowledges by acceptance that the Limited Warranty given herein is accepted in preference to any and other possible materials warranties.

THIS LIMITED WARRANTY SHALL BE GOVERNED BY SOUTH DAKOTA LAW AND VENUE FOR ALL LEGAL PROCEEDINGS IN CONNECTION WITH THIS LIMITED WARRANTY SHALL BE IN MINNEHAHA COUNTY, SOUTH DAKOTA. RAVEN INDUSTRIES INC. MAKES NO WARRANTY OF ANY KIND OTHER THAN THAT GIVEN ABOVE AND HEREBY DISCLAIMS ALL WARRANTIES, BOTH EXPRESSED OR IMPLIED, OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THIS IS THE ONLY WARRANTY THAT APPLIES TO THE MATERIALS REFERRED TO HEREIN AND RAVEN INDUSTRIES INC DISCLAIMS ANY LIABILITY FOR ANY WARRANTIES GIVEN BY ANY OTHER PERSON OR ENTITY, EITHER WRITTEN OR ORAL.

RAVEN INDUSTRIES' WARRANTY BECOMES AN OBLIGATION OF RAVEN INDUSTRIES INC. TO PERFORM UNDER THE WARRANTY ONLY UPON RECEIPT OF FINAL PAYMENT AND EXECUTION BY A DULY AUTHORIZED OFFICER OF RAVEN INDUSTRIES INC.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Maintenance and Operating Plan

In accordance with Rule 19.15.17 the following information describes the operation and maintenance of Below Grade Tank (BGT) on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all BGT. A separate plan will be submitted for any BGT which does not conform to this plan.

- BR will operate and maintain a BGT to contain liquids and solids and maintain
 the integrity of the liner, liner system and secondary containment system to
 prevent contamination of fresh water and protect public health and environment.
 BR will accomplish this by performing an inspection on a monthly basis, installing
 cathodic protection, and automatic overflow shutoff devices as seen on the
 design plan.
- 2. BR will not discharge into or store any hazardous waste in the BGT.
- 3. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a belowgrade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 4. As per 19.17.15.12 Subsection D, Paragraph 3, BR will inspect the below-grade tank at least monthly reviewing several items which include 1) containment berms adequate and no oil present, 2) tanks had no visible leaks or sign of corrosion, 3) tank valves, flanges, and hatches had no visible leaks and 4) no evidence of significant spillage of produced liquids. In addition, BR's multi-skilled operators (MSOs) are required to visit each well location once per week. If detected on either inspection, BR shall remove any visible or measurable layer of oil from the fluid surface of a below-grade tank in an effort to prevent significant accumulation of oil overtime. The written record of the monthly inspections will include the items listed above and will be maintained for five years.
- 5. BR shall require and maintain a 10" adequate freeboard to prevent overtopping of the below-grade tank.
- 6. If the below grade tank develops a leak, or if any penetration of the pit liner or below grade tank, occurs below the liquid's surface, then BR shall remove all liquid above the damage or leak line within 48 hours. BR shall notify the appropriate district office. BR shall repair or replace the pit liner or below grade tank, within 48 hours of discovery. If the below grade tank or pit liner does not demonstrate integrity, BR shall promptly remove and install a below grade tank or pit liner that complies with Subsection I of 19.15.17.11 NMAC. BR shall notify the appropriate district office of a discovery of leaks less than 25 barrels as required pursuant to Subsection B of 19.15.3.116 NMAC shall be reported within twenty-four (24) hours of discovery of leaks greater than 25 barrels. In addition, immediate verbal notification pursuant to Subsection B, Paragraph (1), and Subparagraph (d) of 19.15.3.116 NMAC shall be reported to the division's Environmental Bureau Chief.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Closure Plan

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of Below Grade Tanks (BGTs) on Burlington Resources Oil & Gas Company, LP locations hereinafter known as BR locations. This is BR's standard procedure for all BGTs. A separate plan will be submitted for any BGT which does not conform to this plan.

General Requirements:

- 1. BR shall close a below-grade tank within the time periods provided in Subsection A of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) permitted below-grade tanks within 60 days of cessation of the below-grade tank's operation., or c) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.
- 2. BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.
- 3. BR will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves. Documentation of how the below-grade tank was disposed of or recycled will be provided in the closure report.
- 4. If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless the equipment is required for some other purpose.
- 5. BR shall test the soils beneath the below-grade tank to determine whether a release has occurred. BR shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyze for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 100 mg/kg; and the chloride concentration, as determined by EPA method 300.1 or other EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration, whichever is greater. BR shall notify the division of its results on form C-141.
- 6. If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

- 7. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site.
- 8. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.
- 9. The surface owner shall be notified of BR's closing of the below-grade tank prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 11. BR shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federally jurisdicted lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. BR will repeat seeding or planting will be continued until successful vegetative growth occurs.
- 12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.
- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the belowgrade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation
 - Re-vegetation application rates and seeding techniques
 - Photo documentation of the site reclamation
 - Confirmation Sampling Results
 - Proof of closure notice