Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

FEB 01 2010

FORM APPROVED OM B No 1004-0137 Expires: March 31, 2007

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Land Manage	Politicus Carron
Do not use this form for proposals to drill or to repentantion Fleid O	net Indian, Allottee or Tribe Name
abandoned well. Use Form 3160 - 3 (APD) for such proposals.	

abandoned well.	ose Form 3100-3 (/				
SUBMIT IN TRIPLICATE- Other instructions on reverse side.		7. If Unit or CA	VAgreement, Name and/or No.		
1. Type of Well ✓ Oil Well ☐ ☐	Gas Well Of Other			9 Wall Name	and No.
2. Name of Operator Nacogdoches Oil & Gas Inc.			8. Well Name and No. South Hospah #53		
	l & Gas Inc.			9. API Well N	
34 Address PO Box 632418, Nacogdoches TX. 75963		3b. Phone No. (include area code) 936-560-4747			3 (-20278 pol, or Exploratory Area
4. Location of Well (Footage, Sec., T., R	R, M, or Survey Description)			South Hos	pah
950' FNL & 330' FEL				11. County or P	arish, State
Section 12 17N 9W			•	McKinley	
12. CHECK APPR	OPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, I	report, or o	THER DATA
TYPE OF SUBMISSION		TYP	E OF ACTION	,	
	Acidize .	Deepen	Production (St	art/Resume)	Water Shut-Off
✓ Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete		Other Drill Laterals
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	☐ Temporarily A ☐ Water Disposal		
If the proposal is to deepen direction Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for the NOC plans to re-enter the Sou into the Upper Hospah Sand @	ed operations. If the operation in Abandonment Notices shall be fi final inspection.) Ath Hospah #53 and drill (5)	results in a multiple complified only after all requiren	etion or recompletion nents, including reclan	in a new interval, a f nation, have been con	form 3160-4 shall be filed once impleted, and the operator has
Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for the NOG plans to re-enter the Sou	ed operations. If the operation in Abandonment Notices shall be fifinal inspection.) 1th Hospah #53 and drill (5) 1526'.	results in a multiple complified only after all requiren	etion or recompletion nents, including reclan	in a new interval, a f nation, have been con	form 3160-4 shall be filed once impleted, and the operator has
Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for I NOC plans to re-enter the Sou into the Upper Hospah Sand @	ed operations. If the operation in Abandonment Notices shall be fifinal inspection.) 1th Hospah #53 and drill (5) 1526'.	results in a multiple complified only after all requiren	etion or recompletion nents, including reclan	in a new interval, a f nation, have been con	form 3160-4 shall be filed once inpleted, and the operator has gree, 270 degree, 315 degree
Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for I NOC plans to re-enter the Sou into the Upper Hospah Sand @	ed operations. If the operation in Abandonment Notices shall be fifinal inspection.) 1th Hospah #53 and drill (5) 2 1526'. r lateral footages.	results in a multiple complified only after all requiren 5) 90 degree 600' Later:	etion or recompletion nents, including reclan als at 360 degree, 13	in a new interval, a f nation, have been con	Form 3160-4 shall be filed once inpleted, and the operator has gree, 270 degree, 315 degree
Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for I NOC plans to re-enter the Sou into the Upper Hospah Sand @	Approve	esults in a multiple complified only after all requiren 9 90 degree 600' Later: ed for high presoration and dire	etion or recompletion nents, including reclan als at 360 degree, 18	in a new interval, a f nation, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involve testing has been completed. Final A determined that the site is ready for I NOC plans to re-enter the Sou into the Upper Hospah Sand @	Approve	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction	etion or recompletion nents, including reclan als at 360 degree, 18 ssure water ectional	in a new interval, a f nation, have been con	form 3160-4 shall be filed once inpleted, and the operator has gree, 270 degree, 315 degree
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for f NOG plans to re-enter the Sou into the Upper Hospah Sand @	Approve	esults in a multiple complified only after all requiren 9 90 degree 600' Later: ed for high presoration and dire	etion or recompletion nents, including reclan als at 360 degree, 18 ssure water ectional	in a new interval, a f nation, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for I NOG plans to re-enter the Sou into the Upper Hospah Sand @ Please see the attached plat for	Approve Approve Approve This is	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction	etion or recompletion nents, including reclan als at 360 degree, 18 ssure water ectional	in a new interval, a f nation, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for f NOG plans to re-enter the Sou into the Upper Hospah Sand @ Please see the attached plat for 14. Thereby certify that the foregoing Name (Printed/Typed)	Approve Approve Approve This is	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction s not a drilling of	etion or recompletion ents, including reclamates at 360 degree, 18 as at	in a new interval, a f nation, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for f NOG plans to re-enter the Sou into the Upper Hospah Sand @ Please see the attached plat for Name (Printed/Typed) Mike Allen	Approve Approve Approve This is	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction completion not a drilling of	etion or recompletion tents, including reclamates at 360 degree, 18 as at 360 degree, 18 as at 360 degree water ectional operation	in a new interval, a fination, have been con	Form 3160-4 shall be filed once inpleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for I NOC plans to re-enter the Sou into the Upper Hospah Sand @ Please see the attached plat for Please see the attached plat for Name (Printed/Typed) Mike Atlen Signature	Approve performance and correct Approve performance and correct	esults in a multiple complified only after all requiren 3) 90 degree 600' Laters ed for high presoration and direction s not a drilling of	etion or recompletion tents, including reclamates at 360 degree, 18 sure water ectional operation	in a new interval, a fination, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for f NOG plans to re-enter the Sou into the Upper Hospah Sand @ Please see the attached plat for Please see the attached plat for Name (Printed/Typed) Mike Allen Signature	Approve performand correct This is gistrue and correct	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction completion not a drilling of Title VP Date	etion or recompletion tents, including reclamates at 360 degree, 18 sure water ectional operation	in a new interval, a fination, have been con	RCVD FEB 8 OIL CONS. C
Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for I NOG plans to re-enter the Sou into the Upper Hospah Sand @ Please see the affached plat for Please see the affached plat for Name (Printed/Typed) Mike Affen Signature	Approve performance and correct Approve performance and correct	esults in a multiple complified only after all requiren 9 90 degree 600' Laters ed for high presoration and direction completion not a drilling of Title VP Date	etion or recompletion ents, including reclar als at 360 degree, 13 essure water ectional ectional exercice at the completion exercice at the completion exercice ectional exercice ectional exercice exer	in a new interval, a fination, have been con	Form 3160-4 shall be filed once impleted, and the operator has gree, 270 degree, 315 degree RCVD FEB 8

(Instructions on page 2)

1 74 • **13** 3 € South Hospah-C52931 Santa Fe Railroad A 81 9 80 9 76 17N 17N 8269 **•**4 8270

Well No. 35 Spot Locations:

Well Bore is 330' FNL 850' FEL

360° @ 600'= -271' FNL 850' FEL

90° @ 500'= 330' FNL 350' FEL

135° @ 600'= 630' FNL 550' FEL

180° @ 600'= 930' FNL 850' FEL

225° @ 600'= 630' FNL 1150' FEL

270° @ 600'= 330' FNL 1450' FEL

Well No. 53 Spot Locations:

Well Bore is 950' FNL 330' FEL

360° @ 600'= 350' FNL 330' FEL

180° @ 600'= 1550' FNL 330' FEL

225° @ 600'= 1250' FNL 630' FEL

270° @ 600'= 950' FNL 930' FEL

315° @ 600'- 650' FNL 630' FEL