Form 3160- 5 (November, 1996)

UNITED STATES DEPARTMENT OF THE INTERIOR 19 BUREAU OF LAND MANAGEMENT

FORM APPROVED

OMB No. 1004- 0135

Expires: July 31, 1996

1

SUNDRY NOTICES AND REPORTS ON WELL'S

Do not use this form for proposals to dillion to re-enter an abandoned well. Use Form 3160-3 (APQ) for such proposals.

5. Lease Serial No.

SF-078988
6 If Indian, Allottee, or Tribe Name

		Arms 1 - ON D X Shill A	25/	
SUBMIT IN TRIPL	ICATE- Other Instru	ctions on the reverse side	7. If Unit or CA. Agreement Designation.	
1. Type of Well			Northeast Blanco Unit	
Oil Well X Gas Well	Other	~ (9.5 # 5.7)	8. Well Name and No.	
2. Name of Operator			NEBU 61A	
Devon Energy Production Co. L.P. Attn: Kenny Rhoades			9. API Well No.	
3a. Address		3b. Phone No. (include area code)	30-045-31272	
1751 Highway 511 Na	avajo Dam, NM 87419	(505)320-6310	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T.,	R., M., or Survey Description)		Blanco Mesaverde Basin Dakota	
2000' FNL & 75' FEL	SE /4, NE /4	, Sec. 19 , T 31N R. 6W	11. County or Parish, State	
Latitude	Longitude	UNIT H	San Juan NM	
12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
TYPE OF SUBMISSION		TYPE OF ACTION	N	
Notice of Intent	Acidize	Deepen Production (Start/	/ Resume) Water Shut-off	
_	Altering Casing	Fracture Treat Reclamation	Well Integrity	
X Subsequent Report	Casing Repair	New Construction Recomplete	Other	
_	Change Plans	Plug and abandon Temporarily Aban	don Zonal Isolation	
Final Abandonment Notice	Convert to Injection	Plug back Water Disposal		
•		nt details including estimated starting date of any p		
it the proposal is to deepen direction	onaliy or recomplete norizontally, ç	give subsurface locations and measured and true v	vertical depuis or pertinent markers and sands.	

Primary cement job on well yielded no cement to surface. CBL log showed TOC at 760'. A void was present across L Shot squeeze holes at 6600' and 6100'. Pumped 80 sx (16.8 bbls) class "H" cement under retainer into holes at 6600'. Pumped 25 sx (5 bbls) Class "H" into holes at 6100'. Pressure tested holes at 6600' to 1500 psi-OK.

Attach the Bond under which the work will performed or provide the Bond No. on file with the BLM/ BIA. Required susequnet reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in anew interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has

Pumped 50 sx (10.5 bbls) Class "H" cement into holes at 6100' under retainer. Pressure tested holes to 1500 psi-OK.

BHT in 30 days cP-KR

6/1/ 1/4	JU CATS CP-KK	
14. I hereby certify that the foregoing is true and correct. Name (Printed/ Typed)	Title	
Kenny Rhoades	Company Representative	
My Whon	12-30-03 CERTED FOR DECOR	
Approved by	DERAL OR STATE OFFICE USE Title Date JAN 1 3 2004	
Conditions of approval, if any are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject leas which would entitle the applicant to conduct operations thereon.	1 mm 2 mm	

Title 18 U.S.C. Section1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitio or fraudulent statements or representations as to any matter within its jurisdiction.

determined that the site is ready for final inspection.)