

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
OMB NO. 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
*Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.*

OCT 01 2010

SUBMIT IN TRIPLICATE - Other instructions on page 2

Farmington Field Office
Bureau of Land Management

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other		5. Lease Serial No. NMM-16473
2. Name of Operator XTO ENERGY INC.		6. If Indian, Allottee or Tribe Name
3a. Address 382 CR 3100 AZTEC, NM 87410	3b. Phone No. (include area code) 505-333-3176	7. If Unit or CA/Agreement, Name and/or No. Gen
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1850' FNL & 810' FWL SWNW SEC. 31 (E) - T26N-R12W N.M.P.M.		8. Well Name and No. GALLEGOS FEDERAL 26-12-31 #15
		9. API Well No. 30-045-31904
		10. Field and Pool, or Exploratory Area Basin Fruitland Coal
		11. County or Parish, State SAN JUAN NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
☐ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off
☒ Subsequent Report	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
☐ Final Abandonment Notice	☐ Casing Repair	☐ New Construction	☐ Recomplete	☐ Other
	☐ Change Plans	☒ Plug and Abandon	☐ Temporarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

XTO Energy Inc. has plugged and abandoned this well per the attached morning report.

RCVD OCT 5 '10
OIL CONS. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) TEENA M. WHITING		Title REGULATORY COMPLIANCE TECHNICIAN
Signature <i>Teena M. Whiting</i>		Date 9/30/2010
THIS SPACE FOR FEDERAL OR STATE OFFICE USE		
Approved by	Title	Date OCT 04 2010
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office FARMINGTON FIELD OFFICE	

NNMOCD

Gallegos Federal 26-12-31-01S

From: 9/27/2010

MIRU A-Plus rig #5. TOH & LD 1-1/4" x 22' PR w/10' lnr, 2 - 3/4" rod subs (2', 8'), 35 - 3/4" rods, 9 - 3/4" rods w/4 molded guides per rod, 21K shear tl, 1 - 3/4" rod w/4 molded guides per rod, 1" x 1' LS, spiral rod guide & 2" x 1-1/4" x 10' RHAC-Z pmp w/1" x 1' strnr nip (XTO #1339).

9/28/2010

TOH tbg & SN. TIH 4-1/2" csg scr, xo & 34 jts 2-3/8" tbg. No ti spots. TOH 34 jts 2-3/8" tbg, xo & 4-1/2" csg scr. TIH 4-1/2" CICR. Set CICR @ 1,088'. Ld & PT tbg to 1,200 psig. Tstd OK. Sting out of CICR. Ppd 16 BLW dwn tbg & circ TCA to surf. PT csg to 650 psig for 10 min. Tstd OK. Ppd 29 sks Class B cmt. Ppd cmt plg fr/1,088' - 706'. TOH & LD tbg. Ld & PT BH to 400 psig w/0.5 BLW for 5 min. Tstd OK. Ppd 21 sks Class B cmt. Ppd cmt plg fr/231' to surf. Circ 1/2 bbl cmt to surf. TOH & LD 7 jts 2-3/8" tbg & stinger. WOC per NMBLM.

9/29/2010

Dug cellar @ WH. Cut & remove WH. TIH 4 jts PVC tbg in 4-1/2" csg. Tgd @ 36' FS. Ppd 2.5 sks Class B cmt. Ppd cmt plg fr/36' to surf. Cut off PVC. TIH 3 jts 1" PVC tbg in csg ann. Tgd @ 26' FS. Ppd 2.4 sks Class B cmt. Ppd cmt plg fr/20' to surf. Cut off PVC. Weld on P&A marker. RDMO A-Plus rig #5. FR for P&A.