## AMENDED

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

FEB 15 2011 BUREAU OF LAND MANAGEMENT Earniming Field Office Sundry Notices and Reports on Wells Sureau of Land Management Lease Number SF-078813 Type of Well 6. If Indian, All. or **GAS** Tribe Name 7. **Unit Agreement Name** 2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY LP 8. Well Name & Number 3. Address & Phone No. of Operator Cooper 100 PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-045-34881 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Surface: Unit P (SESE), 1034' FSL & 788' FEL, Section 7, T29N, R11W, NMPM Basin FC / Fulcher-Kutz PC **County and State** 11. San Juan, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Notice of Intent Abandonment Completion Report Change of Plans Recompletion New Construction Subsequent Report Plugging Non-Routine Fracturing Water Shut off Casing Repair Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations PLEASE SEE ATTACHED - Amended FC & PC perfs. 14. I hereby certify that the foregoing is true and correct. Dollie L. Busse Title Staff Regulatory Technician Date 2-14-11 (This space for Federal or State Office use) APPROVED BY Title Date CONDITION OF APPROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ASSEPTED FOR RECORD

FEB 2 2 2011

FARASHGTON FIELD OFFICE



Cooper 100 API #30-045-34881 Basin FC / Fulcher-Kutz PC Page Two

11/16/2010 RU Basin W/L. RIH w/ 3 ¾" gauge ring. Run GR/CCL/CBL Logs. TOC @

surface. RD W/L 11/16/10.

**12/17/2010** Install Frac valve. PT csg to 4100#/30min @ 14:15hrs on 12/17/10. Test – OK.

**12/17/2010** RU Basin W/L to Perf **Pictured Cliffs** w/ .40" diam. – 1 SPF @ 1928'–1926', 1924', 1922, 1920' = 5 Total Holes. Acidize w/ 12bbls 10% Formic Acid. Frac w/ 21,168gals 75% N2 Foam 25# Linear Gel w/ 61,497# 20/40 Brady

sand. Set CFP @ 1806'.

Perf Fruitland Coal w/ .40" diam. – 3SPF @ 1731'-1734', 1742'-1744', 1770'-1778' = 39 Holes. 2SPF @ 1658'-1662', 1684'-1694' = 28 Holes. 1SPF @ 1880'-1892' = 12 Holes. 79 Total Holes. Acidize w/ 12bbls 10% Formic Acid. Frac w/ 25,452gals 75% N2 Foam 25# Linear Gel w/ 90,583# 20/40 Brady sand.

N2:982,000SCF. Start Flowback.

**12/20/2010** RIH w/ CBP set @ 1550'. RD Flowback & Frac Equip.

01/10/2011 MIRU Key 28. ND WH. NU BOPE. PT BOPE. Test – OK.

Tag CBP set @ 1550' & M/O. Flowback.

01/12/2011 C/O & M/O CFP @ 1806'. C/O to PBTD @ 2085'. Flowback.

01/17/2011 Flow Test PC & FC.

01/18/2011 RIH w/ 4 ½" RBP set @ 1900' @ 08:00hrs. Flow test FC. RIH, latch onto RBP &

release @ 12:00hrs. RIH w/ 61jts, 2 3/8", 4.7#, J-55 tbg set @ 1922' w/ F-Nipple

@ 1921'. ND BOPE. NU WH. RD RR @ 17:30hrs on 1/18/11.