Submit 3 Copies To Appropriate District Office	State of New Me			Form C-103	
District I	Energy, Minerals and Natur	rai Resources	WELL API NO.	Revised May 08, 2003	
1625 N. French Dr., Hobbs, NM 87240 District II	OIL CONSERVATIO	NDIVISION	30-045-31804		
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.?		5. Indicate Type of L	ease	
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM/87505		STATE 🗌	FEE 🗴	
District.IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	(2)	FEB 200	6. State Oil & Gas L	ease No.	
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name:					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C 101) FOR SUCH PROPOSALS.)					
1. Type of Well:	of We <u>ll:</u>			/8. Well Number	
Oil Well Gas Well Z 2. Name of Operator	Other CO 9 3		9. OGRID Number		
-	XTO Energy Inc.			167067	
3. Address of Operator			10. Pool name or Wildcat		
2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401			BASIN FRUITLAND COAL		
4. Well Location					
Unit Letter C: 1090' feet from the FNL line and 1510 feet from the FWL line					
Section 29	Township 29N	Range 10W	NMPM	County SAN JUAN	
	11. Elevation (Show whether	DR, RKB, RT, GR, etc	c.)		
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
			SEQUENT REPO		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	·	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLI		PLUG AND ABANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB			
OTHER:		OTHER: TO & ST F	RODUCTION CSG	x	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date					
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.					
Reached driller's TD of 1,958' KB @ 3:00 a.m. 02/17/04. TIH w/47 jts 4-1/2", 10.5#, J-55, ST&C csg to					
1,951.47' KB. Cmt'd csg w/250 sx Type III cmt w/8% gel, 1/4#/sx celloflake & 2% Phenoseal (11.4 ppg, 3.03					
cuft/sx) followed by80 sx Type III w/1% CaCl2, 1/4#/sx celloflake & 2% Phenoseal (14.5 ppg, 1.41					
cuft/sx). Circ 15 bbls cmt to surf. Released Stewart Brothers Rig #51 @ 12:00 a.m., 02/18/04.					
PRODUCTION CSG WILL BE PRESSURE TSTD @ COMPLETION					
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE	Matter	LE DRILLING	ENGINEER D	ATE 02/18/04	
7	V	LE PAGE	D.	ATE - 02/10/04	
Type or print name JEFF W. PATTO	N		Telephon	e No. 505-324-1090	
(This space for State use)	7	DEPUTY OIL & GAS IT		reb 23 2004	
APPROVED BY Conditions of approval, if any:	TIN	TLE	DA	TE	