District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tasts, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

74/4

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances Dugan Production Corp. OGRID#: 006515 Operator: 709 East Murray Drive, Farmington, New Mexico 87401 RCVD JH 15'08 Address: OIL CONS. DIV. Facility or well name: Hoss Com #90-S API Number: 30-045-34501 OCD Permit Number: _Township 23N Range 11W U/L or Qtr/Qtr P Section 11 County: Longitude 107.96885 West Center of Proposed Design: Latitude 36.23731 North NAD: []1927 [1983 Surface Owner: X Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC Closed-loop System: Subsection H of 19.15.17.11 NMAC Temporary: X Drilling Workover Drying Pad Tanks Haul-off Bins Other ☐ Permanent ☐ Emergency ☐ Cavitation ☐ Lined ☐ Unlined __mil | LLDPE | HDPE | PVC X Lined ☐ Unlined Liner type: Thickness Liner type: Thickness 20 mil X LLDPE HDPE PVC ☐ Other Seams: Welded Factory Other X String-Reinforced Seams: Welded A Factory Other Volume: 600 bbl Dimensions: L 76' xW 13' xD 8' Dimensions: Length x Width Below-grade tank: Subsection I of 19.15.17.11 NMAC Fencing: Subsection D of 19.15.17.11 NMAC Chain link, six feet in height, two strands of barbed wire at top Volume: Type of fluid: Four foot height, four strands of barbed wire evenly spaced between one and Tank Construction material: Netting: Subsection E of 19.15.17.11 NMAC Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting Other ☐ Monthly inspections ☐ Visible sidewalls and liner ☐ Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC 12'x24', 2' lettering, providing Operator's name, site location, and Other _ Liner type: Thickness_ mil | HDPE | PVC emergency telephone numbers Signed in compliance with 19.15.3.103 NMAC Other Alternative Method: Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration 19.15.17 NMAC for guidance. of approval. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe

Oil Conservation Division

MPR 2010

OIL CONS. DIV. DIST. 3

Environmental Bureau office for consideration of approval.

Page 1 of 4

	
Siting Criteria (regarding permitting): 19.15 to NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of Ecceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.	
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☒ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map: Visual inspection (certification) of the proposed site	☐ Yes 🏻 No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☒ No ☐ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☒ No ☐ NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes 🗵 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes 🕅 No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes 🏻 No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes 🗓 No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes 🖾 No
Within a 100-year floodplain FEMA map	☐ Yes 🖾 No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.15 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2)-of-Subsection B of 19.15.17.12 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
☑ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: 30-045- or Permit Number:	
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	
Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
NMAC	
Previously Approved Design (attach copy of design) API Number:	

Permanent Pits Permit	Application Checklis. Jubsection B of 19.15.17.9 NMAC see following items must be attached to the application. Please indicate, by a check mark in the box, that the a	documents a			
attached.	e journing action times of mineral to the upplications. I lease multiply if a cheek mark in the obly that the a	.Jennens u			
	port - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.15 NMAC				
	Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Climatological Fac					
	ing Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC				
	d Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC sign - based upon the appropriate requirements of 19.15.17.11 NMAC				
Leak Detection De	is and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC				
	is and Companiontry Assessment - based upon the appropriate requirements of 19.13.17.11 NMAC islant and Installation Plan				
	ntenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Freeboard and Ove	propping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
	dous Odors, including H ₂ S, Prevention Plan				
☐ Emergency Respon	nse Plan				
Oil Field Waste Str	ream Characterization				
☐ Monitoring and Ins					
Erosion Control Pla					
	ed upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Proposed Closure: 19.1:	5.17.13 NMAC				
Type: X Drilling W	orkover 🗌 Emergency 🗋 Cavitation 🔲 Permanent Pit 🔲 Below-grade Tank 🔲 Closed-loop System [Alternati			
- -					
Proposed Closure Method	l: Waste Excavation and Removal				
	☑ On-site Closure Method (only for temporary pits and closed-loop systems)				
	☑ In-place Burial ☐ On-site Trench Burial				
	Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for co	nsideration)			
Siting Criteria (regardin	ng on-site closure methods only): 19.15.17.10 NMAC	f			
	criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable	ì			
	ded below. Requests regarding changes to certain siting criteria may require administrative approval from				
	ffice or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau				
	of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10				
NMAC for guidance.	, , , , , , , , , , , , , , , , , , , ,	į.			
		1			
- 0					
Ground water is less than	50 feet below the bottom of the buried waste.				
Ground water is less than	50 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ ☑ NA			
Ground water is less than - NM Office of the					
Ground water is less than NM Office of the Ground water is between	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	X NA			
Ground water is less than NM Office of the Ground water is between NM Office of the	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	X NA Yes C X NA			
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste.				
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	X NA Yes C X NA			
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells n 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells				
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells n 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, takebed, sinkhole, or playa lake				
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous contin	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells n 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, takebed, sinkhole, or playa lake				
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous contin	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site	X NA Yes □ NA Yes □ NA Yes □ NA Yes □			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous conti	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application.				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous conti	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site	X NA Yes □ NA Yes □ NA Yes □ NA Yes □			
Ground water is less than NM Office of the Ground water is between the NM Office of the Ground water is more than NM Office of the Within 300 feet of a continuous	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a continue of the ordination of the ordinati	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock	X NA Yes □ NA Yes □ NA Yes □ NA Yes □			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a pee Visual inspection Within 500 horizontal feet watering purposes, or with	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image				
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map. Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock in 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated muni	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock hin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS.	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image it of a private, domestic fresh water well or spring that less than five households use for domestic or stock ini 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended.				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS.	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells inuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock hin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetla	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality	X NA Yes NA Yes NA Yes Yes Yes Yes Yes			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting the ordination of	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. life Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	X NA Yes			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetland US Fish and Wild	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. life Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site a subsurface mine.	X NA Yes NA Yes NA Yes Yes Yes Yes Yes			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetland US Fish and Wild	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. life Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	X NA Yes			
Ground water is less than NM Office of the Ground water is between NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map. Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetland US Fish and Wild Within the area overlying Written confirmat	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells nuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). ; Visual inspection (certification) of the proposed site rmanent residence, school, hospital, institution, or church in existence at the time of initial application. (certification) of the proposed site; Aerial photo; Satellite image t of a private, domestic fresh water well or spring that less than five households use for domestic or stock nin 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. life Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site a subsurface mine.	X NA Yes			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting the ordination of	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells incously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake ary high-water mark). State Engineer - iWATERS database search; USGS; Data obtained from nearby wells incounting the proposed site in the proposed site in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site; Aerial photo; Satellite image It of a private, domestic fresh water well or spring that less than five households use for domestic or stock in 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. life Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site a subsurface mine. ion or verification or map from the NM EMNRD-Mining and Mineral Division				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a pe Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetlater US Fish and Wild Within the area overlying Written confirmat Within an unstable area. Engineering meas	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells incomplete in the state of the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the state of the proposed site incomplete in the proposed site; Aerial photo; Satellite in the proposed site; Aerial photo; Satellite image it of a private, domestic fresh water well or spring that less than five households use for domestic or stock in 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. Ilife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site a subsurface mine. ion or verification or map from the NM EMNRD-Mining and Mineral Division were incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	X NA Yes			
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting the ordination of the ordination	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells incomplete in the state of the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the proposed search; USGS; Data obtained from nearby wells incomplete in the state of the proposed site incomplete in the proposed site; Aerial photo; Satellite in the proposed site; Aerial photo; Satellite image it of a private, domestic fresh water well or spring that less than five households use for domestic or stock in 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. State Engineer - iWATERS database; Visual inspection (certification) of the proposed site cipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance A 1978, Section 3-27-3, as amended. ion or verification from the municipality; Written approval obtained from the municipality and. Ilife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site a subsurface mine. ion or verification or map from the NM EMNRD-Mining and Mineral Division were incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological				
Ground water is less than NM Office of the Ground water is between: NM Office of the Ground water is more than NM Office of the Ground water is more than NM Office of the Within 300 feet of a conting Topographic map Within 300 feet from a per Visual inspection Within 500 horizontal feet watering purposes, or with NM Office of the Within incorporated munical adopted pursuant to NMS. Written confirmat Within 500 feet of a wetlater of the water of the water of the water of the within source of the within source of the within source of the within source of the water	State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 50 and 100 feet below the bottom of the buried waste State Engineer - iWATERS database search; USGS; Data obtained from nearby wells in 100 feet below the bottom of the buried waste. State Engineer - iWATERS database search; USGS; Data obtained from nearby wells incomplete incomplet	X NA Yes X NA Yes X NA Yes X X X X X X X X X			

*

. .

Waste Excavation and Removal Closure 1			
closure plan. Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (or liquids, drilling fluids and drill cuttings)			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facility			
or facilities for the disposal of liquids, drilling fluids and drill cuttings.			
Disposal Facility Name: Disposal Facility Permit Number:			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate,			
by a check mark in the box, that the documents are attached.			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
 			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.			
1			
Name (Print): Kurt Fagrelius Title: Vice President, Exploration			
Signature: Kurt Fagralin Date: 7-11-08			
Signature: // Url Tegreum Date: /- 11 00			
e-mail address: kfagrelius@duganproduction.com Telephone: 505-325-1821 (0), 505-320-8248 (C)			
OCD Approval: Permit Application (including closure plan) Closure Plan (only)			
OCD Representative Signature: Bel Sel Doll 3/3/1/ Approval Date: 8-4-08			
Approval Date: 6-7-08			
Title: Egyico /spec OCD Permit Number:			
The state of the s			
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC			
☑ Closure Completion Date: 2-26-2609			
Closure Method:			
☐ Waste Excavation and Removal ☑ On-Site Closure Method ☐ Alternative Closure Method ☐ If different from approved plan, please explain.			
~			
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check			
mark in the box, that the documents are attached. Proof of Closure Notice			
Proof of Deed Notice (if applicable)			
☑ Plot Plan			
Confirmation Sampling Analytical Results			
☑ Waste Material Sampling Analytical Results ☑ Disposal Facility Name and Permit Number			
Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Technique			
Site Reclamation (Photo Documentation)			
On-site Closure Location: Latitude 36.23723/V Longitude 107.96870 W NAD: 1927 2 1983			
Operator Closure Certification:			
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and			
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print): Kurt Fagrelius Title: Vice President, Exploration			
Signature: Sunt terms Date; 2-8-2010			
Signature: /W//ECM/ Date: 2020			

Dugan Production Corp. Closure Report

Lease Name: Hoss Com #90-S

API No.: 30-045-34521

In accordance with Rule 10.15.17.13 NMAC the following information describes the closure of the temporary pit referenced above. All proper documentation concerning closure activities is included with the C-144. The temporary pit for this location was an approved design under Rule 19.15.17. **The closure plan for the temporary pit was submitted on 7-11-2008 and approved on 8-4-2008.**

1. Comply with siting criteria for temporary pits established by the State of New Mexico, Energy Minerals and Natural Resources Department 19.15.17.10 NMAC.

See approved permit dated 8-4-2008.

2. Provide the NMOCD district office at least 72-hours notice but no greater than 1-week prior to any closure operations. Notice will include operator name, well name and number, API number, and location (unit letter, section, township and range).

See email notification dated 2-18-2009.

3. Provide the surface owner notice of the operator's proposal of an on-site closure method. Proof of notice will be attached to the permit application. Also, proof of closure notice will be provided by certified mail to surface owner after closure. Proof of notice will be attached to final closure report.

Federal Surface, certified notification not applicable as per BLM/OCD MOU, however, proof of notification is attached.

4. Remove all liquid from pit and reclaim, re-use or dispose of at an NMOCD approved facility. Upon completion of drilling operations, drilling mud will be vacuumed from pit and transported to the next reserve pit for re-use at another drilling location. After the remaining mud settles, the free water that shakes out and any free water left over from completion operations will be hauled to the Dugan Production operated Sanchez O'Brien #1 SWD located 1650 feet from the South line and 990 feet from the West line (Unit L) of Section 6, Township 24 North, Range 9 West NMPM, San Juan County, New Mexico. The disposal facility was permitted by the NMOCD with Administrative Order SWD-694.

Drilling rig was released (9-12-2008) and drilling mud was transferred to the Hoss Com #94 for re-use (9-13-2008). Remaining free water was transferred to the Sanchez O'Brien SWD #1 salt water disposal well.

5. Remove all fluids from temporary pit within 30-days and close within 6-months following release of drilling rig.

Free water was removed within 30-days and temporary pit was closed (2-20-2009).

6. Air dry pit contents and stabilize or solidify to a load bearing capacity sufficient to support the temporary pit's final cover.

Pit contents were allowed to dry prior to temporary pit closure.

7. Collect a five point, composite sample of the pit contents to demonstrate that Benzene, BTEX, the GRO and DRO combined fraction, TPH. and chlorides (depth to groundwater from bottom of pit is greater than 100-feet), do not exceed the standards as specified in 19.15.17.9.B or the background concentration, whichever is greater.

A five point composite sample was taken of remaining cuttings in temporary pit and was tested in accordance with Subsection B of 19.15.17.13 (B)(1)(b)(ii). Depth from bottom of pit to top of ground-water is greater than 100-feet. Sample results are attached.

Components	Test Method	Limit (mg/kg)	*Results (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2	< 0.0009
BTEX	EPA SW-846 8021B or 8260B	50	0.0156
TPH	EPA SW-846 418.1	2500	954
GRO/DRO	EPA SW-846 8015M	500	53.3
Chlorides	EPA 300.1	1000 / 500	245

8. Other methods if the standards in 19.15.17.9.B can not be met will include: The pit contents may be mixed to a ratio not to exceed 3:1, un-contaminated soil or other material to pit contents. A second five point, composite sample of the contents after treatment or stabilization will be taken to demonstrate that the contents do not exceed the standards. If the second soil analyses do no satisfy the closure standards, the operator will close the temporary pit using the waste excavation and removal method.

Not applicable, testing standards of 19.15-17.9 were met.

9. Cut pit liner off at the mud line (solids level); remove liner and apron and transport to a NMOCD approved facility for disposal.

Pit liner was removed 2-20-2009 and disposed of at the Crouch Mesa Waste Management facility on 4-2-2009 (see attached invoice).

10. Stockpiled sub-surface soil will be used to backfill pit and re-contour well pad (to a final or intermediate cover that blends with the surrounding topography). A minimum of four-feet of compacted, non-waste containing, earthen material will be used as backfill.

Stockpiled sub-surface soil was used to backfill temporary pit and re-contour well pad. A minimum of four-feet of compacted, non-waste containing, earthen material was used to backfill pit.

11. Stockpiled surface soil will be used as a cover over the backfilled pit and disturbed areas of the well pad no longer needed for production operations. The soil cover will include either the background thickness of top soil or one foot of suitable material to establish vegetation at the site whichever is greater.

Stockpiled surface soil was used to cover backfilled temporary pit and disturbed areas of the well pad no longer needed for production operations. The soil cover included the greater of either the background thickness or one foot of suitable material necessary to establish vegetation. The location was re-contoured to approximate the original topography of the site and diversions were constructed to protect soil cover and minimize erosion.

12. The area will be re-seeded as per BLM guidelines. Re-seeding will be repeated until 70% of the native natural cover is achieved and maintained for two successive growing seasons. The first growing season after the pit is closed the disturbed area will be re-seeded. The seeding method will be to drill on contour whenever possible.

The area was re-seeded according to BLM/OCD guidelines in May of 2009. The BLM less than 10" seed mix was drilled in at a rate of 2.5# per acre. Re-seeding will be repeated if needed until 70% of the native natural cover is achieved. Re-seeding will be done according to BLM guidelines as specified by BLM/OCD memorandum of understanding.

13. The NMOCD will be notified once successful re-vegetation has been achieved.

Re-seeding will be done according to BLM guidelines as specified by BLM/OCD memorandum of understanding.

14. A steel marker will be set at the center of the on-site burial following onsite-pit closure (see application for administrative approval). The marker will be (24" X 24") and will have the operator name, lease name, well number, location (UL, Sec., Twp. and Rge.) and that it designates an "on-site burial location" lettering welded on the

top side with a 4" threaded collar welded to the bottom side. The marker will be set at ground level and attached to a 4" diameter pipe that is cemented in a hole three feet deep. When the well is abandoned, a steel riser that is 4" in diameter, extending 4' above the ground will be welded to the pipe anchored in cement below the surface. The riser will have lettering welded on side showing operator name, well number, location (UL, Sec., Twp., and Rge.) and that it designates an on-site burial location.

A flat steel marker (24" X 24") with the lettering "on-site burial location" was set at ground-level in the center of the burial site. The marker is welded to a 4" pipe that is cemented in a 3-foot deep hole and is shown in the attached photographs (administrative approval was received). When the well is P&A'd, the steel plate will be removed and a riser that is 4" in diameter, extending 4' above the ground will be welded to the pipe anchored in cement below the surface. The riser will have lettering welded on the side showing operator name, well number, location (UL, Sec., Twp., and Rge.) and that it designates an on-site burial location.

- 15. Closure Report will be submitted within 60-days of completion of temporary pit closure. Closure report will include the following: 1) Proof of Closure Notice.

 - 2) Proof of Deed Notice (if applicable).
 - 3) Plot Plan.
 - 4) Confirmation Sampling Analytical Results.
 - 5) Waste Material Sampling Analytical Results.
 - 6) Disposal Facility Name and Permit Number.
 - 7) Soil Backfilling and Cover Installation.
 - 8) Re-vegetation Application Rates and Seeding Technique.

All items listed above if applicable are attached and submitted on this date.

16. A deed notice identifying the exact location of the on-site burial will be filed with the County clerk in the county where the on-site burial occurs.

Federal Surface, deed notice identifying exact location of on-site burial is not applicable according to BLM/OCD MOU.

Kurt Fagrelius

From: Kurt Fagrelius

Sent: Friday, December 12, 2008 4:32 PM

To: brandon.powell@state.nm.us; Mark_Kelly@nm.blm.gov

Subject: Close Temporary Pits

Dear Mr. Powell and Mr. Kelly: with this e-mail I am notifying you of Dugan Production Corp's. plans to close the temporary pits on the Hoss Com #97, Hoss Com #90-S, Hoss Com #93 and Hoss Com #94 on Tuesday December 16, 2008 beginning at approximately 8 AM. If weather conditions or some other unforeseen problem comes up that prevents us from doing this work, I will contact you as soon as possible.

If you have any questions or require additional information, please contact me.

Sincerely, Kurt Fagrelius

Kurt Fagrelius

From: Kurt Fagrelius

Sent: Wednesday, December 17, 2008 9:32 AM

To: brandon.powell@state.nm.us; Mark_Kelly@nm.blm.gov

Subject: FW: Close Temporary Pits

8". Will have to let pits dry out before scheduling a date to close. Hope to close sometime in the 1st or 2nd week of January 2009, weather permitting. The due date for closure on these pits is Hoss Com #97 – 1/3/09, Hoss Com #90S – 1/10/09, Hoss Com #94 – 1/17/09 and Hoss Com #93 – 1/24/09. With this e-mail I am asking for an extension of time to enable us to dry the pits out again (30-60 days). The soil analysis are all below the allowed threshold Dear Sirs: Inclement weather has spoiled plans to close the Hoss 97, 90-S, 93 and 94 tomorrow (12-18-2008) Latest storm dropped 4-5 inches total depth is 6-

If you have any questions or require additional information, please contact me

Sincerely, Kurt Fagrelius

From: Kurt Fagrelius

Sent: Monday, December 15, 2008 1:32 PM

To: 'brandon.powell@state.nm.us'; 'Mark_Kelly@nm.blm.gov'

Subject: FW: Close Temporary Pits

after the first of January 2009. Dear Sirs: Due to the storm that went through the area over the weekend, Dugan is canceling plans to close the Hoss 97, 90-S, 93 and #94 until Thursday December 18, 2008. Again this is dependent on weather conditions. If we are unable to close on Thursday, will notify both of you and re-schedule for sometime

If you have any questions or require additional information, please contact me.

Sincerely, Kurt Fagrelius

From: Kurt Fagrelius

Sent: Friday, December 12, 2008 4:32 PM

To: 'brandon.powell@state.nm.us'; 'Mark_Kelly@nm.blm.gov'

Subject: Close Temporary Pits

Dear Mr. Powell and Mr. Kelly: with this e-mail I am notifying you of Dugan Production Corp's. plans to close the temporary pits on the Hoss Com #97, Hoss Com #90-S, Hoss Com #93 and Hoss Com #94 on Tuesday December 16, 2008 beginning at approximately 8 AM. If weather conditions or some other unforeseen problem comes up that prevents us from doing this work, I will contact you as soon as possible.

If you have any questions or require additional information, please contact me

Sincerely, Kurt Fagrelius

Kurt Fagrelius


From: Kurt Fagrelius

Sent: Wednesday, February 18, 2009 7:39 AM

To: brandon.powell@state.nm.us; Mark_Kelly@nm.blm.gov

Subject: Drilling Reserve Pit Closures

Dear Sirs: on Friday February 20, 2009 Dugan Production Corp. will close the Drilling Reserve Pits for the Hoss Com #97, #90-S, #93 and #94. If you have any questions or require additional information, please contact me. Sincerely, Kurt Fagrelius



Mr. Dave Mankiewicz Assistant Field Manager Bureau of Land Management 1235 La Plata Highway Farmington, New Mexico 87401 April 6, 2009

RE: Certification Notice of On-Site Closure of Temporary Pit for the Hoss Com #90-S

Return Receipt Certification Number

7005 1820 0001 6168 7390

Dear Mr. Mankiewicz:

In accordance with the New Mexico Oil Conservation Division "Pit Rule" (19.15.17 NMAC), the Bureau of Land Management is hereby being notified that the "Temporary Pit" (drilling reserve pit for the Hoss Com #90-S, located on Federal surface) was closed "On-Site" in accordance with 19.15.17 NMAC.

If you have any questions or require additional information on this matter, please contact me.

me.	-		
Sincerely, Surt Fig vo	COMPLETE THIS SECTION ON DELIVERY	6164 7340 600 600 600 600 600 600 600 600 600 6	Postal Servicem RTIFIED MAIL RECEIPT Contraction Medical Contraction Visits cur website at www.arspr.com Postage \$ Certified Fee Postage \$ Postage \$
 Complete items 1, 2, and 3. Also complete item 4 if Restricted Delivery is desired. Print your name and address on the reverse so that we can return the card to you. Attach this card to the back of the mailpiece, or on the front if space permits. 	2 Septending	☐ Agent ☐ Addressee tte of Delivery	I'm Receipt Fee Heris 4 Heris 4
1. Article Addressed to: Davet Manhiew.ca, - AFM bereau of Land Management 1235 Ku Hata Huy		□ Yes □ No	Dave Markieure - 6LM pt. No.; 1235 La Plata Hurr 10, 21944 10, 219
Farmington MM 87401	3. Service Type Certified Mail Registered Return Receipt for C.O.D. 4. Restricted Delivery? (Extra Fee)) NE: (505) 325-1821 • FAX# (505) 327-4613
2. Article Number (Transfer from service label) 7005	1820 0001 6168 7390		
PS Form 3811, February 2004 Domestic Ret	urn Receipt 102	2595-02-M-1540	1



Chloride

Client: Dugan Prod Project #: 06094-0003 Hoss Com 90-S Sample ID: Date Reported: 12-10-08 Lab ID#: 48445 12-08-08 Date Sampled: Sample Matrix: Soil Date Received: 12-08-08 Preservative: Cool Date Analyzed: 12-11-08 Condition: Intact Chain of Custody: 5892

Parameter

Concentration (mg/Kg)

Total Chloride

245

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Hoss Com.

Analyst

Mustum Weeters Review

EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	Dugan Prod	Project #:	06094-0003
Sample ID:	Hoss Com 90-S	Date Reported:	12-15-08
Laboratory Number:	48445	Date Sampled:	12-08-08
Chain of Custody No:	5892	Date Received:	12-08-08
Sample Matrix:	Soil	Date Extracted:	12-10-08
Preservative:	Cool	Date Analyzed:	12-10-08
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons	954	5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Hoss Com.

Analyst



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Dugan Prod	Project #:	06094-0003
Sample ID:	Hoss Com 90-S	Date Reported:	12-16-08
Laboratory Number:	48445	Date Sampled:	12-08-08
Chain of Custody No:	5892	Date Received:	12-08-08
Sample Matrix:	Soil	Date Extracted:	12-11-08
Preservative:	Cool	Date Analyzed:	12-12-08
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	53.3	0.1
Total Petroleum Hydrocarbons	53.3	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Hoss Com

Analyst



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Dugan Prod.	Project #:	06094-0003
Sample ID:	Hoss Com 90-S	Date Reported:	12-16-08
Laboratory Number:	48445	Date Sampled:	12-08-08
Chain of Custody:	5892	Date Received:	12-08-08
Sample Matrix:	Soil	Date Analyzed:	12-12-08
Preservative:	Cool	Date Extracted:	12-11-08
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	0.9	фr
Toluene	8.0	1.0	
Ethylbenzene	1.8	1.0	•
p,m-Xylene	3.0	1.2	
o-Xylene	2.8	0.9	
Total BTEX	15.6		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Hoss Com

Analyst

CHAIN OF CUSTODY RECORD

					-	7	7	/												
S/PARAMETERS		(1	.814	HA⁻ } Hq⁻	- >	7	>	7								λ	2			
ANALYSI		noir	nA \	JStlon)										6	0			5-632-0615	
	(1208 t	pou	təM) TiəM	VOC (3 /	7	7	7							y: (Signatude)		y: (Signature)	y: (Signature)		
	(9108) (A)				,		7	7								Ž.	Received b	Received b	TECH ington, NM 87	
	2 in his		2003		snos eg	Indge	ludge snoons	Indge	ludge snoenb	ludge Judge	ndge ludge	ndge snoenb	snoenb	Indge Indge		(2)				
S / Location:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		06094-0	San	Solid	Solid Discoli	Solid	Solid	Soil S	Soil Si Solid A	Soil SI Solid Ac	Soil SI Solid Ac	Soil Si Solid A	Soil Si	\$	27			U.S. Highwa	
//oss C		Client No.:			6h8h	2	hhsh ww	Am 4844											5796	-
prod	2		3578	m	200	0									nature)	non	nature)	nature)		
Ingago,	int Address:	int Phone No.:		Sample No./ Identification		Com	}	7							nquished by: (Sign	wit Tegi	nquished by: (Sigr	nquished by: (Sign		
	bool o	Analysis/Parameters Additions: Sampler Name: Additions: Analysis/Parameters Additions: Additions: Additions: Additions: Additions: Additions: Additions: Analysis/Parameters Analysis/Parameters	Analysis / Parameters Analysis / Parameters Analysis / Parameters Sampler Name: $\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Analysis / Project Name / Location: Addiress: Sampler Name: Addiress: Sampler Name: Sampler Name: Sampler N	Analysis / Project Name / Location: Addiress: Sampler Name: Lab No. Marrix Lab No. Marrix	Analysis Parameters Project Name Location: Analysis Parameters	10 10 10 10 10 10 10 10	Composition Composition	And the size of the solid Aqueous	Andly Sis / Parameters: **Address:** **Add	Analysis / Paramet Location: Address: ***Constitution** Com \$7 \cap 2 \cap 3 \cap 4	ANALYSIS / PARAMETERS Andress ANALYSIS / PARAMETERS Andress Analysis / Comp C	100 oct Name Location: 100 oct Name 100 oct Name	14,227 70 d 14,625 2000 23 miles Name 1,000 2000	1, 1, 2, 3 7, 4 7, 6 7, 7, 7 7, 7	Collect Name Location: Constitution: C	100 100	Project Name	The Sample Name Cotation: Cotation:	Clear No. Clear No. Co. Clear No. Co. Clear No. Co. Clear No. Clear No.



EPA METHOD 418.1 TOTAL PETROLEUM **HYROCARBONS** QUALITY ASSURANCE REPORT

Client:

QA/QC

Project #:

N/A

Sample ID:

QA/QC

Date Reported:

12-15-08

Laboratory Number:

12-11-TPH.QA/QC 48445

Date Sampled:

N/A

Sample Matrix:

Freon-113

Date Analyzed:

12-11-08

Preservative: Condition:

N/A N/A

Date Extracted: Analysis Needed: 12-11-08

TPH

Calibration

I-Cal Date

C-Cal Date

I-Cal RF:

C-Cal RF:

% Difference 4.4%

Accept. Range

12-03-08 12-11-08 1,590

1,520

+/- 10%

Blank Conc. (mg/Kg)

Concentration

Detection Limit

TPH

ND

19.1

Duplicate Conc. (mg/Kg)

TPH

Sample

Duplicate

% Difference

Accept. Range

954

763

20.0%

+/- 30%

Spike Conc. (mg/Kg) **TPH**

Sample 954

Spike Added 2,000

2,480

84.0%

Spike Result % Recovery Accept Range 80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 48437 - 48441, 48445 - 48448 and 48456 - 48457.



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

and the second s					was an experience of the second
Client:	QA/QC		Project #:		N/A
Sample ID:	12-12-08 QA/	QC	Date Reported:		12-16-08
Laboratory Number:	48422		Date Sampled:		N/A
Sample Matrix:	Methylene Chlo	ride	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		12-12-08
Condition:	N/A		Analysis Reques	ted:	TPH
Principle (Constitution of State of the Constitution of the Consti				where common your marketing it on the rest property	naganak a stonaturajan, a sampapirayayyay (jabbis a nasaby
	I-Cel Date	A-UCal RF	C-Gal RF:	% Difference	Accept Range
Gasoline Range C5 - C10	05-07-07	9.9667E+002	9.9707E+002	0.04%	0 - 15%
Diesel Range C10 - C28	05-07-07	1.0028E+003	1.0032E+003	0.04%	0 - 15%
ESTAIN TO THE THE PROPERTY OF THE PROPERTY STATES FOR THE PROPERTY AND A THE PROPERTY OF THE P		ang Ti, ang Calonya ng panggangan pangganang panggan ang manggan	na asan pagawan ngi tuyah mad in magahini M _a m bi kapiking ti Jumi, Brigill Ma	and the control of th	• &
Blank Cone. (mg/L = mg/Kg)		 Concentration 		Detection Limit	
Gasoline Range C5 - C10		ND		0.2	
Diesel Range C10 - C28		ND		0.1	•
Total Petroleum Hydrocarbons		ND		0.2	
indigen per 1711 es viver fraggrad Terskopprober annam en generalementer best			*		7
Duplicate Conc. (mg/Kg)	Sample :	:: Düplicate	% Difference	Accept Range	
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%	
Diesel Range C10 - C28	ND	ND	0.0%	0 - 30%	
Spike Conc. (mg/Kg)	ee = Sample = =	Spike-Added	Spike Result	% ₂ Recovery	Accept Range
Gasoline Range C5 - C10	ND	250	246	98.4%	75 - 125%
Diesel Range C10 - C28	ND	250	248	99.2%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 48422, 48423, 48435, 48445 - 48448, 48453, 48454.

Analyst



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	12-12-BT QA/QC	Date Reported:	12-16-08
Laboratory Number:	48422	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	12-12-08
Condition:	N/A	Analysis:	BTEX

Calibration and E : Detection Limits (ug/L		C-Cal/RF/ Accept Rang	% %Diff je 0 -15%	Blank Gond	Detect Limit
Benzene	1.3292E+006	1.3318E+006	0.2%	ND	0.1
Toluene	1.2791E+006	1.2817E+006	0.2%	ND	0.1
Ethylbenzene	1.1612E+006	1.1635E+006	0.2%	ND	0.1
p,m-Xylene	2.8132E+006	2.8189E+006	0.2%	ND	0.1
o-Xylene	1.1987E+006	1.2011E+006	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample Di	iplicate(s)	%DIff.	Accept Range	Detect: Limit
Benzene	4.7	4.6	2.1%	0 - 30%	0.9
Toluene	19.5	19.4	0.5%	0 - 30%	1.0
Ethylbenzene	2.3	2.2	4.3%	0 - 30%	1.0
p,m-Xylene	23.4	22.2	5.1%	0 - 30%	1.2
o-Xylene	15.4	15.3	0.6%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample : Amo	iunt Spiked Spik	red Sample	% Recovery	Accept Range
Benzene	4.7	50.0	52.7	96.3%	39 - 150
Toluene	19.5	50.0	68.2	98.1%	46 - 148
Ethylbenzene	2.3	50.0	50.3	96.2%	32 - 160
p,m-Xylene	23.4	100	118	95.9%	46 - 148
o-Xylene	15.4	50.0	67.8	104%	46 - 148

ND - Parameter not detected at the stated detection limit.

References

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996,

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 48422, 48423, 48435. 48445 - 48448, 48450, 48453, and 48454.

Analyst



Added, Physics Co.

Constant the Constant Personal Constant to the Constant C

gotar Petro (14:00:000) Paraza Aspec Decellores et al competitiones

The control of the co

State Worte Code German Communication Commun

Hamilest Pastingtion - 5 11

Profile Secondor

Out #4.03.3000 intopen Molecular Met Bridge Service Met Bridge Service Met Bridge Service Met Bridge Met Bridg

造功准数许约至多

FB.

 Oraduct
 100
 Pty
 ODF
 Base
 Tall
 Green't
 Integral

 1 Monthly Course
 100
 400
 accent
 100
 400
 accent
 100
 400
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600
 600

Hoss Gon # 97 Kuttegur 1 1 93-3

Hoss Com # 97

The set of the set of

The second section is a second

403WM

❽

Tw	omit To Appropro o Copies	riate Distri	ct Office		-		State of No											orm C-105	
162	<u>trict I</u> 5 N. French Dr.	., Hobbs, N	IM 88240	0	Energy, Minerals and Natural R				l Ke	sources		1. WELL	API	NO.			July 17, 2008		
130	<u>trict II</u> 1 W, Grand Ave trict <u> III</u>	enue, Arte	sia, NM	88210		Oi	l Conserva	ition	Div	isic	n		30-045-345						
100	unet III 0 Rio Brazos Re trict.IV	d., Aztec, ì	NM 8741	10			20 South S				r.		2. Type of Lease ☐ STATE ☐ FEE ☐ FED/INDIAN						
	0 S. St. Francis	Dr., Santa	Fe, NM	87505			Santa Fe, 1	NM	8750)5			3. State Oil & Federal Leas			lo.			
			LETI	ON OR	RECC	MPL	ETION RE	PO	RT A	NE	LOG				ALC:				
4.	Reason for fili	ing:											5. Lease Nam Hoss Com	ne or t	Jnit Agre	eement l	lame		
	COMPLETI	ION REF	PORT (Fill in boxe	s #1 throu	igh #31	for State and Fe	e well	ls only))			6. Well Numl	ber:					
#33	; attach this ar	nd the pla					ough #9, #15 D rdance with 19.					d/or	908						
		WELL [□ WOR	RKOVER [DEEPE	ENING	□PLUGBAC	к 🗀	DIFFE	EREN	NT RESER	VOIE					44.40		
	lame of Opera												9. OGRID 006515						
	Address of O												11. Pool name	or W	ildcat				
_	D. Box 420, F					la i a	I Dance	Lot		T	F 6	41-	N/S Line	L E	. C	e E/W	1	L C	
	Location face:	Unit Ltr	30	ection	Towns	mb	Range	Lot		Feet from the		ine	N/S Line	Fee	t from th	e E/W	Line	County	
BH	:				-			+		_				 -					
13.	Date Spudded	e Spudded 14. Date T.D. Reached 15. Da					Released 9/12/08			16.	Date Comp	letec	(Ready to Prod	luce)		17. Eleva RT, GR,		and RKB,	
18.	18. Total Measured Depth of Well				19, F	lug Bac	ck Measured De	pth	20. Was Directiona				al Survey Made?	,			e Electric and Other Logs Run		
22.	Producing Int	erval(s),	of this c	ompletion -	· Top, Bot	tom, Na	nme												
23.						CAS	ING REC	OR	D (R	epo	ort all st	rin	gs set in w	ell)			M. 1. 2. 2. 2. 1. 2. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.		
	CASING SIZ	ZE	W	EIGHT LB	/FT. DEPTH SET					HOLE SIZE CEME			CEMENTIN	CEMENTING RECORD AMOUNT PULLED				PULLED	
-																			
														7_					
-																			
24.						LIN	ER RECORD					25.			NG REC				
SIZ	<u> </u>	TOP		BC	MOTTO	·	SACKS CEM	ENT	SCR	EEN		SIZ	ZE	DI	EPTH SE	<u> ΣΓ</u>	PACK	ER SET	
26.	Perforation	record (in	ıterval,	size, and n	ımber)						D, SHOT. NTERVAL		ACTURE, CE AM OU NT A						
																-			
									-							,			
28.								PRO	ODU	C	TION	,	1						
Date	e First Produc	tion		Produc	tion Meth	od (Flo	owing, gas lift, p	umpin	ig - Size	e and	l type pump)	Well Status	(Proc	d. or Shu	t-in)			
Dat	e of Test	Цонга	Tested	16	oke Size		Prod'n For		Oil -	DM		Car	s - MCF	337	ater - Bb		T _{Gno.} (Dil Ratio ·	
Date	e or rest	Hours	restea	C	ioke Size		Test Period			BDI		Ga:	s - MCF	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ater - Bo	1.	Gas - C	ni Kalio -	
1	v Tubing	Casin	g Pressi		lculated 2	24-	Oil - Bbl.		 (Gas -	MCF	L	Water - Bbl.		Oil Gr	avity - A	PI - (Cor	r.)	
Pres	s. Disposition of	Gas (Sol	d. used		our Rate			,					·····	30. 1	est Witr	essed B	v		
	•																		
31.	List Attachme	ents																	
ı		-		-	-		e location of the	-											
33.	If an on-site b	urial was	used at	the well, re	port the e	xact loc	ation of the on-	site bu	rial:	72	3°10		07.96870	Le	>				
I he	ereby certif	y that th	he info	rmation .	shown o	n botk	Latitude sides of this	- 36	.2373 1		Longitud	e 10 lete	1.96885 to the best o	f my	knowle	NAD edge ar	1927 © id belief	مؤلا	
	nature /					I	Printed	-			•		dent, Explora	•			J		
ŀ	nail Addres			,		n.com													

District J 1625 N. French Dr., Hobbs, NM 88240

State of New Mexico Energy, Minerals & Natural Resources Department

Form C-102 Revised October 12, 2005 Instructions on back

District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

District IV 1220 S St. Francis Dr., Santa Fe, NM 87505

MENDED REPORT

3	API Numbe			'Pool Coo 71629	·	DA	Pool Nam SIN FRUITL			
*Property	Codo			/ 1025	Property		ZIN LHOTIF		ell Number	
Property	Code				HOSS			"	905	
'OGRID	No.				*Operator	Name		9	Elevation	
00651	.5			DUGAN	PRODUCTIO	CTION CORPORATION 6375				
					¹⁰ Surface	Location				
UL or lot no.	Section	Township	Range	Lot Idn					County	
Р	11	23N	11W		1285	S0UTH 1285		EAST	SAN JUAN	
			ottom	Hole L	ocation I		From Surf			
UL or lot no.	Section	Township	ship Range Lot Idn Feet from the North/South line Feet from the East		East/West line	County				
Dedicated Acres	320	.0 Acres	SSIGNE	O TO TH	13 Joint or Infill IS COMPLETI	14 Consolidation Code ON UNTIL ALL	¹⁵ Order No. INTERESTS H	AVE BEEN CO	NSOL IDATED	
16		UH A		380.98	UNII HAS BI	EEN APPROVED	I hereby con herein is thoushedge a either owns mineral int proposed botto drill the	ATOR CERT ertify that the infi rue and complete t and belief, and that belief, and that is erest in the land attom-hole location act with an owner of	ormation contained the best of my this organization to unleased including the or has a right cation pursuant	
					····	1	agreement c	interest, or to a variate compulsory pool entered by the divi	voluntarý pooling ling order	

52

5318.281

LAT: 36.23731 N LONG: 107.96885 W DATUM: NAD1983 1285'

center of pit

AND ESSIONAL

Survey Date: DECEMBER 4, 2007 Signature and Seal of Professional Surveyor

SON C. EDWARDS

Certificate Number

