

	23		
X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa FeLease No. SM-01487

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	
Notice of Intention to plug & abandon - X	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


October 12, 1956

Well No. NWP-Moran #1 Federal is located 660 ft. from EX line and 760 ft. from EX line of sec. 23.SW/4 SW/4 23 17N 6W NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat (Entrada) McKinley New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the ungr. grnd. surface above sea level is 6532 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 3912'. Ran Lane Wells Gamma Ray - Neutron logs. Propose to set 75 sx cement plug fr 3912 - 3750; 60 sx plug fr 3900 - 2875; 75 sx plug fr 2650 - 2500; 50 sx plug fr 1750 - 1650; 75 sx plug fr 550 - 400; 10 sx plug in top of 9 5/8" OD surf casing. Install prescribed marker and release rig.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Northwest Production CorporationAddress 520 Simms BuildingAlbuquerque, New MexicoBy RAY PHILLIPS
Ray PhillipsTitle Asst. Mgr. Production Operations

