

# MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
9"	7" O.D. 1535		40 sacks	plug		

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
 Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment. \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

### TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to 1570 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
 Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

### PRODUCTION

Put to producing July 5 1940 100  
 The production of the first 24 hours was 8 barrels of fluid of which xx % was oil; xxxx % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be 30.6  
 If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
 Rock pressure, lbs. per sq. in. \_\_\_\_\_

### EMPLOYEES

R. C. Wilson Driller \_\_\_\_\_ Driller  
C. Bond. Driller \_\_\_\_\_ Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 24 Albuquerque, N.M. Sept. 20, 1940  
 day of Sept. 1940 Name Glen W. Atterbury  
 Position President  
 Representing Petroleum Products Corporation  
 Address Thoreau, New Mexico  
 My Commission expires Jan 27 1944  
Notary Public  
Rec'd Sept. 30 1940