

(SUBMIT IN TRIPLICATE)


Indian Agency Window Rock

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Navajo

Allottee \_\_\_\_\_

Lease No. 14-2-403-1877



SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

AUG 10 1959

|   |  |                                     |
|---|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL _____                  | SUBSEQUENT REPORT OF WATER SHUT-OFF _____        |                                     |
| NOTICE OF INTENTION TO CHANGE PLANS _____           | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____ |                                     |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____    | SUBSEQUENT REPORT OF ALTERATIONS _____           |                                     |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____ | SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____  |                                     |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____       | SUBSEQUENT REPORT OF ABANDONMENT _____           | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO PULL OR ALTER CASING _____   | SUPPLEMENTARY WELL HISTORY _____                 |                                     |
| NOTICE OF INTENTION TO ABANDON WELL _____           |  |                                     |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 7, 1959

Well No. 1 is located 660 ft. from N line and 660 ft. from W line of sec. 20

18N  
(1/4 Sec. and Sec. No.)

18N  
(Twp.)

10W  
(Range)

R.M.P.M.  
(Meridian)

Seven Lakes  
(Field)

McKinley  
(County or Subdivision)


New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6493 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pumped a cement plug from 2700 feet to 2857, T.D., which is 30 feet in the Harrison Formation. Put a cement plug from 2490 feet to 2590 feet to plug off the Dakota. Put a cement plug from 1450 feet to 1550 feet to plug off the Hesperia Section of the Gallup Formation. Ran 950 feet of 4 1/2" casing to 950 feet and circulated cement to surface. Put plug at top of 4 1/2" casing and set regulation marker.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Neas Retailers, Inc.

Address 102 South Second Street

Artesia, New Mexico

By Flora Duke

Title Bookkeeper