



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Allottee _____

Lease No. 14-20-603-2676

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
JUL 30 1959
GEOLOGICAL SURVEY
NEW MEXICO

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 30, 1959

Well No. 2 -I7 is located _____ ft. from [N] line and _____ ft. from [E] line of sec. 17

SE -NW 1/4 -I7
(¼ Sec. and Sec. No.)

I9 N 5 W
(Twp.) (Range)

(Meridian)

Undesignated
(Field)

McKinley
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6618 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 6 3/4" hole to T.D. 4329' w/Rotary tools. Cased w/^{5 1/2}9 I 1/2" J55 casing to 4320'. Cemented w/250 sacks. Top Cement 2700'. Perf. at 4286' to 4296'. Set Bridge Plug at 2400'. Perf. 2375'. Re-Cemented w/200 sacks 10 % Gel. Pumped Plug to 2100'. Left 275' Cement in Casing. Top of Cement 800'. Cemented Top hole Marker w/10 sacks.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Douglas Corporation -Caswell Silvers

Address 327 Denver U S Nat'l.

Bank Bldg.

Denver, Colorado

By Harmer Allen

Title Field Supt.