



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office ST
Lease No. 079478
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 27, 1960

Well No. 2-A-7 is located 330 ft. from RTK line and 230 ft. from E line of sec. 7.

SE 7 (1/4 Sec. and Sec. No.) 19N (Twp.) SW (Range) N.M. (Meridian)
Star Lake (Field) McKinley (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6637 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TOTAL DEPTH 3450

It is planned to plug and abandon this well by cementing all perforations.

Leave top of cement at least fifty feet above uppermost perforations.

A marker will be erected per regulations.
The casing will be cemented 1450-3300. Mud will fill hole to 2250. Cement 2250-1900. Cement 1900-100. 10 sz plug in top of hole.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Goddie Mining Company

Address Suite 1500

Mile High Center

Denver, Colorado

By John K. Petty

Title John K. Petty
Consulting Geologist
Farmington, New Mexico

[illegible]