


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 079181

Unit RECEIVED



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT..... X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 16, 1957

Federal

Well No. 12-8 is located 1650 ft. from N line and 1650 ft. from E line of sec. 8

SW NE SW, Sec. 8

($\frac{1}{4}$ Sec. and Sec. No.)

19N

(Twp.)

5W

(Range)

N. M. P. M.

(Meridian)

Wildcat

(Field)

McKinley

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6617 ft. D. F.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was drilled from surface to total depth of 2200' with rotary tools. Surface casing (8 5/8" 38#, 8 Rd., J55) was set at 37.15' below K. B. with 25 sacks of cement. Hole was dry and plugged with 50' cement plug 2075'-2125', 50' cement plug at 750'-800', and 4' cement marker set at surface.

RECEIVED
MAR 3 1958
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Caswell Silver and Douglas Corporation

Address 323 Simms Building

Albuquerque, New Mexico

By _____

Title Operator