

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well OIL	<b>RECEIVED</b> MAR 13 1998	API # (assigned by OCD) 30-031-05358
2. Name of Operator Geo Engineering	<b>OIL CON. DIV.</b> DIST. 3	5. Lease Number Fee
3. Address & Phone No. of Operator P.O.Box 2966 Santa Fe, NM 87505		6. State Oil & Gas Lease #
4. Location of Well, Footage, Sec., T, R, M Sec. 29, T-20-N, R-9-W, NMPM, McKinley County Unit B, 300' FNL and 1800' FEL		7. Lease Name/Unit Name Santa Fe Pacific
		8. Well No. #20
		9. Pool Name or Wildcat
		10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

A-Plus Well Service, contractor, plugged and abandoned said well according to the attached Daily Report.

This work was completed under State of New Mexico Contract No. 98-521.25-059.

SIGNATURE William F. Clark Contractor  
William F. Clark

March 4, 1998

(This space for State Use)

Approved by Johnny Robinson

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Title

Date

MAR 13 1998

## Daily Report

## A - PLUS WELL SERVICE

P.O. BOX 1979 • FARMINGTON, NM 87499  
505-325-2627 • FAX (505) 325-1211

Rig No 6-7Date 2/13/98Well No Sanita Fe Pacific #20 Location (B) 29-20-9WCompany Geo Engineering

FROM	TO	DESCRIPTION OF OPERATION
2/13/98		
1:15	1:30 PM	move to Well set up PT & WL
1:30	1:45 PM	Run WL in 2" csg to 440 Tag.
1:45 PM	2 PM	Pump down 2" csg. couldn't pump in to Port or open Hole Pressured up to 500 PSI Holding.
2 PM	2:15 PM	Perf 1 Hole At 300' w/ 1 1/16 Biwire shot
2:15	2:30	Pump in to Perf at 300' at 1 BPM at 300 PSI Pump SBL
2:30	2:45	Plug #1 Mix 25 SX well Pressured up to 500 PSI & Holding After Mixing 25 SX Bleed off PSI well setting Full no circulation Baking 2" csg.
2:45		Perf 1 Hole w/ 1 1/16 Biwire shot at 30'
		Pump in to Perf at 0 PSI w/ 5 BBL water. No circulation Behind 2" csg Plug #2 Mix 20 SX cement at 15.4 #
		Pump in to Perf at 30 FT no circulation shut Well in Wash up PT open Well standing Full set Dry Hole
3:30		Mark SDF Weekend

Fuel &amp; Motor Oil \_\_\_\_\_

Water Hauled \_\_\_\_\_

Rental Equipment \_\_\_\_\_

Cement Retainers \_\_\_\_\_

Cementing Plug #1 25 SX Plug #2 20 SXWireline 1-Hole At 300' w/ 1 1/16 Biwire shot, 1-Perf At 30' w/ 1 1/16 Biwire shot