State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division

Sundry Notices and Reports on Wells						
				API i	# (assigned by OCD)	
1.	Type of Well OIL			5.	Lease Number Fee	
				6.	State Oil & Gas Lease #	
2.	Name of Operator Geo Engineering			7.	Lease Name/Unit Name Santa Fe Pacific	
3.	Address & Phone No. of Operato	r		8.	Well No. #3	
	P.O.Box 2966 Santa Fe, NM 87505			9.	Pool Name or Wildcat	
4.	Location of Well, Footage, Sec., Sec. 20 T-20-N, R-9-W, NMPM, Munit O, 657 FSL and 1718 FEL	McKinley County		10.	Elevation:	
	Type of Submission	Type of Action				
	X Notice of Intent	X Abandonment	Change of Pl			
		Recompletion	New Constru			
	Subsequent Report	Plugging Back	Non-Routine		cturing	
	Fig. 1 About to a cont	Casing Repair	Water Shut of			
	Final Abandonment	Altering Casing Other -	Conversion to	o Inje	ection	
13.	A-Plus Well Service, contract procedure prepared by NMO This work will be in accordant	tor, will plug and aband				
					DECEIVED N 2 2 1998	
SIC	GNATURE William F. Clark	Contractor	December 30), 199	970IL CON. DIV. DIST. 3	
•	proved by Shary Robins	nson DEPUTY OIL &	GAS INSPECTOR, DIST	±43 ate _	JAN 2 2 1998	

COMPANY		PROPERTY NAME		
(7	ep Engineering	Sante	Ee Pacific	WELL NO.
DATE	1		POOTAGE	
API NO.	1 0-20-20N-090	XX.		
		XL		
		سنجسجان استنبائك		-
			1	Γ
				İ
	Found 5-20-9	7: No 4: +		
	2" line pipe	i a Sul		
	icon programme		-	
CASING REC	CORD:			
	2" csg.	?		
	\mathcal{C}	•		
	۸	,		
	No Reco	inds		
		•		
	IN Tec	tion.		
	<u>@</u>			
	701		.[
	X [0			
	name(it is no victor motion to Alberta to Sub-			
			4	•
			 	

:

COMPANY	PROPERTY NA	MP	
(7)	eo Engineering San	te Fe Pacific	WELL NO.
DATE	LOCATION (ULSTR)	POOTAGE	
API NO.	0-20-20N-09W		
API NO.	POOL		
		q	r
	Found 5-20-97 Workers	tora	
			i
			l i
			
<u></u> -			
Casing Rec	XORD:		
!	d'' csg.		
	9		
	No Records		
1. D	etermine depth		
I	fdepth is 300' or more continue		
W	ith procedure if not move rig in to	lean	·
0.0	~, 454.		(300'
L. P.	erf. @ 300'430'	()), T.O.C.
بع . م	stablish cine. to the sunface if po	ssuble)	
7.61	H with slick line + load hala will)/
	· MCKT	1 \ \ \ \ \ \	1((
4 . P	of with slick line + sump cement sq. + cinc, cement	, ()	(')
С	sq. teinc. cement to the surface	a. wh	500'
5.1	Install dry hole manker	e 4	
	y manker		2' csa.
			Ŭ
			il i