

NO. OF COPIES RECEIVED	9
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Walker Bros. Oil Company	8. Farm or Lease Name Santa Fe
3. Address of Operator P.O. Box 776, Durango, Colorado 81301	9. Well No. 8
4. Location of Well UNIT LETTER L 330 FEET FROM THE West LINE AND 5040 FEET FROM THE South LINE, SECTION 7 TOWNSHIP 17N RANGE 8W NMPM.	10. Field and Pool, or Wildcat South Hespah Lower Sand Oil Pool
15. Elevation (Show whether DF, RT, GR, etc.) 7023 KB	12. County McKinley

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input checked="" type="checkbox"/> Complying with NMOCC Order No.R-3170x	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sand-packed perforations at 1661 feet capped with Calseal (10 feet sand, 5 gallon Calseal). Squeezed upper Hespah sand perforation IN 1599 - 1600, 1602 - 1604, 1612 - 1616, 1625 - 1629, 1637 - 1641. Packer set at 1572 feet Mixed 50 sacks cement. Squeezed to 1000 pounds. Let set 72 hours, drilled out and washed perforations at 1661 feet. Ran rods and tubing and put on pump. Pump rate 12 bbls. oil per day, 80 bbls. water. Well is presently producing from the South Hespah Lower Sand only. Work performed 4-1-67 to 4-8-67.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Virginia Carmichael*
APPROVED BY *Arthur E. Gaudin*
CONDITIONS OF APPROVAL, IF ANY:

TITLE **Secretary**

DATE **4-18-67**

DISTRIBUTION ENC WITH MAIL NO. 3

TITLE

DATE

APR 19 1967