

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Shelly Oil Company		Santa Fe "B"
3. Address of Operator		9. Well No.
P. O. Box 730 - Hobbs, New Mexico		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER "P" , 640 FEET FROM THE South LINE AND 835 FEET FROM		Hospah-Gallup
THE East LINE, SECTION 6 TOWNSHIP 17-N RANGE 9-W NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
6813' GR		McKinley


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been drilled to a total depth of 1661' with no quantities of oil or gas being encountered in any zone. We now plan to plug and abandon this well in the following manner:

1. Spot 30-sack cement plug from 1600' to 1459'.
2. Spot 30-sack cement plug from 436' to 295'.
3. Place 10-sack cement cap in top of 7"OD casing and install 4" steel dry hole marker.
4. All intervals not cemented were filled with heavy mud laden fluid.

NOTE: Verbal approval was given.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **(ORIGINAL SIGNED) H. E. Aab** TITLE **District Superintendent** DATE **July 12, 1966**

Original Signed by A. R. Kendrick PETROLEUM ENGINEER DIST. NO. 3 DATE **JUL 14 1966**

CONDITIONS OF APPROVAL, IF ANY: