

GOVERNOR  
JOHN BURROUGHS  
CHAIRMAN

State of New Mexico  
Oil Conservation Commission

LAND COMMISSIONER  
MURRAY E. MORGAN  
MEMBER



STATE GEOLOGIST  
A. L. PORTER, JR.  
SECRETARY DIRECTOR

1000 RIO BRAZOS ROAD  
AZTEC

December 6, 1960

Sinclair Oil & Gas Company  
Denver Club Building  
Denver 2, Colorado

Attn: Mr. Ford Haskins  
Asst. Division Supt.

Re: Santa Fe 103 Miguel, SE $\frac{1}{4}$  Section  
20-16N-6W, McKinley County, N.M.

Dear Sir:

Reference is made to your letter of November 28, 1960 regarding plugging instructions for the above well.

From reviewing the well record previously filed on this well it appears that 5 $\frac{1}{2}$ " production casing was cemented at total depth, which was 1030 feet with 250 sacks of cement. You have not indicated in your letter whether it is your intention to pull any 5 $\frac{1}{2}$ " casing. If this is your intention we would request that the perforations in the 5 $\frac{1}{2}$ " be squeezed with cement and that sufficient cement be left in the casing to extend above the perforations. Another 50' cement plug should be set at the top of the 5 $\frac{1}{2}$ " casing stub and another cement plug should be placed in the top of the surface casing. A pipe marker should be installed extending at least 4 feet above ground level, the pits should be filled and the location levelled.

If further instructions are needed, please contact us.

Yours very truly

ECA:ks

Emery C. Arnold  
Supervisor, District #3