

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-108
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - M" (FORM C-101) FOR SUCH PROPOSALS.)


1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Tesoro Petroleum Corporation		8. Farm or Lease Name Santa Fe R.R.
3. Address of Operator 8520 Crownhill Boulevard, San Antonio, Texas 78209		9. Well No. 10
4. Location of Well UNIT LETTER <u>B</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>17N</u> RANGE <u>8W</u> NMPM.		10. Field and Pool, or Wildcat South Hospah-Upper Sand
11. Elevation (Show whether DE, RT, GR, etc.) 6908' RKB 6904' GL		12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/> (Plug back)	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 6-16-70: Cleaned 1588' - 1602' RKB. Set Halliburton C.I. retainer at 1585'. Squeezed Lower Hospah Sand with 30 sacks common cement to 1400#. Left 2' cement on retainer. P.B.T.D. 1583' RKB.
- 6-18-70: Ran Collar Log and perforated Upper Hospah Sand with 64 holes, 4/ft., 1541'-44'; 1550' - 55'; 1558' - 62'; 1565' - 69'. Ran 2-cup packers and pumped 1/2 bbl. 15% HCl acid into each foot of perforations w/1000#.
- 6-19-70: Swabbed well. Ran completion tubing.
- 7-7-70: Ran rods and pump.
- 7-8-70: Put on production.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>July 28, 1970</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>SUPERVISOR DIST. #3</u>	DATE <u>AUG 3 1970</u>
CONDITIONS OF APPROVAL, IF ANY:		