

CONFIDENTIAL

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry hole	7. Unit Agreement Name
2. Name of Operator Kerr-McGee Corporation	8. Farm or Lease Name Santa Fe
3. Address of Operator P.O. Box K, Sunray, Texas 79086	9. Well No. 1
4. Location of Well UNIT LETTER P 827.5 FEET FROM THE South LINE AND 742.7 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 15N RANGE 19W NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 6,434' GR	12. County McKinley

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugging operation began 4-3-67 and were completed at 3 AM 4-4-67. The following cement plugs were placed through drill pipe. Plug No.1 from 3640' to 3740' with 35 sacks cement. Plug No.2 from 3250' to 3350' with 35 sks cement. Plug No.3 240' to 370' with 55 sks cement. Plug No.4 at top of surface casing with 5 sks cement. 9.5#/ gallon mud left between plugs. Surface casing 13 3/8" OD, 48#/Ft, H-40, ST&C casing set at 277' RKB, left in hole. Dry hole marker placed on well.

PLEASE KEEP INFORMATION CONFIDENTIAL.

CONFIDENTIAL



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. C. Baird, Jr. TITLE Engineer DATE 4-20-67

APPROVED BY Emory C. Arnold TITLE Asst. Dir. Sub DATE 7-18-67

CONDITIONS OF APPROVAL, IF ANY: