

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tesoro Petroleum Corporation	8. Farm or Lease Name Santa Fe Railroad
3. Address of Operator 533 Busby Drive, San Antonio, Texas 78209	9. Well No. 73
4. Location of Well UNIT LETTER O 330 FEET FROM THE South LINE AND 2000 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 17N RANGE 9W NMPM.	10. Field and Pool, or Wildcat South Hospah Lower Sand
15. Elevation (Show whether DF, RT, GR, etc.)	12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Rigged up and spudded well on March 12, 1967. Drilled 12-1/4" surface hole and set 63' 8-5/8" 24# casing and cemented with 40 sax common cement with 2% calcium chloride. Cement circulated. Drilled out from under surface pipe on March 16, 1967. Drilled to 1652' and ran Schlumberger I. E. S. Log to 1645' RKB. Ran 1647' 4-1/2" 9.5# casing and set at 1647' RKB. Cemented with 75 sax Class "C" cement - good circulation during cementing. On March 20, 1967 picked up core barrel and cored from 1652 - 1665'. Recovered 14' good oil sand. Ran 1606' 2-3/8" EUE tubing and released rig at 11:00 a.m. March 21, 1967.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Harold Vagthor Jr.</u>	TITLE <u>Vice President</u>	DATE <u>March 27, 1967</u>
APPROVED BY <u>Emory C. Cundiff</u>	TITLE <u>SUPERVISOR DIST. #3</u>	DATE <u>MAR 28 1967</u>
CONDITIONS OF APPROVAL, IF ANY:		

