

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION



Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. -

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -
2. Name of Operator Tesoro Petroleum Corporation	8. Farm or Lease Name Santa Fe Railroad
3. Address of Operator 533 Busby Drive, San Antonio, Texas 78209	9. Well No. 12
4. Location of Well UNIT LETTER D 330 FEET FROM THE West LINE AND 330 FEET FROM THE North LINE, SECTION 7 TOWNSHIP 17N RANGE 8W NMPM.	10. Field and Pool, or Wildcat South Hospah Lower Sand
15. Elevation (Show whether DF, RT, GR, etc.) 6919' G.L. 6927' RKB	12. County McKinley

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded 10:30 p.m. Aug. 25, 1967. Drilled 12-1/4" hole to 72.42 RKB, ran 8-5/8" 24# J-55 casing and set at 64.42' G.L. Cemented with 40 sacks common cement with 2% calcium chloride. Cement circulated to surface.

Drilled 7-7/8" hole to 1550' RKB and ran Schlumberger electric log to 1549'. Went in hole and drilled to 1562' RKB.

Ran 48 joints (1561') 5-1/2" 14# J-55 casing set at 1553' G.L. Cemented with 60 sacks Class "C" cement. Plug down 3:00 p.m. August 28, 1967. Waited on cement 24 hours. Drilled out cement. Changed mud system to oil and drilled 4-3/4" hole to 1569' RKB. Released rig at 10:00 p.m. August 29, 1967.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harold Vaytberg Jr. TITLE Vice President DATE Sept. 5, 1967
APPROVED BY Emory C. Cline TITLE SUPERVISOR DIST. #3 DATE SEP 8 1967
CONDITIONS OF APPROVAL, IF ANY: