

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)


1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tesoro Petroleum Corporation	8. Farm or Lease Name Santa Fe Railroad
3. Address of Operator 533 Busby Drive, San Antonio, Texas 78209	9. Well No. 14
4. Location of Well UNIT LETTER D 330 FEET FROM THE North LINE AND 990 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 17N RANGE 8W NMPM.	10. Field and Pool, or Wildcat South Hospah Lower Sand
15. Elevation (Show whether DF, RT, GR, etc.) 6908' G.L. 6916' RKB	12. County McKinley

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded 8:15 p.m. 9/26/67. Drilled 12-1/4" hole to 70' RKB. Ran 2 joints 8-5/8" 24# J-55 surface casing and set at 60.58' G.L. Cemented with 40 sacks common cement with 2% calcium chloride. Cement circulated. Job completed at 11:30 p.m. 9/26/67.

Drilled 7-7/8" hole to 1553' and ran Schlumberger electric log. Deepened to 1559' RKB and ran 48 joints 5-1/2" 14# J-55 casing and set at 1562' RKB. Cemented with 60 sacks Class "C" cement. Plug down 5:00 a.m. 9/28/67. Released rig.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harold Vagthoug Jr TITLE Vice President DATE Oct. 9, 1967

APPROVED BY Emmy C. Cliver TITLE SUPERVISOR DIST. #3 DATE OCT 11 1967

CONDITIONS OF APPROVAL, IF ANY: