

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Tesoro Petroleum Corporation</b>	8. Farm or Lease Name <b>Santa Fe Railroad</b>
3. Address of Operator <b>533 Busby Drive, San Antonio, Texas 78209</b>	9. Well No. <b>13</b>
4. Location of Well UNIT LETTER <b>D</b> , <b>330</b> FEET FROM THE <b>West</b> LINE AND <b>930</b> FEET FROM THE <b>North</b> LINE, SECTION <b>7</b> TOWNSHIP <b>17N</b> RANGE <b>8W</b> NMPM.	10. Field and Pool, or Wildcat <b>South Hospah Lower Sand</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6930' G.L. 6938' RKB</b>	12. County <b>McKinley</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐


REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 6:00 p.m. 10/1/67. Drilled 12-1/4" hole and set 2 joints 8-5/8" 24# surface pipe at 69' RKB, 61' G.L. Cemented with 40 sacks common cement with 2% calcium chloride. Cement circulated. Job completed 10:45 p.m. 10/1/67.

Drilled 7-7/8" hole to 1554' and ran Schlumberger electric log. Drilled to 1576' and ran 49 joints 5-1/2" 14# J-55 casing and set at 1576' RKB, 1568' G.L. Cemented with 60 sacks Class "C" cement. Plug down 10:45 p.m. 10/3/67. Released rig.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Harold Vaytberg Jr.</u>	TITLE <u>Vice President</u>	DATE <u>Oct. 9, 1967</u>
APPROVED BY <u>Curry C. Ames</u>	TITLE <u>SUPERVISOR DIST. #3</u>	DATE <u>OCT 11 1967</u>
CONDITIONS OF APPROVAL, IF ANY:		