

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 052931

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanson

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

South Hospah Lower Sand

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6.

Twp 17N, R8W, NMPM

12. COUNTY OR PARISH 13. STATE

McKsley New Mexico

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Tesoro Petroleum Corporation

3. ADDRESS OF OPERATOR
533 Busby Drive, San Antonio, Texas 78209

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2040' FSL and 1660' FWL

14. PERMIT NO.
Approved 9/6/67

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6888' G.L., 6896' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

Commencement of drilling
(NOTE: Report results of multiple completion on Well
Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded 3:45 a. m. 10/7/67. Drilled 12-1/4" hole and set 2 joints 8-5/8" 24# surface casing at 63' G.L. Cemented with 40 sacks common cement. Cement circulated.

Drilled 7-7/8" hole to 1535' RKB and ran Schlumberger induction log to 1536' RKB. Went in hole and drilled to 1541' RKB.

Ran 48 joints 5-1/2" 14# J-55 casing and set at 1541' RKB. Cemented with 60 sacks Class "C" cement. Plug down 4: 20 a. m. 10/9/67. Released rig.



RECEIVED

OCT 20 1967

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED Harold Vestberg TITLE Vice President

DATE Oct. 17, 1967

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or other wise; depths (top and bottom) and method of placement of cement plugs; and/or other material placed below, between and above plugs; amount, size, method of parting, of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965-O-688229

687-951

