

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator <b>Tesoro Petroleum Corporation</b>		8. Farm or Lease Name <b>Santa Fe</b>
3. Address of Operator <b>533 Busby Drive, San Antonio, Texas 78209</b>		9. Well No. <b>16</b>
4. Location of Well UNIT LETTER <b>C</b> , <b>330</b> FEET FROM THE <b>North</b> LINE AND <b>2310</b> FEET FROM THE <b>West</b> LINE, SECTION <b>7</b> TOWNSHIP <b>17N</b> RANGE <b>8W</b> NMPM.		10. Field and Pool, or Wildcat <b>Undesignated</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6913 Gr. 6922 KB</b>		12. County <b>McKinley</b>


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 10/23/68. Drilled 12-1/4" hole and set 128' of 8-5/8" J-55, 24# casing at 137. Cemented with 100 sacks Class "A" cement with 2% Calcium Chloride.

Drilled out from under surface pipe and drilled 7-7/8" hole to 2460'. Began coring at 2460 and cored solid to TD 2708. Set 5-1/2" 15.5#, J-55 pipe at 2571 RKB and cemented with 100 sacks Class "A" cement with 2% Calcium Chloride.

Now preparing to perforate for completion in Dakota.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. H. Newman TITLE Petroleum Engineer DATE 11/8/68

APPROVED BY Emily Clark TITLE SUPERVISOR DIST. #3 DATE NOV 12 1968  
CONDITIONS OF APPROVAL, IF ANY: