

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tesoro Petroleum Corporation	8. Farm or Lease Name Santa Fe
3. Address of Operator 8520 Crownhill Boulevard, San Antonio, Texas 78209	9. Well No. 57
4. Location of Well UNIT LETTER J 2330 FEET FROM THE East LINE AND 1620 FEET FROM THE South LINE, SECTION 1 TOWNSHIP 17N RANGE 9W NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 6952' GR 6960' RKB	12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☒
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 7-29-69. Ran 4 joints of 8-5/8" 24# J-55 surface pipe and set at 135' RKB. Cemented with 110 sacks Class "A" cement with 2% CaCl. Drilled, cored and logged through the Morrison to total depth of 2800' RKB. Evaluation of cores and log indicated possible completion in Second or Third Bench of Dakota to be of doubtful commercial value and it was decided to plug back to the Upper Hospah. Spotted cement plug from 2800' to 2450' and 15-sack plug from 1800' to 1750'. Set 54 joints of 5-1/2" 15.5# J-55 casing (1686.81') at 1697.61' RKB with 140 sacks Class "A" cement with 2% CaCl. Will perforate for completion along with Santa Fe No. 56.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

[Signature]

TITLE **Petroleum Engineer**

DATE **August 11, 1969**

APPROVED BY

[Signature]

TITLE **SUPERVISOR DIST. #3**

DATE

AUG 14 1969

CONDITIONS OF APPROVAL, IF ANY: