

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee <u>411</u> (Schl)	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos <u>705</u> (Schl)	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup <u>1631</u> (Schl)	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota <u>2522</u> (Schl)	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison <u>2764</u> (Schl)	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Schlumberger measurements:							
0	135	135	Surface dirt, sand and gravel				
135	411	276	Shale and sandy shale				
411	705	294	Sand and sandy shale				
705	940	235	Shale				
940	1400	460	Sand and sandy shale				
1400	1631	231	Shale				
1631	1830	199	Sand w/shale streaks				
1830	2522	692	Shale				
2522	2537	15	Hard sand - First Bench - Dakota				
2537	2600	63	Shale				
2600	2620	20	Hard sand - Second Bench - Dakota				
2620	2658	38	Shale				
2658	2690	32	Hard sand - Third Bench - Dakota				
2690	2764	74	Shale				
2764	2800	36	Medium grained water sand.				