

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | 3 |
| DISTRIBUTION | |
| SANTA FE | 1 |
| FILE | 1 |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | 1 |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| |
|--|
| 5a. Indicate Type of Lease |
| State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> |

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT..." (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- | 7. Unit Agreement Name |
| 2. Name of Operator Tesoro Petroleum Corporation | 8. Farm or Lease Name Santa Fe R. R. "A" |
| 3. Address of Operator 8520 Crownhill Boulevard, San Antonio, Texas 78209 | 9. Well No. 80 |
| 4. Location of Well UNIT LETTER P 1310 FEET FROM THE East LINE AND 630 FEET FROM THE South LINE, SECTION 1 TOWNSHIP 17N RANGE 9W NMPM. | 10. Field and Pool, or Wildcat South Hospah-Lower Sand |
| 15. Elevation (Show whether DF, RT, GR, etc.) 6993' GR 7005' RKB | 12. County McKinley |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐


PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER Drilling and completion ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 12-12-69: Ran 2 joints of 8-5/8" surface pipe and cemented at 62.5' GR with 50 sacks common cement with 2% CaCl.
- 12-14-69: Drilled out from under surface pipe and drilled to 1613' RKB.
- 12-16-69: Ran Induction Electric Log. Set 5 1/2" 14# K-55 casing at 1612' RKB with 100' rotating scratchers, Larkin float and guide shoe. Cemented at 1612' RKB with 100 sacks common cement plus 2% CaCl.
- 12-17-69: Moved in completion rig. Loaded hole with Lower Hospah crude and drilled cement plug and formation to total depth of 1622' RKB. Ran Gamma Ray-Neutron Log to T. D. 1622' RKB. Preparing to run tubing, rods, and put on pump.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. A. Linman TITLE Petroleum Engineer DATE January 6, 1970

APPROVED BY [Signature] TITLE SUPERVISOR DIST. #8 DATE JAN 9 - 1970

CONDITIONS OF APPROVAL, IF ANY: