

NEW MEXICO OIL CONSERVATION COMMISSION

Form O-100
Revised 1-1-68
Effective 1-1-68
Approved 1-1-68

3

1

1

SUPPLY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR WELLS WHICH ARE NOT PRODUCING OR ARE NOT BEING PRODUCED BY THE OIL CONSERVATION COMMISSION. USE APPROPRIATE FORM FOR WELLS WHICH ARE PRODUCING OR ARE BEING PRODUCED BY THE OIL CONSERVATION COMMISSION.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Lessee
Tesoro Petroleum Corporation

3. Address of Lessee
8520 Crownhill Boulevard, San Antonio, Texas 78209

4. Name of Well

UNIT LIES IN F 2010 FEET FROM THE West LINE AND 1800 FEET FROM

THE North LINE, SECTION 7 TOWNSHIP 17N RANGE 8W NMPM.

5. Elevation (Surface and other BP, RT, GR, etc.)

6980' GL 6992' RKB

6. Indicate Type of Lease

7. Date ☐ Day ☒

8. State (If A. Gas Lease No.)

9. Unit Agreement Name

10. Form or Lease Name

Santa Fe R.R.

11. Well No.

20

12. Field and Pool, or Vildet

South Hospah-Upper Sand

13. County

McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OF ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

REMEDIATION WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe in brief or Complete Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1102.

Spudded 10:30 AM 4-22-70. Drilled 12-1/4" hole to 76' RKB. Set two joints 8-5/8" 24# H-40 ST&C surface casing at 75' RKB with 50 sacks common cement plus 2% CaCl. Cement circulated to surface.

Drilled 7-7/8" hole to 1614' RKB and ran Schlumberger IES Log.

Ran 49 joints 5-1/2" 14# K-55 casing with Larkin float shoe and Larkin coupling insert float in top of bottom joint, 4 short bow latch-on centralizers, and 50' rotating scratchers. Set at 1605' RKB with 100 sacks common cement. Plug down at 7:50 PM 4-23-70.

Preparing to drill in with power swivel for open hole completion.

NOTE AMENDED LOCATION.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N. H. Denman

TITLE Petroleum Engineer

DATE April 29, 1970

APPROVED BY [Signature]

TITLE SUPERVISOR DIST. #3

DATE MAY 4 1970

CONDITIONS OF APPROVAL, IF ANY: